



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 226 (2.8 GHz Xeon, 2MB L2 Cache)

SPECfp2000 = 1594

SPECfp_base2000 = 1569

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jul-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	71.4	2241	71.4	2241	
171.swim	3100	136	2286	136	2285	
172.mgrid	1800	144	1246	144	1246	
173.applu	2100	159	1318	157	1338	
177.mesa	1400	114	1230	114	1231	
178.galgel	2900	99.0	2929	99.0	2929	
179.art	2600	68.5	3796	68.5	3796	
183.quake	1300	64.9	2002	53.2	2446	
187.facerec	1900	117	1619	117	1618	
188.amp	2200	212	1037	212	1037	
189.lucas	2000	107	1864	107	1875	
191.fma3d	2100	167	1259	167	1259	
200.sixtrack	1100	198	556	198	556	
301.apsi	2600	239	1086	239	1086	

Hardware

CPU: Intel Xeon 2.8 GHz (800 MHz system bus)
CPU MHz: 2800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12K(I) micro-ops + 16KB(D) on chip
Secondary Cache: 2048KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 4 x 2048 MB ECC PC2-3200 Single Rank
Disk Subsystem: 73GB SCSI 15K RPM
Other Hardware:

Software

Operating System: Windows Server 2003 Standard Edition
Compiler: Intel C/C++ Compiler 9.0 (20050624Z) for 32-bit applications
Intel Fortran Compiler 9.0 (20050624Z) for 32-bit applications
Microsoft Visual Studio .NET 13.0.9466 (for libraries)
MicroQuill Smartheap Library 7.30
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY

178.galgel: -FI /F3200000
191.fma3d: srcalt=windowsdp

BASE TUNING

C/F77/F90: -fast -Qansi_alias +FDO

PEAK TUNING

168.wupwise: basepeak=yes
171.swim: -fast -f77rtl +FDO
172.mgrid: basepeak=yes
173.applu: -fast -Qscalar_rep- -Qauto -f77rtl +FDO
177.mesa: -fast +FDO
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO shlw32M.lib



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

IBM Corporation

IBM eServer xSeries 226 (2.8 GHz Xeon, 2MB L2 Cache)

SPECfp2000 = 1594

SPECfp_base2000 = 1569

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Aug-2005 | Hardware Avail: Sep-2005 | Software Avail: Jul-2005

Notes/Tuning Information (Continued)

```
187.facerec: -fast -Qunroll11 -Qscalar_rep- +FDO
188.amp: basepeak=yes
189.lucas: -fast
191.fma3d: basepeak=yes
200.sixtrack: -Qipo +FDO
301.apsi: basepeak=yes
```