



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 254

SPECint2000 = 1918
SPECint_base2000 = 1763

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	91.4	1532	91.4	1532	
175.vpr	1400	95.4	1467	93.1	1504	
176.gcc	1100	53.8	2043	54.1	2034	
181.mcf	1800	154	1166	128	1405	
186.crafty	1000	55.6	1797	50.7	1971	
197.parser	1800	104	1724	104	1724	
252.eon	1300	60.0	2168	42.6	3054	
253.perlbnk	1800	100	1795	92.0	1956	
254.gap	1100	57.0	1931	57.0	1931	
255.vortex	1900	68.0	2792	63.4	2997	
256.bzip2	1500	105	1433	103	1463	
300.twolf	3000	166	1808	137	2184	

Hardware

CPU: AMD Opteron (TM) 254 processor (2.80 GHz)
 CPU MHz: 2800
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD on chip
 Secondary Cache: 1024KB (I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2048MB DDR-RAM PC3200R
 Disk Subsystem: Western Digital WD2500 (SATA, 7.2krpm)
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1
 Compiler: Intel C++ 8.0
 Build 20040318Z (for 32-bit applications),
 Microsoft Visual Studio .Net 2003
 7.1.3088 (for libraries),
 SmartHeap Library Version 8.0
 from <http://www.microquill.com>
 File System: NTFS
 System State: Default

Notes/Tuning Information

GENERAL

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Portability flags

176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

Base tuning flags

for C programs: -fast -arch:SSE2 -Oi- +FDO
 for C++ programs: -fast -GX -GR +FDO

Peak tuning flags

164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000,
 -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO shlw32M.lib
 181.mcf: -fast -QaxN +FDO shlw32M.lib
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes shlw32M.lib



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMERGY RX220, AMD Opteron (TM) 254

SPECint2000 = 1918
SPECint_base2000 = 1763

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jan-2006 | Hardware Avail: Dec-2005 | Software Avail: Mar-2005

Notes/Tuning Information (Continued)

```
197.parser: basepeak=yes
252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes shlw32M.lib
253.perlbnk: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes shlw32M.lib
254.gap: basepeak=yes
255.vortex: -fast -arch:SSE -Oi- -Qoption,c,-ip_ninl_max_stats=2000,
        -ip_ninl_max_total_stats=4500 +FDO shlw32M.lib
256.bzip2: -fast -Qunroll2 shlw32M.lib
300.twolf: -fast -arch:SSE2 -Qansi_alias +FDO ONESTEP=yes shlw32M.lib
```

'start /b /wait /affinity' command is used to bind CPU(s) to processes

```
boot options: /Execute
              /NOPAE
              /USEPMTIMER
```

BIOS settings: Memory timing=1T

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>