



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1955 (Intel Xeon processor 5050, 3.00GHz)

SPECint\_rate2000 = 41.6

SPECint\_rate\_base2000 = 41.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	4	182	35.7	4	190	34.1
175.vpr	4	239	27.2	4	209	31.0
176.gcc	4	85.9	59.4	4	85.9	59.4
181.mcf	4	322	25.9	4	322	25.9
186.crafty	4	149	31.2	4	157	29.5
197.parser	4	226	37.0	4	207	40.3
252.eon	4	92.5	65.2	4	93.2	64.8
253.perlbnk	4	158	52.9	4	158	52.9
254.gap	4	92.3	55.3	4	120	42.5
255.vortex	4	137	64.5	4	137	64.5
256.bzip2	4	223	31.3	4	202	34.4
300.twolf	4	327	42.6	4	327	42.6

### Hardware

CPU: Intel Xeon processor 5050 (667MHz system bus)  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip (Hyper-Threading Technology enabled)  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 12K(I) micro-ops + 16KB(D) on chip, per core  
 Secondary Cache: 2048KB(I+D) on chip, per core  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 1GB 533MHz ECC CL4 DDR2 FB-DIMM  
 Disk Subsystem: 1 x 73GB SAS 10000 RPM  
 Other Hardware: None

### Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)  
 Compiler: Intel C++ Compiler 9.1 for IA32(20060323Z)  
 Microsoft Visual Studio .NET 2003(7.1.3088)  
 MicroQuill SmartHeap Library 8.0  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

### GENERAL

ONESTEP=yes  
 +FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### PORTABILITY FLAGS

176.gcc: -Dalloca=\_alloca /F10000000  
 186.crafty: -DNT\_i386  
 253.perlbnk: -DSPEC\_CPU2000\_NTOS -DPERLDLL /MT  
 254.gap: -DSYS\_HAS\_CALLOC\_PROTO -DSYS\_HAS\_MALLOC\_PROTO

### BASE TUNING

C: -fast +FDO shlw32M.lib  
 C++: -fast -Qcxx\_features +FDO

### PEAK TUNING

164.gzip: -fast +FDO  
 175.vpr: -fast +FDO  
 176.gcc: basepeak=yes  
 181.mcf: basepeak=yes  
 186.crafty: -fast -Oa +FDO shlw32M.lib  
 197.parser: -fast +FDO  
 252.eon: -fast +FDO  
 253.perlbnk: basepeak=yes



# CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Dell

PowerEdge 1955 (Intel Xeon processor 5050, 3.00GHz)

SPECint\_rate2000 = 41.6

SPECint\_rate\_base2000 = 41.8

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: May-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

## Notes/Tuning Information (Continued)

254.gap: -fast +FDO  
255.vortex basepeak=yes  
256.bzip2: -fast -Qunroll11 -Oa +FDO  
300.twolf: basepeak=yes