



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECfp_rate2000 = 81.5

SPECfp_rate_base2000 = 81.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	68.4	109	4	68.4	109
171.swim	4	265	54.3	4	265	54.3
172.mgrid	4	169	49.3	4	169	49.3
173.applu	4	182	53.4	4	182	53.4
177.mesa	4	47.9	136	4	47.9	136
178.galgel	4	59.3	227	4	59.3	227
179.art	4	54.5	221	4	54.5	221
183.quake	4	114	52.7	4	114	52.7
187.facerec	4	84.9	104	4	84.9	104
188.amp	4	117	86.9	4	117	86.9
189.lucas	4	169	54.8	4	169	54.8
191.fma3d	4	165	58.9	4	165	58.9
200.sixtrack	4	97.7	52.2	4	97.7	52.2
301.apsi	4	180	67.0	4	180	67.0

Hardware

CPU: Intel Xeon 5160 processor (3.0 GHz, 4MB SLC, 1333 MHz system bus)
CPU MHz: 3000
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32KB(I) + 32KB(D) on chip, per core
Secondary Cache: 4096KB(I+D) on chip, per chip
L3 Cache: N/A
Other Cache: N/A
Memory: 8x1024 MB DDRII-RAM PC2-5300F (CAS 5-5-5)
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)
Other Hardware: none

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 9 with SP3
Kernel 2.6.5-7.244-smp on an x86_64
Compiler: Intel C++ and Fortran Compiler 9.0 for EM64T
Build 20060120 (for 64-bit applications)
File System: ext2
System State: Multi-user run level 3

Notes/Tuning Information

GENERAL

+FDO implies feedback-directed optimization
PASS1: -prof_gen PASS2: -prof_use

Optimization flags

ONESTEP=yes set for all benchmarks

Portability flags

-DSPEC_CPU2000_LP64 applied to all benchmarks
178.galgel: -FI for fixed-format Fortran

Base tuning flags

for Fortran and C programs: -fast +FDO

Peak tuning flags

same as baseline (basepeak=true set globally)



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon 5160 processor, 3.0 GHz

SPECfp_rate2000 = 81.5

SPECfp_rate_base2000 = 81.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Jan-2006

Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:
<http://www.fujitsu-siemens.com/countries>