



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec LX201 (Intel Xeon 5160 processor)

SPECfp_rate2000 = 76.0

SPECfp_rate_base2000 = 76.0

SPEC license #: 9001 | Tested by: Itaotec | Test date: Oct-2006 | Hardware Avail: Jul-2006 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	70.8	105	4	70.8	105
171.swim	4	294	48.9	4	294	48.9
172.mgrid	4	180	46.4	4	180	46.4
173.applu	4	226	43.1	4	226	43.1
177.mesa	4	53.6	121	4	53.6	121
178.galgel	4	62.3	216	4	62.3	216
179.art	4	62.5	193	4	62.5	193
183.quake	4	88.4	68.2	4	88.4	68.2
187.facerec	4	97.3	90.6	4	97.3	90.6
188.amp	4	155	65.7	4	155	65.7
189.lucas	4	195	47.5	4	195	47.5
191.fma3d	4	167	58.4	4	167	58.4
200.sixtrack	4	94.5	54.0	4	94.5	54.0
301.apsi	4	178	67.8	4	178	67.8

Hardware

CPU: Intel Xeon 5160 processor (3.00 GHz, 4MB L2 shared, 1333 MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4096KB(I+D) on chip, per chip, shared
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2GB DDR2-RAM PC2-5300F (CAS 5-5-5)ECC
 Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (64-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Intel Fortran Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Microsoft Visual Studio .NET 7.0.9466 (for libraries),
 MicroQuill SmartHeap for SMP Library 8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlSMPMt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library 8.0 available from
<http://www.microquill.com/>