



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull

NovaScale R460 (Intel Xeon processor 5160, 3.00 GHz)

SPECfp_rate2000 = 78.4

SPECfp_rate_base2000 = 76.7

SPEC license #: 20 | Tested by: Bull | Test date: Oct-2006 | Hardware Avail: Oct-2006 | Software Avail: Oct-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	69.5	107	4	69.5	107
171.swim	4	265	54.3	4	265	54.3
172.mgrid	4	168	49.6	4	168	49.6
173.applu	4	188	51.9	4	188	51.9
177.mesa	4	54.1	120	4	54.1	120
178.galgel	4	59.1	228	4	59.1	228
179.art	4	78.3	154	4	78.3	154
183.equake	4	121	49.8	4	89.4	67.5
187.facerec	4	96.1	91.7	4	96.1	91.7
188.amp	4	123	83.2	4	123	83.2
189.lucas	4	185	50.1	4	185	50.1
191.fma3d	4	166	58.9	4	166	58.9
200.sixtrack	4	94.8	53.8	4	94.8	53.8
301.apsi	4	187	64.7	4	187	64.7

Hardware

CPU: Intel Xeon Processor 5160 (1332MHz bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1 to 2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 4096KB(I+D) on chip per chip (shared)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 12GB (12x1GB 533MHz ECC CL4 DDR2 FB-DIMM)
 Disk Subsystem: 2x73GB SAS 15000 rpm
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise Edition (32 bits), Service Pack 1
 Compiler: Intel(R) C++ Compiler for 32-bit app., Version 9.1, - Build 20060927Z Package ID: W_CC_C_9.1.032
 Intel(R) Fortran Compiler for 32-bit app., Version 9.1, - Build 20060927Z Package ID: W_FC_C_9.1.032
 Microsoft Visual Studio .NET 2003 (for libraries)
 MicroQuill SmartHeap Library 8.0 (shlW32M.lib)
 File System: NTFS
 System State: Default

Notes/Tuning Information

Portability flags:

178.galgel: -FI /F32000000

Feedback optimization:

+FDO: PASS1= -Qprof_gen PASS2= -Qprof_use

Baseline Tuning Flags:

for C programs:
 -fast -Qansi_alias +FDO
 for Fortran programs:
 -fast -Qansi_alias +FDO

Peak Tuning Flags:

168.wupwise: basepeak=yes
 171.swim: basepeak=yes
 172.mgrid: basepeak=yes
 173.applu: basepeak=yes



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Bull

NovaScale R460 (Intel Xeon processor 5160, 3.00 GHz)

SPECfp_rate2000 = 78.4

SPECfp_rate_base2000 = 76.7

SPEC license #: 20 | Tested by: Bull | Test date: Oct-2006 | Hardware Avail: Oct-2006 | Software Avail: Oct-2006

Notes/Tuning Information (Continued)

```
177.mesa: basepeak=yes
178.galgel: basepeak=yes
179.art: basepeak=yes
183.quake: -fast -Oa -Qrcd +FDO ONESTEP=yes shlW32M.lib
187.facerec: basepeak=yes
188.ammp: basepeak=yes
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes
```

For information about Bull please see:
<http://www.bull.com>