



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY TX300 S3, Intel Xeon processor X5355, 2.66 GHz

SPECfp\_rate2000 = 60.8

SPECfp\_rate\_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	98.7	75.2	4	98.7	75.2
171.swim	4	425	33.8	4	425	33.8
172.mgrid	4	266	31.4	4	266	31.4
173.applu	4	291	33.5	4	291	33.5
177.mesa	4	53.5	121	4	53.5	121
178.galgel	4	75.3	179	4	75.3	179
179.art	4	68.2	177	4	68.2	177
183.equake	4	184	32.8	4	184	32.8
187.facerec	4	111	79.7	4	111	79.7
188.amp	4	127	80.4	4	127	80.4
189.lucas	4	251	37.0	4	251	37.0
191.fma3d	4	229	42.5	4	229	42.5
200.sixtrack	4	110	46.5	4	110	46.5
301.apsi	4	201	60.0	4	201	60.0

### Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4MB L2, 1333 MHz system bus)  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST336754SS (SAS, 15.4krpm, 36GB)  
Other Hardware: none

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10  
Kernel 2.6.16.21-0.8-smp on an x86\_64  
Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T  
Build 20060816 (for 64-bit applications)  
File System: ext2  
System State: Multi-user runlevel 3

## Notes/Tuning Information

### GENERAL

+FDO implies feedback-directed optimization  
PASS1: -prof\_gen PASS2: -prof\_use

### Optimization flags

ONESTEP=yes set for all benchmarks

### Portability flags

-DSPEC\_CPU2000\_LP64 applied to all benchmarks  
178.galgel: -FI for fixed-format Fortran

### Base tuning flags

for Fortran and C programs: -fast +FDO

### Peak tuning flags

same as baseline (basepeak=true set globally)



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY TX300 S3, Intel Xeon processor X5355, 2.66 GHz

SPECfp\_rate2000 = 60.8

SPECfp\_rate\_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Oct-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Adjacent Sector Prefetch = disable

This result was measured on the PRIMERGY RX300 S3. The PRIMERGY TX300 S3 and the PRIMERGY RX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>