



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S3, Intel Xeon processor X5355, 2.66 GHz

SPECfp\_rate2000 = 60.8

SPECfp\_rate\_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	98.7	75.2	4	98.7	75.2
171.swim	4	425	33.8	4	425	33.8
172.mgrid	4	267	31.3	4	267	31.3
173.applu	4	291	33.5	4	291	33.5
177.mesa	4	53.1	122	4	53.1	122
178.galgel	4	75.5	178	4	75.5	178
179.art	4	69.2	174	4	69.2	174
183.quake	4	184	32.8	4	184	32.8
187.facerec	4	109	81.1	4	109	81.1
188.amp	4	127	80.6	4	127	80.6
189.lucas	4	251	37.0	4	251	37.0
191.fma3d	4	230	42.4	4	230	42.4
200.sixtrack	4	110	46.3	4	110	46.3
301.apsi	4	202	59.7	4	202	59.7

### Hardware

CPU: Intel Xeon processor X5355 (2.66 GHz, 2x4MB L2, 1333 MHz system bus)  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Parallel: No  
Primary Cache: 32KB(I) + 32KB(D) on chip, per core  
Secondary Cache: 8MB(I+D) on chip, per chip (4MB shared per 2 cores)  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x1GB DDR2-RAM PC2-5300F (CAS 5-5-5)  
Disk Subsystem: Seagate ST373454SS (SAS, 15.4krpm, 73GB)  
Other Hardware: none

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10  
Kernel 2.6.16.21-0.8-smp on an x86\_64  
Compiler: Intel C++ and Fortran Compiler 9.1 for EM64T  
Build 20060816 (for 64-bit applications)  
File System: reiserfs  
System State: Multi-user run level 3

## Notes/Tuning Information

### GENERAL

+FDO implies feedback-directed optimization  
PASS1: -prof\_gen PASS2: -prof\_use

Optimization flags  
ONESTEP=yes set for all benchmarks

Portability flags  
-DSPEC\_CPU2000\_LP64 applied to all benchmarks  
178.galgel: -FI for fixed-format Fortran

Base tuning flags  
for Fortran and C programs: -fast +FDO

Peak tuning flags  
same as baseline (basepeak=true set globally)



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX200 S3, Intel Xeon processor X5355, 2.66 GHz

SPECfp\_rate2000 = 60.8

SPECfp\_rate\_base2000 = 60.8

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: Aug-2006

## Notes/Tuning Information (Continued)

The system bus runs at 1333 MHz

This result was measured with 64-bit binaries using the 64-bit version of the operating system.

BIOS Configuration:

Adjacent Sector Prefetch = Disable

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>