



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec MX201 (Intel Xeon 5140 processor, 2.33GHz)

SPECfp_rate2000 = 67.7

SPECfp_rate_base2000 = 67.7

SPEC license #: 9001 | Tested by: Itaotec | Test date: Nov-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	4	75.4	98.5	4	75.4	98.5
171.swim	4	321	44.8	4	321	44.8
172.mgrid	4	205	40.7	4	205	40.7
173.applu	4	240	40.5	4	240	40.5
177.mesa	4	64.9	100	4	64.9	100
178.galgel	4	70.9	190	4	70.9	190
179.art	4	66.4	182	4	66.4	182
183.equake	4	93.7	64.4	4	93.7	64.4
187.facerec	4	108	81.8	4	108	81.8
188.amp	4	171	59.7	4	171	59.7
189.lucas	4	212	43.8	4	212	43.8
191.fma3d	4	181	53.9	4	181	53.9
200.sixtrack	4	120	42.6	4	120	42.6
301.apsi	4	227	53.1	4	227	53.1

Hardware

CPU: Intel Xeon 5140 processor (2.33 GHz, 4MB L2 shared, 1333 MHz system bus)
CPU MHz: 2330
FPU: Integrated
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4MB (I+D) on chip, per chip, shared
L3 Cache: N/A
Other Cache: N/A
Memory: 14GB (7x2GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler: Intel C++ Compiler 9.1
Build 20060323Z (for 32-bit applications),
Intel Fortran Compiler 9.1
Build 20060323Z (for 32-bit applications),
Microsoft Visual Studio 2005 (for libraries),
MicroQuill SmartHeap for SMP Library v.8.0
File System: NTFS
System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO

for C programs: -fast +FDO shlsmpmt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library v.8.0

<http://www.microquill.com/>

BIOS settings default.

The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org>