



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

IBM BladeCenter HS21 XM (Intel Xeon 5140)

**SPECint\_rate2006 = Not Run**

**SPECint\_rate\_base2006 = 45.2**

CPU2006 license: 11


Test sponsor: IBM Corporation

Tested by: IBM Corporation

Test date: Jan-2007

Hardware Availability: Feb-2007

Software Availability: Aug-2006



### Hardware

CPU Name: Intel Xeon 5140  
CPU Characteristics: 1333MHz system bus  
CPU MHz: 2333  
FPU: Integrated  
CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 4 MB I+D on chip per chip  
L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8 x 2GB DDR2-5300F ECC)  
Disk Subsystem: 1 x 74 GB SAS, 1000 RPM  
Other Hardware: None

### Software

Operating System: Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)  
Compiler: Intel C++ Compiler for IA32 version 9.1 Build no 20060816  
Auto Parallel: No  
File System: NTFS  
System State: Default  
Base Pointers: 32-bit  
Peak Pointers: Not Applicable  
Other Software: Smart Heap Library, Version 8



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

**SPECint\_rate2006 = Not Run**

IBM BladeCenter HS21 XM (Intel Xeon 5140)

**SPECint\_rate\_base2006 = 45.2**

CPU2006 license: 11

Test date: Jan-2007

Test sponsor: IBM Corporation

Hardware Availability: Feb-2007

Tested by: IBM Corporation

Software Availability: Aug-2006

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	594	65.7	<b>595</b>	<b>65.7</b>	595	65.7							
401.bzip2	4	<b>1010</b>	<b>38.2</b>	1011	38.2	1009	38.3							
403.gcc	4	1283	25.1	1284	25.1	<b>1283</b>	<b>25.1</b>							
429.mcf	4	<b>803</b>	<b>45.4</b>	803	45.4	803	45.4							
445.gobmk	4	<b>700</b>	<b>60.0</b>	700	59.9	699	60.0							
456.hammer	4	949	39.3	<b>949</b>	<b>39.3</b>	949	39.3							
458.sjeng	4	857	56.5	857	56.5	<b>857</b>	<b>56.5</b>							
462.libquantum	4	2877	28.8	<b>2876</b>	<b>28.8</b>	2875	28.8							
464.h264ref	4	928	95.4	929	95.2	<b>929</b>	<b>95.3</b>							
471.omnetpp	4	770	32.4	<b>771</b>	<b>32.4</b>	771	32.4							
473.astar	4	<b>760</b>	<b>36.9</b>	761	36.9	760	36.9							
483.xalancbmk	4	477	57.8	<b>478</b>	<b>57.8</b>	478	57.8							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

## Base Portability Flags

403.gcc: -DSPEC\_CPU\_WIN32

464.h264ref: -DSPEC\_CPU\_NO\_INTTYPES -DWIN32

## Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE
```

C++ benchmarks:

```
-fast -Qcxx_features /F512000000 shlw32m.lib  
-link /FORCE:MULTIPLE
```



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

**SPECint\_rate2006 = Not Run**

IBM BladeCenter HS21 XM (Intel Xeon 5140)

**SPECint\_rate\_base2006 = 45.2**

**CPU2006 license:** 11

**Test date:** Jan-2007

**Test sponsor:** IBM Corporation

**Hardware Availability:** Feb-2007

**Tested by:** IBM Corporation

**Software Availability:** Aug-2006

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 10:42:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 6 March 2007.