



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440  
(Intel Xeon processor E5335, 2.00GHz)

**SPECfp®2006 = 12.1**

**SPECfp\_base2006 = 11.9**

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Apr-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006



Hardware		Software	
CPU Name:	Intel Xeon E5335	Operating System:	SuSE Linux Enterprise Server 10 (EM64T) kernel 2.6.16.21-0.8-smp
CPU Characteristics:	2.0GHz, 2x4 MB L2 shared, 1333 MHz system bus	Compiler:	Intel C++ Compiler for Intel EM64T-based applications, Version 9.1 Package ID l_cc_c_9.1.045 Build no 20061101
CPU MHz:	2000		Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1 Package ID l_fc_c_9.1.040 Build no 20061101
FPU:	Integrated	Auto Parallel:	No
CPU(s) enabled:	1 core, 1 chip, 4 cores/chip	Continued on next page	
CPU(s) orderable:	1 to 2 chips		
Primary Cache:	32 KB I + 32 KB D on chip per core		
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores		

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440  
(Intel Xeon processor E5335,2.00GHz)

**SPECfp2006 = 12.1**

**SPECfp\_base2006 = 11.9**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Apr-2007

**Hardware Availability:** Mar-2007

**Software Availability:** Dec-2006

L3 Cache: None  
Other Cache: None  
Memory: 24 GB (2GB DIMMx12, FB-DIMM PC2-5300F ECC CL5)  
Disk Subsystem: 73 GB SAS, 10000RPM  
Other Hardware: None

File System: ext2  
System State: Multi-user, run level 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	769	17.7	<b>769</b>	<b>17.7</b>	769	17.7	<b>766</b>	<b>17.7</b>	766	17.7	765	17.8
416.gamess	1430	13.7	<b>1430</b>	<b>13.7</b>	1429	13.7	<b>1545</b>	<b>12.7</b>	1548	12.6	<b>1547</b>	<b>12.7</b>
433.milc	953	9.63	<b>954</b>	<b>9.62</b>	955	9.62	<b>955</b>	<b>9.61</b>	955	9.61	955	9.61
434.zeusmp	<b>824</b>	<b>11.0</b>	825	11.0	824	11.0	852	10.7	<b>852</b>	<b>10.7</b>	852	10.7
435.gromacs	589	12.1	<b>586</b>	<b>12.2</b>	586	12.2	<b>567</b>	<b>12.6</b>	567	12.6	567	12.6
436.cactusADM	<b>921</b>	<b>13.0</b>	923	12.9	921	13.0	<b>942</b>	<b>12.7</b>	935	12.8	951	12.6
437.leslie3d	<b>868</b>	<b>10.8</b>	869	10.8	866	10.9	<b>872</b>	<b>10.8</b>	<b>872</b>	<b>10.8</b>	873	10.8
444.namd	764	10.5	764	10.5	<b>764</b>	<b>10.5</b>	776	10.3	<b>777</b>	<b>10.3</b>	777	10.3
447.dealII	<b>614</b>	<b>18.6</b>	614	18.6	614	18.6	<b>597</b>	<b>19.2</b>	597	19.2	597	19.2
450.soplex	769	10.8	<b>767</b>	<b>10.9</b>	766	10.9	<b>750</b>	<b>11.1</b>	<b>749</b>	<b>11.1</b>	<b>749</b>	<b>11.1</b>
453.povray	386	13.8	<b>385</b>	<b>13.8</b>	384	13.8	<b>295</b>	<b>18.0</b>	294	18.1	295	18.0
454.calculix	777	10.6	777	10.6	<b>777</b>	<b>10.6</b>	<b>757</b>	<b>10.9</b>	<b>757</b>	<b>10.9</b>	<b>757</b>	<b>10.9</b>
459.GemsFDTD	1015	10.5	<b>1015</b>	<b>10.5</b>	1015	10.5	<b>1021</b>	<b>10.4</b>	<b>1021</b>	<b>10.4</b>	1021	10.4
465.tonto	890	11.1	885	11.1	<b>886</b>	<b>11.1</b>	874	11.3	853	11.5	<b>854</b>	<b>11.5</b>
470.lbm	2332	5.89	2340	5.87	<b>2334</b>	<b>5.89</b>	2339	5.87	2332	5.89	<b>2334</b>	<b>5.89</b>
481.wrf	<b>830</b>	<b>13.4</b>	831	13.4	829	13.5	864	12.9	<b>863</b>	<b>12.9</b>	862	13.0
482.sphinx3	1334	14.6	<b>1339</b>	<b>14.6</b>	1348	14.5	<b>1240</b>	<b>15.7</b>	<b>1219</b>	<b>16.0</b>	<b>1221</b>	<b>16.0</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Environment stack size set to 'unlimited'

System was booted uniprocessor by setting "maxcpus=0" kernel parameter in menu.lst

## General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.

The results have been measured on a NovaScale R440 model.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440  
(Intel Xeon processor E5335,2.00GHz)

**SPECfp2006 = 12.1**

**SPECfp\_base2006 = 11.9**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Apr-2007

**Hardware Availability:** Mar-2007

**Software Availability:** Dec-2006

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-fast

Fortran benchmarks:  
-fast

Benchmarks using both Fortran and C:  
-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440  
(Intel Xeon processor E5335,2.00GHz)

**SPECfp2006 =** 12.1

**SPECfp\_base2006 =** 11.9

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Apr-2007

**Hardware Availability:** Mar-2007

**Software Availability:** Dec-2006

## Peak Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

C++ benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

Fortran benchmarks:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast

Benchmarks using both Fortran and C:  
-prof\_gen(pass 1) -prof\_use(pass 2) -fast -auto\_ilp32

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/EM64T\\_Intel91\\_flags.html](http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/EM64T\\_Intel91\\_flags.xml](http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.xml)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R440  
(Intel Xeon processor E5335,2.00GHz)

**SPECfp2006 =** 12.1

**SPECfp\_base2006 =** 11.9

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Apr-2007

**Hardware Availability:** Mar-2007

**Software Availability:** Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 12:11:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 15 May 2007.