



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor 5110, 1.60 GHz

**SPECint®\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 35.4**

CPU2006 license: 22


Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007



### Hardware

CPU Name: Intel Xeon 5110  
 CPU Characteristics: 1067 MHz system bus  
 CPU MHz: 1600  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip  
 L3 Cache: None  
 Other Cache: None  
 Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)  
 Disk Subsystem: SAS (73GB 15400 rpm)  
 Other Hardware: None

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86\_64  
 Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l\_cc\_p\_9.1.047  
 Auto Parallel: No  
 File System: ext2  
 System State: Multiuser, Runlevel 3  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Smart Heap Library, Version 8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor 5110,  
1.60 GHz

SPECint\_rate2006 = 37.2

SPECint\_rate\_base2006 = 35.4

CPU2006 license: 22

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers

Test date: May-2007

Hardware Availability: Jul-2006

Software Availability: Feb-2007

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	899	43.5	<b>899</b>	<b>43.5</b>	900	43.4	4	823	47.5	819	47.7	<b>822</b>	<b>47.5</b>
401.bzip2	4	<b>1378</b>	<b>28.0</b>	1376	28.0	1382	27.9	4	1307	29.5	1300	29.7	<b>1304</b>	<b>29.6</b>
403.gcc	4	879	36.6	872	36.9	<b>873</b>	<b>36.9</b>	4	879	36.6	872	36.9	<b>873</b>	<b>36.9</b>
429.mcf	4	994	36.7	<b>996</b>	<b>36.6</b>	998	36.6	4	<b>1019</b>	<b>35.8</b>	1017	35.9	1019	35.8
445.gobmk	4	989	42.4	<b>996</b>	<b>42.1</b>	996	42.1	4	<b>922</b>	<b>45.5</b>	918	45.7	923	45.4
456.hmmer	4	<b>1390</b>	<b>26.9</b>	1387	26.9	1390	26.8	4	1161	32.1	<b>1161</b>	<b>32.1</b>	1161	32.2
458.sjeng	4	<b>1215</b>	<b>39.8</b>	1216	39.8	1212	39.9	4	1124	43.1	<b>1121</b>	<b>43.2</b>	1118	43.3
462.libquantum	4	3581	23.1	<b>3580</b>	<b>23.2</b>	3573	23.2	4	3515	23.6	3521	23.5	<b>3517</b>	<b>23.6</b>
464.h264ref	4	1356	65.3	<b>1355</b>	<b>65.3</b>	1355	65.3	4	1340	66.1	1342	65.9	<b>1341</b>	<b>66.0</b>
471.omnetpp	4	913	27.4	<b>906</b>	<b>27.6</b>	905	27.6	4	832	30.0	831	30.1	<b>832</b>	<b>30.1</b>
473.astar	4	1056	26.6	<b>1056</b>	<b>26.6</b>	1055	26.6	4	1041	27.0	1042	27.0	<b>1041</b>	<b>27.0</b>
483.xalancbmk	4	589	46.9	<b>589</b>	<b>46.9</b>	590	46.8	4	589	46.9	<b>589</b>	<b>46.9</b>	590	46.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs

## General Notes

The system bus runs at 1067 MHz

All binaries were built with 32-bit Intel compiler except:  
401.bzip2, 456.hmmer and 462.libquantum in peak were built with  
64-bit Intel compiler by changing the path for include and library files.

BIOS configuration:  
Adjacent Sector Prefetch = Disable

The PRIMERGY RX300 S3 and the PRIMERGY TX300 S3 are electronically equivalent.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon processor 5110,  
1.60 GHz

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 35.4**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** May-2007

**Hardware Availability:** Jul-2006

**Software Availability:** Feb-2007

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_X64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-xP -O3 -ipo -no-prec-div -L/opt/SmartHeap\_8\_1/lib -lsmartheap

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

401.bzip2: /opt/intel/cce/9.1.047/bin/icc  
-I/opt/intel/cce/9.1.047/include  
-L/opt/intel/cce/9.1.047/lib

456.hmmer: /opt/intel/cce/9.1.047/bin/icc  
-I/opt/intel/cce/9.1.047/include  
-L/opt/intel/cce/9.1.047/lib

462.libquantum: /opt/intel/cce/9.1.047/bin/icc  
-I/opt/intel/cce/9.1.047/include  
-L/opt/intel/cce/9.1.047/lib

C++ benchmarks:  
icpc

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_X64  
401.bzip2: -DSPEC\_CPU\_LP64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon processor 5110,  
1.60 GHz

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 35.4**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** May-2007

**Hardware Availability:** Jul-2006

**Software Availability:** Feb-2007

## Peak Portability Flags (Continued)

456.hmmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

401.bzip2: -fast

403.gcc: basepeak = yes

429.mcf: -prof\_gen(pass 1) -prof\_use(pass 2) -fast  
-L/opt/SmartHeap\_8\_1/lib -lsmartheap

445.gobmk: Same as 429.mcf

456.hmmmer: Same as 400.perlbench

458.sjeng: Same as 429.mcf

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 429.mcf

C++ benchmarks:

471.omnetpp: -prof\_gen(pass 1) -prof\_use(pass 2) -xP -O3 -ipo  
-no-prec-div -L/opt/SmartHeap\_8\_1/lib -lsmartheap

473.astar: -prof\_gen(pass 1) -prof\_use(pass 2) -fast  
-L/opt/SmartHeap\_8\_1/lib -lsmartheap

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090714.09.html](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090714.09.xml](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml)



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX300 S3, Intel Xeon processor 5110,  
1.60 GHz

**SPECint\_rate2006 = 37.2**

**SPECint\_rate\_base2006 = 35.4**

**CPU2006 license:** 22

**Test sponsor:** Fujitsu Siemens Computers

**Tested by:** Fujitsu Siemens Computers

**Test date:** May-2007

**Hardware Availability:** Jul-2006

**Software Availability:** Feb-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 11:45:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 29 May 2007.