



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECfp®2006 = 14.6

SPECfp_base2006 = 14.3

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon 5150
 CPU Characteristics: 2.66 GHz, 4 MB L2, 1333 MHz system bus
 CPU MHz: 2666
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1 to 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

Software

Operating System: SuSE Linux Enterprise Server 10 (EM64T)
 kernel 2.6.16.21-0.8-smp
 Compiler: Intel C++ Compiler for Intel EM64T-based applications, Version 9.1
 Package ID l_cc_c_9.1.045 Build no 20061101
 Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1
 Package ID l_fc_c_9.1.040 Build no 20061101
 Auto Parallel: No

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECfp2006 = 14.6

SPECfp_base2006 = 14.3

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: May-2007

Hardware Availability: Mar-2007

Software Availability: Dec-2006

L3 Cache: None
Other Cache: None
Memory: 24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

File System: ext2
System State: Multi-user run level 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>711</u>	<u>19.1</u>	712	19.1	711	19.1	711	19.1	<u>711</u>	<u>19.1</u>	710	19.1
416.gamess	1070	18.3	<u>1068</u>	<u>18.3</u>	1068	18.3	1155	17.0	1160	16.9	<u>1157</u>	<u>16.9</u>
433.milc	881	10.4	<u>881</u>	<u>10.4</u>	880	10.4	<u>885</u>	<u>10.4</u>	885	10.4	884	10.4
434.zeusmp	675	13.5	675	13.5	<u>675</u>	<u>13.5</u>	698	13.0	<u>698</u>	<u>13.0</u>	698	13.0
435.gromacs	440	16.2	441	16.2	<u>441</u>	<u>16.2</u>	<u>426</u>	<u>16.8</u>	426	16.8	426	16.8
436.cactusADM	780	15.3	<u>782</u>	<u>15.3</u>	789	15.2	804	14.9	789	15.1	<u>801</u>	<u>14.9</u>
437.leslie3d	768	12.2	<u>767</u>	<u>12.2</u>	765	12.3	<u>770</u>	<u>12.2</u>	770	12.2	768	12.2
444.namd	572	14.0	<u>572</u>	<u>14.0</u>	573	14.0	582	13.8	<u>583</u>	<u>13.8</u>	583	13.8
447.dealII	482	23.8	483	23.7	<u>482</u>	<u>23.7</u>	469	24.4	<u>469</u>	<u>24.4</u>	470	24.4
450.soplex	<u>690</u>	<u>12.1</u>	690	12.1	688	12.1	674	12.4	673	12.4	<u>673</u>	<u>12.4</u>
453.povray	<u>290</u>	<u>18.4</u>	287	18.5	291	18.3	<u>221</u>	<u>24.1</u>	220	24.1	221	24.0
454.calculix	590	14.0	<u>590</u>	<u>14.0</u>	591	14.0	575	14.3	<u>575</u>	<u>14.3</u>	576	14.3
459.GemsFDTD	<u>937</u>	<u>11.3</u>	937	11.3	937	11.3	<u>943</u>	<u>11.2</u>	943	11.2	943	11.3
465.tonto	677	14.5	682	14.4	<u>680</u>	<u>14.5</u>	649	15.2	654	15.1	<u>653</u>	<u>15.1</u>
470.lbm	2285	6.01	2252	6.10	<u>2257</u>	<u>6.09</u>	2246	6.12	<u>2250</u>	<u>6.11</u>	2255	6.09
481.wrf	678	16.5	<u>678</u>	<u>16.5</u>	679	16.4	702	15.9	704	15.9	<u>702</u>	<u>15.9</u>
482.sphinx3	1098	17.8	<u>1091</u>	<u>17.9</u>	1090	17.9	999	19.5	<u>999</u>	<u>19.5</u>	1001	19.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Environment stack size set to 'unlimited'
'/usr/bin/taskset' used to bind processes to CPUs

General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.
The results have been measured on a NovaScale R460 model.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECfp2006 = 14.6

SPECfp_base2006 = 14.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Base Compiler Invocation

C benchmarks:
icc
C++ benchmarks:
icpc
Fortran benchmarks:
ifort
Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast
C++ benchmarks:
-fast
Fortran benchmarks:
-fast
Benchmarks using both Fortran and C:
-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECfp2006 = 14.6

SPECfp_base2006 = 14.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

C++ benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

Fortran benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast

Benchmarks using both Fortran and C:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/EM64T_Intel91_flags.xml



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5150,2.66GHz)

SPECfp2006 = 14.6

SPECfp_base2006 = 14.3

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Mar-2007
Software Availability: Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:45:26 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.