



SPEC[®] CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint[®]2006 = 12.8

ProLiant DL580 G4
(3.4 GHz, Intel Xeon processor 7140M)

SPECint_base2006 = 12.0

CPU2006 license: 3


Test date: Jul-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007



Hardware

CPU Name: Intel Xeon 7140M
 CPU Characteristics: 3.4 GHz, 800 MHz system bus
 CPU MHz: 3400
 FPU: Integrated
 CPU(s) enabled: 2 cores, 1 chip, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2,4 chips
 Primary Cache: 12 K micro-ops I + 16 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core
 L3 Cache: 16 MB I+D on chip per chip
 Other Cache: None
 Memory: 32 GB (16x2 GB PC2-3200R)
 Disk Subsystem: 1x72 GB 15 K SAS
 Other Hardware: None

Software

Operating System: SuSE Linux Enterprise Server 10 (x86_64)
 kernel 2.6.16.21-0.8-smp
 Compiler: Intel C++ Compiler for IA32/EM64T applications, Version 10.0
 Build 20070426 Package ID: 1_cc_p_10.0.023
 Auto Parallel: No
 File System: ext2
 System State: Multi-user run level 3
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap 8.1 libraries



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint2006 = **12.8**

ProLiant DL580 G4
(3.4 GHz, Intel Xeon processor 7140M)

SPECint_base2006 = **12.0**

CPU2006 license: 3

Test date: Jul-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	817	12.0	821	11.9	822	11.9	746	13.1	744	13.1	742	13.2
401.bzip2	1059	9.12	1052	9.17	1052	9.17	974	9.91	973	9.92	972	9.93
403.gcc	640	12.6	640	12.6	639	12.6	640	12.6	640	12.6	639	12.6
429.mcf	671	13.6	672	13.6	671	13.6	670	13.6	671	13.6	672	13.6
445.gobmk	1106	9.49	1105	9.50	1105	9.50	1033	10.2	1032	10.2	1032	10.2
456.hmmmer	1130	8.26	1134	8.23	1129	8.26	949	9.83	950	9.83	950	9.82
458.sjeng	1483	8.16	1484	8.15	1481	8.17	1281	9.45	1284	9.43	1280	9.45
462.libquantum	777	26.7	794	26.1	788	26.3	765	27.1	783	26.5	771	26.9
464.h264ref	1155	19.2	1154	19.2	1154	19.2	1081	20.5	1081	20.5	1083	20.4
471.omnetpp	673	9.29	668	9.35	671	9.32	626	9.98	627	9.97	627	9.97
473.astar	763	9.20	761	9.22	761	9.23	717	9.79	716	9.81	716	9.81
483.xalancbmk	422	16.4	420	16.4	420	16.4	422	16.4	420	16.4	420	16.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

Platform Notes

BIOS configuration:
Power Regulator Disabled
Adjacent Sector Prefetch Enabled
Hardware Prefetcher Enabled
Hyper-Threading Technology Enabled

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint2006 = 12.8

ProLiant DL580 G4
(3.4 GHz, Intel Xeon processor 7140M)

SPECint_base2006 = 12.0

CPU2006 license: 3

Test date: Jul-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007

Base Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xP -ipo -O3 -static -no-prec-div

C++ benchmarks:

-xP -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/cpu2006/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

456.hmmer: /opt/intel/cce/10.0.023/bin/icc
-L/opt/intel/cce/10.0.023/lib
-I/opt/intel/cce/10.0.023/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

SPECint2006 = 12.8

ProLiant DL580 G4
(3.4 GHz, Intel Xeon processor 7140M)

SPECint_base2006 = 12.0

CPU2006 license: 3

Test date: Jul-2007

Test sponsor: Hewlett-Packard Company

Hardware Availability: Aug-2006

Tested by: Hewlett-Packard Company

Software Availability: May-2007

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3
-no-prec-div -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3
-no-prec-div

403.gcc: basepeak = yes

429.mcf: -xP -ipo -O3 -static -no-prec-div -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xP -O2 -ipo
-no-prec_div -ansi-alias

456.hmmer: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static
-no-prec-div -unroll2 -ansi-alias

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -static
-no-prec-div -unroll4

462.libquantum: Same as 458.sjeng

464.h264ref: Same as 456.hmmer

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xP -O3 -ipo
-no-prec_div -ansi-alias -Wl,-z,muldefs
-L/cpu2006/SmartHeap_8.1/lib -lsmarheap

473.astar: Same as 471.omnetpp

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/hp-ic10-flags.20090714.03.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/hp-ic10-flags.20090714.03.xml>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant DL580 G4
(3.4 GHz, Intel Xeon processor 7140M)

SPECint2006 = 12.8

SPECint_base2006 = 12.0

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Jul-2007
Hardware Availability: Aug-2006
Software Availability: May-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:31:32 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 21 August 2007.