



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp®_rate2006 = 45.4

Dell Precision 690 (Intel 5160, 3.00 GHz)

SPECfp_rate_base2006 = 44.5

CPU2006 license: 55


Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: May-2006

Tested by: Dell Inc.

Software Availability: Jun-2007



Hardware

CPU Name: Intel Xeon 5160
 CPU Characteristics: 1333 MHz Bus Speed
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

Software

Operating System: Windows XP Professional x64 Edition SP2
 Compiler: Intel C++ Compiler for Intel 64, Version 10.0
 Build 20070426 Package ID: W_CC_P_10.0.025
 Intel Visual Fortran Compiler for Intel 64,
 Version 10.0
 Build 20070426 Package ID: W_FC_P_10.0.025
 Microsoft Visual Studio 2005 SP1
 Auto Parallel: No
 File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 45.4

Dell Precision 690 (Intel 5160, 3.00 GHz)

SPECfp_rate_base2006 = 44.5

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: May-2006

Tested by: Dell Inc.

Software Availability: Jun-2007

L3 Cache: None
 Other Cache: None
 Memory: 8 GB (8x1 GB 667 MHz ECC CL5 FB-DIMM)
 Disk Subsystem: 1 x 73GB SAS 10K RPM
 Other Hardware: None

System State: Default
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.0 for x64

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	<u>1531</u>	<u>35.5</u>	1531	35.5	1531	35.5	4	<u>1531</u>	<u>35.5</u>	1533	35.5	1531	35.5
416.gamess	4	938	83.5	938	83.5	<u>938</u>	<u>83.5</u>	4	918	85.3	<u>918</u>	<u>85.3</u>	918	85.3
433.milc	4	1560	23.5	<u>1561</u>	<u>23.5</u>	1561	23.5	4	<u>1573</u>	<u>23.4</u>	1572	23.4	1573	23.3
434.zeusmp	4	740	49.2	<u>742</u>	<u>49.0</u>	743	49.0	4	725	50.2	<u>726</u>	<u>50.2</u>	726	50.1
435.gromacs	4	394	72.6	<u>394</u>	<u>72.6</u>	393	72.6	4	393	72.7	391	73.0	<u>391</u>	<u>73.0</u>
436.cactusADM	4	892	53.6	<u>891</u>	<u>53.7</u>	890	53.7	4	892	53.6	<u>891</u>	<u>53.7</u>	890	53.7
437.leslie3d	4	<u>1434</u>	<u>26.2</u>	1434	26.2	1436	26.2	4	1437	26.2	<u>1437</u>	<u>26.2</u>	1439	26.1
444.namd	4	511	62.8	510	62.9	<u>510</u>	<u>62.8</u>	4	504	63.7	503	63.8	<u>503</u>	<u>63.8</u>
447.dealII	4	830	55.1	<u>828</u>	<u>55.3</u>	813	56.3	4	794	57.6	<u>788</u>	<u>58.1</u>	786	58.2
450.soplex	4	<u>1156</u>	<u>28.9</u>	1157	28.8	1155	28.9	4	1156	28.9	1154	28.9	<u>1154</u>	<u>28.9</u>
453.povray	4	<u>240</u>	<u>88.5</u>	240	88.5	240	88.5	4	192	111	<u>192</u>	<u>111</u>	192	111
454.calculix	4	616	53.6	600	55.0	<u>611</u>	<u>54.0</u>	4	618	53.4	597	55.3	<u>607</u>	<u>54.4</u>
459.GemsFDTD	4	1765	24.0	<u>1765</u>	<u>24.0</u>	1769	24.0	4	1765	24.0	<u>1765</u>	<u>24.0</u>	1769	24.0
465.tonto	4	705	55.8	709	55.5	<u>709</u>	<u>55.5</u>	4	703	56.0	<u>708</u>	<u>55.6</u>	710	55.4
470.lbm	4	2463	22.3	<u>2464</u>	<u>22.3</u>	2464	22.3	4	2464	22.3	2466	22.3	<u>2465</u>	<u>22.3</u>
481.wrf	4	925	48.3	925	48.3	<u>925</u>	<u>48.3</u>	4	934	47.8	<u>929</u>	<u>48.1</u>	925	48.3
482.sphinx3	4	<u>1798</u>	<u>43.3</u>	1795	43.4	1799	43.3	4	1797	43.4	<u>1783</u>	<u>43.7</u>	1781	43.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Binaries were built on Windows Vista Ultimate (64-bit)

BIOS Settings

Snoop Filter : ON
 Adjacent Cache Line Prefetch : ON
 Hardware Prefetcher : ON

Snoop Filter

Preserves cache coherency while minimizing snoops to remote nodes.

Adjacent Cache Line Prefetch

Prefetch data in order to shorten execution cycles and maximize data processing efficiency.

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 45.4

Dell Precision 690 (Intel 5160, 3.00 GHz)

SPECfp_rate_base2006 = 44.5

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Aug-2007
Hardware Availability: May-2006
Software Availability: Jun-2007

General Notes (Continued)

Optimization for high-frequency FSB applicatons: ON

Base Compiler Invocation

C benchmarks:
icl -Qstd=c99

C++ benchmarks:
icl

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qstd=c99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -D_Complex= -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -D_Complex= -DSPEC_CPU_P64
436.cactusADM: -D_Complex= -DSPEC_CPU_P64 -Qlowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -D_Complex= -DSPEC_CPU_P64 -DBOOST_NO_INTRINSIC_WCHAR_T
-DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -D_Complex= -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER
-Qlowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -D_Complex= -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -D_Complex= -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-fast -Qauto_ilp32 /F950000000 shlW64M.lib
-link /FORCE:MULTIPLE

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 45.4

Dell Precision 690 (Intel 5160, 3.00 GHz)

SPECfp_rate_base2006 = 44.5

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: May-2006

Tested by: Dell Inc.

Software Availability: Jun-2007

Base Optimization Flags (Continued)

C++ benchmarks:

```
-fast -Qcxx_features -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE
```

Fortran benchmarks:

```
-fast /F950000000 -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:

```
-fast -Qauto_ilp32 /F950000000 -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:

```
icl -Qstd=c99
```

C++ benchmarks:

```
icl
```

Fortran benchmarks:

```
ifort
```

Benchmarks using both Fortran and C:

```
icl -Qstd=c99 ifort
```

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

```
433.milc: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Oa -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE
```

```
470.lbm: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Qscalar-rep- -Qprefetch -Qauto_ilp32
/F950000000 shlw64M.lib -link /FORCE:MULTIPLE
```

```
482.sphinx3: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Qauto_ilp32 /F950000000 shlw64M.lib
-link /FORCE:MULTIPLE
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 45.4

Dell Precision 690 (Intel 5160, 3.00 GHz)

SPECfp_rate_base2006 = 44.5

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: May-2006

Tested by: Dell Inc.

Software Availability: Jun-2007

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Oa
-Qcxx_features -Qauto_ilp32 /F950000000 shlW64M.lib
-link /FORCE:MULTIPLE

447.dealIII: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qprefetch -Qcxx_features -Qauto_ilp32 /F950000000
shlW64M.lib -link /FORCE:MULTIPLE

450.soplex: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qcxx_features -Qauto_ilp32 /F950000000 shlW64M.lib
-link /FORCE:MULTIPLE

453.povray: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qansi-alias -Qcxx_features -Qauto_ilp32 /F950000000
shlW64M.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: ONESTEP -fast /F950000000 -link /FORCE:MULTIPLE

416.gamess: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
-Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F950000000
-link /FORCE:MULTIPLE

434.zeusmp: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2
-Qprec-div- -Qunroll10 -Qscalar-rep- /F950000000
-link /FORCE:MULTIPLE

437.leslie3d: ONESTEP -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast
/F950000000 -link /FORCE:MULTIPLE

459.GemsFDTD: basepeak = yes

465.tonto: Same as 437.leslie3d

Benchmarks using both Fortran and C:

435.gromacs: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Oa
-Qauto_ilp32 /F950000000 -link /FORCE:MULTIPLE

436.cactusADM: basepeak = yes

454.calculix: -fast -Qauto_ilp32 /F950000000
-link /FORCE:MULTIPLE

481.wrf: Same as 454.calculix



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 45.4

Dell Precision 690 (Intel 5160, 3.00 GHz)

SPECfp_rate_base2006 = 44.5

CPU2006 license: 55

Test date: Aug-2007

Test sponsor: Dell Inc.

Hardware Availability: May-2006

Tested by: Dell Inc.

Software Availability: Jun-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/dell.ic10.windows.flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/dell.ic10.windows.flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:14:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 4 September 2007.