



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## SPECfp<sup>®</sup>\_rate2006 = 42.5

## Acer Altos R720 (Intel Xeon 5140)

## SPECfp\_rate\_base2006 = 39.2

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007



### Hardware

CPU Name: Intel Xeon 5140  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 2330  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 4 MB I+D on chip per chip

Continued on next page

### Software

Operating System: SuSE Linux Enterprise Server 10 SP1 EM64T (kernel 2.6.16.46-0.12-smp)  
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Multi-user, level 3  
 Base Pointers: 64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 42.5

Acer Altos R720 (Intel Xeon 5140)

SPECfp\_rate\_base2006 = 39.2

CPU2006 license: 97  
Test sponsor: Acer Incorporated  
Tested by: Acer Incorporated

Test date: Nov-2007  
Hardware Availability: Nov-2006  
Software Availability: Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)  
Disk Subsystem: 1 x 73GB 10000PRM SAS HDD  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: MicroQuill SmartHeap Library 8.1

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	1640	33.1	<b>1638</b>	<b>33.2</b>	1638	33.2	4	1568	34.7	1570	34.6	<b>1570</b>	<b>34.6</b>
416.gamess	4	1192	65.7	1198	65.4	<b>1197</b>	<b>65.4</b>	4	<b>1173</b>	<b>66.7</b>	1174	66.7	1173	66.8
433.milc	4	<b>1706</b>	<b>21.5</b>	1708	21.5	1705	21.5	4	<b>1709</b>	<b>21.5</b>	1703	21.6	1709	21.5
434.zeusmp	4	<b>859</b>	<b>42.4</b>	857	42.5	859	42.4	4	851	42.7	<b>852</b>	<b>42.7</b>	852	42.7
435.gromacs	4	<b>502</b>	<b>56.9</b>	508	56.2	501	57.0	4	<b>496</b>	<b>57.6</b>	496	57.6	501	57.1
436.cactusADM	4	1034	46.2	<b>1040</b>	<b>45.9</b>	1043	45.8	1	245	48.8	243	49.2	<b>245</b>	<b>48.8</b>
437.leslie3d	4	<b>1603</b>	<b>23.5</b>	1595	23.6	1610	23.4	4	1566	24.0	1560	24.1	<b>1565</b>	<b>24.0</b>
444.namd	4	651	49.3	<b>650</b>	<b>49.3</b>	650	49.3	4	648	49.5	<b>647</b>	<b>49.6</b>	647	49.6
447.dealII	4	<b>637</b>	<b>71.9</b>	642	71.3	636	72.0	4	594	77.0	602	76.1	<b>599</b>	<b>76.4</b>
450.soplex	4	1278	26.1	1286	25.9	<b>1282</b>	<b>26.0</b>	4	1176	28.4	<b>1176</b>	<b>28.4</b>	1172	28.5
453.povray	4	287	74.2	<b>287</b>	<b>74.2</b>	287	74.1	4	243	87.6	<b>243</b>	<b>87.7</b>	242	87.9
454.calculix	4	<b>695</b>	<b>47.5</b>	696	47.4	694	47.5	4	495	66.7	<b>492</b>	<b>67.0</b>	490	67.3
459.GemsFDTD	4	<b>2056</b>	<b>20.6</b>	2050	20.7	2056	20.6	4	<b>1946</b>	<b>21.8</b>	1944	21.8	1948	21.8
465.tonto	4	<b>762</b>	<b>51.7</b>	761	51.7	763	51.6	4	737	53.4	740	53.2	<b>739</b>	<b>53.3</b>
470.lbm	4	<b>3129</b>	<b>17.6</b>	3129	17.6	3129	17.6	4	2141	25.7	<b>2141</b>	<b>25.7</b>	2141	25.7
481.wrf	4	1037	43.1	<b>1029</b>	<b>43.4</b>	1027	43.5	4	<b>1028</b>	<b>43.5</b>	1027	43.5	1028	43.5
482.sphinx3	4	2084	37.4	<b>2079</b>	<b>37.5</b>	2076	37.5	4	1937	40.3	<b>1931</b>	<b>40.4</b>	1928	40.4

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

This result was measured on the Acer Altos R520.  
The Altos R720 and Altos R520 are electronically equivalent.

### BIOS Settings

Hardware Prefetcher set to ON

Adjacent Cache Line Prefetch set to ON

Optimization for high-frequency FSB applications set to ON

All results used taskset to bind processes to cores.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 42.5

Acer Altos R720 (Intel Xeon 5140)

SPECfp\_rate\_base2006 = 39.2

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

## Base Compiler Invocation

C benchmarks:

icc

C++ benchmarks:

icpc

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-fast

C++ benchmarks:

-fast

Fortran benchmarks:

-fast

Benchmarks using both Fortran and C:

-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Acer Incorporated**

**SPECfp\_rate2006 = 42.5**

**Acer Altos R720 (Intel Xeon 5140)**

**SPECfp\_rate\_base2006 = 39.2**

**CPU2006 license:** 97

**Test sponsor:** Acer Incorporated

**Tested by:** Acer Incorporated

**Test date:** Nov-2007

**Hardware Availability:** Nov-2006

**Software Availability:** Nov-2007

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
444.namd: -DSPEC_CPU_LP64
447.deallI: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 42.5

Acer Altos R720 (Intel Xeon 5140)

SPECfp\_rate\_base2006 = 39.2

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2006

Software Availability: Nov-2007

## Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll2

### C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4 -auto

### Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 42.5

Acer Altos R720 (Intel Xeon 5140)

SPECfp\_rate\_base2006 = 39.2

**CPU2006 license:** 97

**Test sponsor:** Acer Incorporated

**Tested by:** Acer Incorporated

**Test date:** Nov-2007

**Hardware Availability:** Nov-2006

**Software Availability:** Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 13:43:28 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 11 December 2007.