



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint®\_rate2006 = 74.1

Servidor Itaotec MX221 (Intel Xeon X5450)

SPECint\_rate\_base2006 = 62.0

CPU2006 license: 9001


Test sponsor: Itaotec

Tested by: Itaotec

Test date: May-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008



## Hardware

CPU Name: Intel Xeon X5450  
 CPU Characteristics:  
 CPU MHz: 3000  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores  
 L3 Cache: None  
 Other Cache: None  
 Memory: 16 GB (8 \* 2 GB PC2-5300 FBDIMM, CL-5-5-5, ECC)  
 Disk Subsystem: 1 x SCSI, 73GB, 15000 RPM  
 Other Hardware: None

## Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: Intel C++ Compiler for Linux version 10.1 Build 20080112 Package ID: l\_cc\_p\_10.1.012  
 Auto Parallel: Yes  
 File System: ReiserFS  
 System State: Run Level 3 (multi-user)  
 Base Pointers: 32-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Binutils 2.17.10.50  
 MicroQuill SmartHeap V8.1



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 74.1

Servidor Itaotec MX221 (Intel Xeon X5450)

SPECint\_rate\_base2006 = 62.0

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: May-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

## Results Table

Benchmark	Base						Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	514	76.1	<u>514</u>	<u>76.0</u>	515	75.9	4	426	91.7	<u>427</u>	<u>91.6</u>	432	90.6
401.bzip2	4	653	59.1	650	59.4	<u>651</u>	<u>59.3</u>	4	<u>605</u>	<u>63.8</u>	605	63.8	611	63.2
403.gcc	4	541	59.5	537	59.9	<u>537</u>	<u>59.9</u>	4	533	60.4	<u>534</u>	<u>60.3</u>	535	60.2
429.mcf	4	<u>664</u>	<u>54.9</u>	665	54.9	663	55.0	4	645	56.5	<u>645</u>	<u>56.6</u>	644	56.6
445.gobmk	4	<u>551</u>	<u>76.1</u>	557	75.3	547	76.7	4	502	83.5	<u>503</u>	<u>83.4</u>	513	81.7
456.hammer	4	590	63.3	592	63.0	<u>591</u>	<u>63.2</u>	4	349	107	346	108	<u>347</u>	<u>108</u>
458.sjeng	4	674	71.8	<u>675</u>	<u>71.7</u>	677	71.4	4	612	79.1	<u>612</u>	<u>79.0</u>	613	79.0
462.libquantum	4	<u>2325</u>	<u>35.6</u>	2327	35.6	2325	35.6	1	227	91.4	224	92.4	<u>226</u>	<u>91.6</u>
464.h264ref	4	705	125	<u>705</u>	<u>126</u>	705	126	4	<u>671</u>	<u>132</u>	673	132	670	132
471.omnetpp	4	607	41.2	607	41.2	<u>607</u>	<u>41.2</u>	4	585	42.7	<u>584</u>	<u>42.8</u>	583	42.9
473.astar	4	<u>626</u>	<u>44.9</u>	629	44.6	624	45.0	4	<u>577</u>	<u>48.7</u>	578	48.6	576	48.8
483.xalancbmk	4	358	77.0	<u>359</u>	<u>76.9</u>	359	76.9	4	358	77.0	<u>359</u>	<u>76.9</u>	359	76.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Compiler Invocation Notes

OMP\_NUM\_THREADS set to number of cores  
KMP\_STACK\_SIZE set to 64M  
KMP\_AFFINITY set to physical,0

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run.  
'/usr/bin/taskset' used to bind benchmark copies to processors, except for 462.libquantum at peak.

## Platform Notes

BIOS configuration:  
Hardware Prefetch Enabled

## General Notes

This result was measured on the Servidor Itaotec MX201.  
The Servidor Itaotec MX221 and the Servidor Itaotec MX201 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itaotec

SPECint\_rate2006 = 74.1

Servidor Itaotec MX221 (Intel Xeon X5450)

SPECint\_rate\_base2006 = 62.0

CPU2006 license: 9001  
Test sponsor: Itaotec  
Tested by: Itaotec

Test date: May-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:  
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:  
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs  
-L/opt/sh/SmartHeap\_8.1/lib -lsmartheap

## Base Other Flags

C benchmarks:  
403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):  
icc

401.bzip2: /opt/intel/cce/10.1.012/bin/icc  
-L/opt/intel/cce/10.1.012/lib  
-I/opt/intel/cce/10.1.012/include

456.hmmer: /opt/intel/cce/10.1.012/bin/icc  
-L/opt/intel/cce/10.1.012/lib  
-I/opt/intel/cce/10.1.012/include

C++ benchmarks:  
icpc



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECint\_rate2006 = 74.1

Servidor Itautec MX221 (Intel Xeon X5450)

SPECint\_rate\_base2006 = 62.0

CPU2006 license: 9001  
Test sponsor: Itautec  
Tested by: Itautec

Test date: May-2008  
Hardware Availability: Dec-2007  
Software Availability: Jan-2008

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32  
401.bzip2: -DSPEC\_CPU\_LP64  
456.hmmer: -DSPEC\_CPU\_LP64  
462.libquantum: -DSPEC\_CPU\_LINUX  
483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias  
-prefetch  
401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
403.gcc: -fast -inline-calloc -opt-malloc-options=3  
429.mcf: -fast -prefetch  
445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo  
-no-prec-div -ansi-alias  
456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive  
458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
462.libquantum: -fast -unroll4 -Ob0 -prefetch  
-opt-streaming-stores always -vec-guard-write  
-opt-malloc-options=3 -parallel -par-runtime-control  
464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=block  
-Wl,-z,muldefs -L/opt/sh/SmartHeap\_8.1/lib -lsmarheap  
473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo  
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine  
-Wl,-z,muldefs -L/opt/sh/SmartHeap\_8.1/lib -lsmarheap  
483.xalancbmk: basepeak = yes



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

SPECint\_rate2006 = 74.1

Servidor Itautec MX221 (Intel Xeon X5450)

SPECint\_rate\_base2006 = 62.0

CPU2006 license: 9001

Test sponsor: Itautec

Tested by: Itautec

Test date: May-2008

Hardware Availability: Dec-2007

Software Availability: Jan-2008

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-INT-intel64-linux-flags.20090714.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Itautec-ic10.1-INT-intel64-linux-flags.20090714.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.1.  
Report generated on Tue Jul 22 17:27:55 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 11 June 2008.