



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp®2006 = 26.4

Supermicro X7DB8+ (Intel Xeon X5470)

SPECfp_base2006 = 25.3

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Sep-2008

Hardware Availability: Sep-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon X5470
CPU Characteristics:
CPU MHz: 3333
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1, 2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores

Software

Operating System: SuSe Linux SLES10 SP2
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.042, l_fproc_b_11.0.042
Auto Parallel: Yes
File System: ReiserFS
System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation		SPECfp2006 =	26.4
Supermicro X7DB8+ (Intel Xeon X5470)		SPECfp_base2006 =	25.3
CPU2006 license:	13	Test date:	Sep-2008
Test sponsor:	Intel Corporation	Hardware Availability:	Sep-2008
Tested by:	Intel Corporation	Software Availability:	Nov-2008
L3 Cache:	None	Other Software:	Microquill SmartHeap V8.1
Other Cache:	None		Binutils 2.18.50.0.7.20080502
Memory:	16 GB(8x2 GB Samsung 5300F, CL5-5-5, 2 rank, ECC)		
Disk Subsystem:	36.4 GB HP SCSI, 15K RPM		
Other Hardware:	None		

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
410.bwaves	385	35.3	385	35.3	387	35.1	383	35.5	384	35.3	386	35.2
416.gamess	864	22.7	864	22.7	860	22.8	769	25.5	771	25.4	769	25.4
433.milc	562	16.3	559	16.4	561	16.4	566	16.2	567	16.2	567	16.2
434.zeusmp	418	21.8	417	21.8	418	21.8	418	21.8	417	21.8	418	21.8
435.gromacs	324	22.0	325	21.9	324	22.0	321	22.2	322	22.2	321	22.3
436.cactusADM	102	117	103	116	103	116	104	115	104	115	104	115
437.leslie3d	460	20.4	461	20.4	460	20.4	460	20.4	461	20.4	460	20.4
444.namd	442	18.1	443	18.1	443	18.1	445	18.0	445	18.0	445	18.0
447.dealII	373	30.7	374	30.6	374	30.6	344	33.3	344	33.3	345	33.2
450.soplex	589	14.2	589	14.2	590	14.1	532	15.7	531	15.7	533	15.6
453.povray	193	27.6	194	27.4	193	27.6	162	32.9	161	33.0	161	33.0
454.calculix	331	24.9	331	24.9	331	24.9	315	26.2	315	26.2	316	26.1
459.GemsFDTD	460	23.1	460	23.1	460	23.1	461	23.0	462	23.0	461	23.0
465.tonto	487	20.2	489	20.1	490	20.1	384	25.6	384	25.6	385	25.6
470.lbm	488	28.1	488	28.1	488	28.2	488	28.1	488	28.1	488	28.2
481.wrf	495	22.6	495	22.6	494	22.6	494	22.6	494	22.6	494	22.6
482.sphinx3	661	29.5	666	29.3	672	29.0	643	30.3	656	29.7	649	30.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

All benchmarks compiled in 64-bit mode except 450.soplex and 482.sphinx3, at peak, are compiled in 32-bit mode
 OMP_NUM_THREADS set to number of processors
 KMP_AFFINITY set to "physical,0"
 KMP_STACKSIZE set to 200M
 Adjacent Cache Line Prefetcher: Enabled

Base Compiler Invocation

C benchmarks:
 icc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation	SPECfp2006 =	26.4
Supermicro X7DB8+ (Intel Xeon X5470)	SPECfp_base2006 =	25.3
CPU2006 license: 13	Test date:	Sep-2008
Test sponsor: Intel Corporation	Hardware Availability:	Sep-2008
Tested by: Intel Corporation	Software Availability:	Nov-2008

Base Compiler Invocation (Continued)

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.games: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Fortran benchmarks:
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 26.4

Supermicro X7DB8+ (Intel Xeon X5470)

SPECfp_base2006 = 25.3

CPU2006 license: 13

Test date: Sep-2008

Test sponsor: Intel Corporation

Hardware Availability: Sep-2008

Tested by: Intel Corporation

Software Availability: Nov-2008

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

```
482.sphinx3: /opt/intel/Compiler/11.0/042/bin/ia32/icc  
          -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/Compiler/11.0/042/bin/ia32/icpc  
          -L/opt/intel/Compiler/11.0/042/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/042/ipp/ia32/include
```

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
        433.milc: -DSPEC_CPU_LP64  
        434.zeusmp: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
        444.namd: -DSPEC_CPU_LP64  
        447.dealII: -DSPEC_CPU_LP64  
        453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
        470.lbm: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3  
          -no-prec-div -static -fno-alias
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation	SPECfp2006 =	26.4
Supermicro X7DB8+ (Intel Xeon X5470)	SPECfp_base2006 =	25.3
CPU2006 license: 13	Test date:	Sep-2008
Test sponsor: Intel Corporation	Hardware Availability:	Sep-2008
Tested by: Intel Corporation	Software Availability:	Nov-2008

Peak Optimization Flags (Continued)

470.lbm: basepeak = yes

482.sphinx3: -xsse4.1 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias -scalar-rep-
-opt-prefetch

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xsse4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -Obo -ansi-alias
-scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -Obo -opt-prefetch
-parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xsse4.1 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

454.calculix: -xsse4.1 -ipo -O3 -no-prec-div -static -auto-ilp32

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECfp2006 = 26.4

Supermicro X7DB8+ (Intel Xeon X5470)

SPECfp_base2006 = 25.3

CPU2006 license: 13

Test date: Sep-2008

Test sponsor: Intel Corporation

Hardware Availability: Sep-2008

Tested by: Intel Corporation

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

481.wrf: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch
-parallel -auto-ilp32

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.09.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revA.20090713.09.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 20:55:04 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 1 October 2008.