



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

YOYOtech

(Test Sponsor: Future Publishing Ltd.)

SPECfp®_rate2006 = 88.3

Fi7EPOWER MLK1610 (Intel Core i7-965)

SPECfp_rate_base2006 = 84.7

CPU2006 license: 3772


Test sponsor: Future Publishing Ltd.

Tested by: Future Publishing Ltd.

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Core i7-965 Extreme Edition
CPU Characteristics: Intel Turbo Boost Technology disabled, clocked at 3.73 GHz
CPU MHz: 3733
FPU: Integrated
CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core
CPU(s) orderable: 1 chip
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Windows Vista Ultimate w/ SP1 (64-bit)
Compiler: Intel C++ Compiler Professional 11.0 for IA32
 Build 20080930 Package ID: w_cproc_p_11.0.054
 Intel Visual Fortran Compiler Professional 11.0 for IA32
 Build 20080930 Package ID: w_cprof_p_11.0.054
 Microsoft Visual Studio 2008 (for libraries)
Auto Parallel: No
File System: NTFS

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

YOYOtech

(Test Sponsor: Future Publishing Ltd.)

SPECfp_rate2006 = 88.3

Fi7EPOWER MLK1610 (Intel Core i7-965)

SPECfp_rate_base2006 = 84.7

CPU2006 license: 3772

Test sponsor: Future Publishing Ltd.

Tested by: Future Publishing Ltd.

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 9 GB (3x 2GB and 3x 1GB Corsair DDR3-1066, 9-9-9-24)
Disk Subsystem: 80 GB SATA, SSD
Other Hardware: None

System State: Default
Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: SmartHeap Library Version 8.1 from <http://www.microquill.com/>

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	1508	72.0	1508	72.0	1508	72.0	4	720	75.6	721	75.6	721	75.2
416.gamess	8	1498	105	1504	104	1502	104	8	1477	106	1478	106	1480	106
433.milc	8	1063	68.8	1063	68.8	1063	68.8	8	1063	68.8	1063	68.8	1064	68.8
434.zeusmp	8	742	98.4	740	98.4	738	98.4	8	694	105	692	105	697	105
435.gromacs	8	538	106	550	104	541	106	8	518	110	517	110	520	110
436.cactusADM	8	898	106	896	106	934	102	8	898	106	896	106	934	102
437.leslie3d	8	1499	50.4	1497	50.4	1497	50.4	8	1503	50.4	1505	49.6	1504	50.4
444.namd	8	629	102	630	102	629	102	8	614	105	620	103	616	104
447.dealII	8	815	112	807	114	801	114	8	697	131	681	134	691	133
450.soplex	8	1130	59.2	1129	59.2	1130	59.2	4	523	63.6	523	64.0	523	63.6
453.povray	8	286	149	287	148	277	154	8	234	182	229	186	230	186
454.calculix	8	543	122	543	122	543	122	8	542	122	539	122	543	122
459.GemsFDTD	8	1852	45.6	1850	45.6	1850	45.6	8	1858	45.6	1861	45.6	1863	45.6
465.tonto	8	798	98.4	765	103	799	98.4	8	751	105	753	105	753	105
470.lbm	8	2420	45.6	2421	45.6	2421	45.6	8	2421	45.6	2420	45.6	2421	45.6
481.wrf	8	1004	88.8	1005	88.8	1000	89.6	8	1004	88.8	1005	88.8	1000	89.6
482.sphinx3	8	1693	92.0	1695	92.0	1694	92.0	8	1692	92.0	1690	92.0	1691	92.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

General Notes

System was configured with HIS Radeon HD 4870 X2 discrete graphics card
Binaries were built on Windows Vista Ultimate (32-bit)

Base Compiler Invocation

C benchmarks:
icl -Qvc9 -Qc99

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

YOYOtech

(Test Sponsor: Future Publishing Ltd.)

SPECfp_rate2006 = 88.3

Fi7EPOWER MLK1610 (Intel Core i7-965)

SPECfp_rate_base2006 = 84.7

CPU2006 license: 3772

Test sponsor: Future Publishing Ltd.

Tested by: Future Publishing Ltd.

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Base Compiler Invocation (Continued)

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icl -Qvc9 -Qc99 ifort

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

C++ benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features
/F1000000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

Benchmarks using both Fortran and C:

-QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

Peak Compiler Invocation

C benchmarks:

icl -Qvc9 -Qc99

C++ benchmarks:

icl -Qvc9

Fortran benchmarks:

ifort

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

YOYOtech

(Test Sponsor: Future Publishing Ltd.)

SPECfp_rate2006 = 88.3

Fi7EPOWER MLK1610 (Intel Core i7-965)

SPECfp_rate_base2006 = 84.7

CPU2006 license: 3772

Test sponsor: Future Publishing Ltd.

Tested by: Future Publishing Ltd.

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:

icl -Qvc9 -Qc99 ifort

Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:

433.milc: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000

470.lbm: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
/F1000000000

482.sphinx3: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qunroll2 /F1000000000

C++ benchmarks:

444.namd: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

447.dealII: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias
-Qscalar-rep- /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

450.soplex: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

453.povray: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000
shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

YOYOtech

(Test Sponsor: Future Publishing Ltd.)

SPECfp_rate2006 = 88.3

Fi7EPOWER MLK1610 (Intel Core i7-965)

SPECfp_rate_base2006 = 84.7

CPU2006 license: 3772

Test sponsor: Future Publishing Ltd.

Tested by: Future Publishing Ltd.

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

410.bwaves: -QxSSE4.2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
/F1000000000

416.gamess: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias
-Qscalar-rep- /F1000000000

434.zeusmp: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- /F1000000000

437.leslie3d: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

459.GemsFDTD: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qopt-prefetch
/F1000000000

465.tonto: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000

Benchmarks using both Fortran and C:

435.gromacs: -QxSSE4.2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000

436.cactusADM: basepeak = yes

454.calculix: -QxSSE4.2 -Qipo -O3 -Qprec-div- /F1000000000

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.20090713.html>

<http://www.spec.org/cpu2006/flags/Intel-Win32-Platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.20090713.xml>

<http://www.spec.org/cpu2006/flags/Intel-Win32-Platform.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

YOYOtech

(Test Sponsor: Future Publishing Ltd.)

SPECfp_rate2006 = 88.3

Fi7EPOWER MLK1610 (Intel Core i7-965)

SPECfp_rate_base2006 = 84.7

CPU2006 license: 3772

Test sponsor: Future Publishing Ltd.

Tested by: Future Publishing Ltd.

Test date: Oct-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 22:27:12 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 January 2009.