



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp®\_rate2006 = 59.7

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

SPECfp\_rate\_base2006 = 53.2

CPU2006 license: 3


Test date: Dec-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2009

Tested by: Hewlett-Packard Company

Software Availability: Jun-2008



### Hardware

CPU Name: AMD Opteron 2384  
 CPU Characteristics: 2700  
 CPU MHz: 2700  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1,2 chips  
 Primary Cache: 64 KB I + 64 KB D on chip per core  
 Secondary Cache: 512 KB I+D on chip per core

Continued on next page

### Software

Operating System: SUSE Linux Enterprise Server 10 (x86\_64) SP1, Kernel 2.6.16.46-0.12-smp  
 Compiler: PGI Server Complete Version 7.2  
 PathScale Compiler Suite Version 3.2  
 Auto Parallel: Yes  
 File System: ext3  
 System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Hewlett-Packard Company

SPECfp\_rate2006 = 59.7

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

SPECfp\_rate\_base2006 = 53.2

CPU2006 license: 3

Test date: Dec-2008

Test sponsor: Hewlett-Packard Company

Hardware Availability: Jan-2009

Tested by: Hewlett-Packard Company

Software Availability: Jun-2008

L3 Cache: 6 MB I+D on chip per chip  
Other Cache: None  
Memory: 32 GB (8x4 GB, PC2-6400P CL5)  
Disk Subsystem: 1x250 GB 10 K SAS  
Other Hardware: None

Other Software: binutils 2.17.50  
32-bit and 64-bit libhugetlbfs libraries

## Results Table

| Benchmark     | Base   |             |             |             |             |             |             | Peak   |             |             |             |             |             |             |
|---------------|--------|-------------|-------------|-------------|-------------|-------------|-------------|--------|-------------|-------------|-------------|-------------|-------------|-------------|
|               | Copies | Seconds     | Ratio       | Seconds     | Ratio       | Seconds     | Ratio       | Copies | Seconds     | Ratio       | Seconds     | Ratio       | Seconds     | Ratio       |
| 410.bwaves    | 4      | 1030        | 52.8        | 1029        | 52.8        | <b>1030</b> | <b>52.8</b> | 4      | <b>992</b>  | <b>54.8</b> | 990         | 54.9        | 996         | 54.6        |
| 416.gamess    | 4      | <b>1166</b> | <b>67.2</b> | 1167        | 67.1        | 1164        | 67.3        | 4      | <b>1052</b> | <b>74.5</b> | 1051        | 74.5        | 1053        | 74.4        |
| 433.milc      | 4      | 922         | 39.8        | <b>923</b>  | <b>39.8</b> | 924         | 39.8        | 4      | 922         | 39.8        | <b>923</b>  | <b>39.8</b> | 924         | 39.8        |
| 434.zeusmp    | 4      | <b>627</b>  | <b>58.0</b> | 630         | 57.8        | 626         | 58.2        | 4      | 579         | 62.9        | <b>580</b>  | <b>62.8</b> | 583         | 62.4        |
| 435.gromacs   | 4      | 473         | 60.4        | <b>473</b>  | <b>60.4</b> | 473         | 60.4        | 4      | 386         | 73.9        | <b>386</b>  | <b>73.9</b> | 386         | 74.0        |
| 436.cactusADM | 4      | 775         | 61.7        | 773         | 61.9        | <b>773</b>  | <b>61.8</b> | 1      | <b>153</b>  | <b>78.2</b> | 153         | 78.2        | 153         | 77.9        |
| 437.leslie3d  | 4      | <b>1131</b> | <b>33.2</b> | 1132        | 33.2        | 1131        | 33.3        | 4      | 1056        | 35.6        | 1050        | 35.8        | <b>1052</b> | <b>35.7</b> |
| 444.namd      | 4      | <b>619</b>  | <b>51.8</b> | 619         | 51.8        | 619         | 51.8        | 4      | <b>536</b>  | <b>59.8</b> | 536         | 59.9        | 536         | 59.8        |
| 447.dealII    | 4      | 573         | 79.9        | 576         | 79.4        | <b>575</b>  | <b>79.5</b> | 4      | 437         | 105         | <b>437</b>  | <b>105</b>  | 434         | 105         |
| 450.soplex    | 4      | <b>883</b>  | <b>37.8</b> | 883         | 37.8        | 883         | 37.8        | 4      | 808         | 41.3        | <b>798</b>  | <b>41.8</b> | 798         | 41.8        |
| 453.povray    | 4      | 309         | 68.8        | <b>309</b>  | <b>68.9</b> | 309         | 69.0        | 4      | <b>260</b>  | <b>81.7</b> | 261         | 81.5        | 260         | 81.8        |
| 454.calculix  | 4      | 457         | 72.2        | <b>456</b>  | <b>72.4</b> | 455         | 72.5        | 4      | 385         | 85.8        | 384         | 85.9        | <b>384</b>  | <b>85.8</b> |
| 459.GemsFDTD  | 4      | 1304        | 32.5        | 1298        | 32.7        | <b>1301</b> | <b>32.6</b> | 4      | 1253        | 33.9        | <b>1253</b> | <b>33.9</b> | 1253        | 33.9        |
| 465.tonto     | 4      | <b>621</b>  | <b>63.4</b> | 622         | 63.3        | 620         | 63.5        | 4      | <b>507</b>  | <b>77.6</b> | 509         | 77.3        | 507         | 77.7        |
| 470.lbm       | 4      | 1738        | 31.6        | <b>1737</b> | <b>31.6</b> | 1737        | 31.6        | 4      | <b>1736</b> | <b>31.7</b> | 1736        | 31.7        | 1736        | 31.7        |
| 481.wrf       | 4      | <b>789</b>  | <b>56.6</b> | 786         | 56.8        | 791         | 56.5        | 4      | 747         | 59.8        | 745         | 59.9        | <b>746</b>  | <b>59.9</b> |
| 482.sphinx3   | 4      | <b>1033</b> | <b>75.5</b> | 1034        | 75.4        | 1033        | 75.5        | 4      | 962         | 81.1        | <b>960</b>  | <b>81.2</b> | 960         | 81.2        |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.  
numactl was used to bind copies to the cores

## Operating System Notes

Environment stack size set to 'unlimited'  
Max locked memory set to 2097152  
The libhugetlbfs libraries were installed using the installation rpms that came with the distribution.  
PGI\_HUGE\_PAGES set to 896.  
Total number of huge pages available is 3584.  
NCPUS set to number of cores



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 59.7**

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

**SPECfp\_rate\_base2006 = 53.2**

**CPU2006 license:** 3

**Test date:** Dec-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2009

**Tested by:** Hewlett-Packard Company

**Software Availability:** Jun-2008

## General Notes

Environment variables set by runspec before the start of the run:  
HUGETLB\_MORECORE = "yes"  
NCPUS = "4"

## Base Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -Mnomain  
436.cactusADM: -DSPEC\_CPU\_LP64 -Mnomain  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -Mnomain  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge -Mfprelaxed  
-Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic\_pgi

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 59.7**

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

**SPECfp\_rate\_base2006 = 53.2**

**CPU2006 license:** 3

**Test date:** Dec-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2009

**Tested by:** Hewlett-Packard Company

**Software Availability:** Jun-2008

## Base Optimization Flags (Continued)

C++ benchmarks:

-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge -Mfprelaxed  
--zc\_eh -Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic\_pgi

Fortran benchmarks:

-Mvect=cachesize:6291456 -fastsse -Mfprelaxed -Msmartalloc=huge  
-Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic\_pgi

Benchmarks using both Fortran and C:

-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge -Mfprelaxed  
-Mipa=fast -Mipa=inline -tp barcelona-64 -Bstatic\_pgi

## Base Other Flags

C benchmarks:

-Mipa=jobs:4

C++ benchmarks:

-Mipa=jobs:4

Fortran benchmarks:

-Mipa=jobs:4

Benchmarks using both Fortran and C:

-Mipa=jobs:4

## Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks (except as noted below):

pathCC

444.namd: pgcpp

Fortran benchmarks (except as noted below):

pathf95

410.bwaves: pgf95

434.zeusmp: pgf95

437.leslie3d: pgf95

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 59.7**

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

**SPECfp\_rate\_base2006 = 53.2**

**CPU2006 license:** 3

**Test date:** Dec-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2009

**Tested by:** Hewlett-Packard Company

**Software Availability:** Jun-2008

## Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C (except as noted below):

pgcc pgf95

435.gromacs: pathcc pathf95

481.wrf: pathcc pathf95

## Peak Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64  
 436.cactusADM: -DSPEC\_CPU\_LP64 -Mnomain  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -Mnomain  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX -fno-second-underscore  
 482.sphinx3: -DSPEC\_CPU\_LP64

## Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge  
-Mprefetch=t0 -Mloop32 -Mfprelaxed -Mipa=fast -Mipa=inline  
-tp barcelona-64 -Bstatic\_pgi

482.sphinx3: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)  
-Mipa=fast(pass 2) -Mipa=inline(pass 2)  
-Mvect=cachesize:6291456 -fastsse -Mfprelaxed -Msmartalloc  
-tp barcelona-64 -Bstatic\_pgi

C++ benchmarks:

444.namd: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)  
-Mipa=inline(pass 2) -Mvect=cachesize:6291456 -fastsse  
-Munroll=n:4 -Munroll=m:8 -Msmartalloc=huge -Mnodepch  
-Mfprelaxed --zc\_eh -tp barcelona-64 -Bstatic\_pgi

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 59.7**

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

**SPECfp\_rate\_base2006 = 53.2**

**CPU2006 license:** 3

**Test date:** Dec-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2009

**Tested by:** Hewlett-Packard Company

**Software Availability:** Jun-2008

## Peak Optimization Flags (Continued)

447.dealll: -march=barcelona -Ofast -static -INLINE:aggressive=on  
-fno-exceptions -m32

450.soplex: -march=barcelona -fb\_create fbdata(pass 1)  
-fb\_opt fbdata(pass 2) -L/usr/lib -lhugetlbfs(pass 2) -O3  
-INLINE:aggressive=on -OPT:IEEE\_arith=3  
-OPT:IEEE\_NaN\_Inf=off -OPT:fold\_unsigned\_relops=on  
-OPT:malloc\_alg=1 -CG:load\_exe=0 -fno-exceptions -m32

453.povray: -march=barcelona -fb\_create fbdata(pass 1)  
-fb\_opt fbdata(pass 2) -Ofast -INLINE:aggressive=on

Fortran benchmarks:

410.bwaves: -Mvect=cachesize:6291456 -fastsse -Msmartalloc  
-Mprefetch=nta -Mfpelaxed -Mipa=fast -Mipa=inline  
-tp barcelona-64 -Bstatic\_pgi

416.gamess: -march=barcelona -fb\_create fbdata(pass 1)  
-fb\_opt fbdata(pass 2)  
-Wl,-T/usr/share/libhugetlbfs/ldscripts/elf\_x86\_64.xBDT(pass 2)  
-L/usr/lib64 -lhugetlbfs(pass 2) -O2 -OPT:Ofast -OPT:ro=3  
-OPT:unroll\_size=256

434.zeusmp: -Mvect=cachesize:6291456 -fastsse -Mfpelaxed  
-Mprefetch=distance:8 -Mprefetch=t0 -Msmartalloc=huge  
-Msmartalloc=hugebss -Mipa=fast -Mipa=inline  
-tp barcelona-64 -Bstatic\_pgi

437.leslie3d: -Mphi=indirect(pass 1) -Mpfo=indirect(pass 2)  
-Mipa=fast(pass 2) -Mipa=inline(pass 2)  
-Mvect=cachesize:6291456 -fastsse -Mvect=fuse  
-Msmartalloc=huge -Mprefetch=distance:8 -Mprefetch=t0  
-Mfpelaxed -tp barcelona-64 -Bstatic\_pgi

459.GemsFDTD: -march=barcelona -Ofast -LNO:fission=2 -LNO:simd=2  
-LNO:prefetch\_ahead=1 -CG:load\_exe=0 -CG:prefer\_lru\_reg=off  
-OPT:malloc\_alg=1  
-Wl,-T/usr/share/libhugetlbfs/ldscripts/elf\_x86\_64.xBDT  
-L/usr/lib64 -lhugetlbfs

465.tonto: -march=barcelona -Ofast -OPT:alias=no\_f90\_pointer\_alias  
-LNO:blocking=off -CG:load\_exe=1 -IPA:plimit=525  
-OPT:malloc\_alg=1  
-Wl,-T/usr/share/libhugetlbfs/ldscripts/elf\_x86\_64.xBDT  
-L/usr/lib64 -lhugetlbfs

Benchmarks using both Fortran and C:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 59.7**

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

**SPECfp\_rate\_base2006 = 53.2**

**CPU2006 license:** 3

**Test date:** Dec-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2009

**Tested by:** Hewlett-Packard Company

**Software Availability:** Jun-2008

## Peak Optimization Flags (Continued)

435.gromacs: -march=barcelona -Ofast -OPT:rsqrt=2 -OPT:malloc\_alg=1  
-Wl,-T/usr/share/libhugetlbfs/ldscripts/elf\_x86\_64.xBDT  
-L/usr/lib64 -lhugetlbfs

436.cactusADM: -Mvect=cachesize:6291456 -fastsse -Mconcur  
-Msmartalloc=huge -Mfprelaxed -Mipa=fast -Mipa=inline  
-tp barcelona-64 -Bstatic\_pgi

454.calculix: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)  
-Mipa=fast(pass 2) -Mipa=inline(pass 2)  
-Mvect=cachesize:6291456 -fastsse -Msmartalloc=huge  
-Mprefetch=t0 -Mpre -Mfprelaxed -tp barcelona-64  
-Bstatic\_pgi

481.wrf: -march=barcelona -Ofast -LNO:blocking=off  
-LNO:prefetch\_ahead=10 -LANG:copyinout=off  
-IPA:callee\_limit=5000 -GRA:prioritize\_by\_density=on  
-OPT:malloc\_alg=1 -m3dnow  
-Wl,-T/usr/share/libhugetlbfs/ldscripts/elf\_x86\_64.xBDT  
-L/usr/lib64 -lhugetlbfs

## Peak Other Flags

C benchmarks:

-Mipa=jobs:4(pass 2)

C++ benchmarks:

444.namd: -Mipa=jobs:4(pass 2)

Fortran benchmarks (except as noted below):

-Mipa=jobs:4(pass 2)

416.gamess: No flags used

459.GemsFDTD: No flags used

465.tonto: No flags used

Benchmarks using both Fortran and C (except as noted below):

-Mipa=jobs:4(pass 2)

435.gromacs: No flags used

481.wrf: No flags used



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Hewlett-Packard Company**

**SPECfp\_rate2006 = 59.7**

ProLiant DL165 G5p  
(2.7 GHz AMD Opteron 2384)

**SPECfp\_rate\_base2006 = 53.2**

**CPU2006 license:** 3

**Test date:** Dec-2008

**Test sponsor:** Hewlett-Packard Company

**Hardware Availability:** Jan-2009

**Tested by:** Hewlett-Packard Company

**Software Availability:** Jun-2008

The flags files that were used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/pgi72\\_linux\\_flags.html](http://www.spec.org/cpu2006/flags/pgi72_linux_flags.html)  
[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090710.html](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090710.html)  
<http://www.spec.org/cpu2006/flags/amd-platform-amd909gh.20090710.html>

You can also download the XML flags sources by saving the following links:

[http://www.spec.org/cpu2006/flags/pgi72\\_linux\\_flags.xml](http://www.spec.org/cpu2006/flags/pgi72_linux_flags.xml)  
[http://www.spec.org/cpu2006/flags/CPU2006\\_flags.20090710.xml](http://www.spec.org/cpu2006/flags/CPU2006_flags.20090710.xml)  
<http://www.spec.org/cpu2006/flags/amd-platform-amd909gh.20090710.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.1.  
Report generated on Tue Jul 22 22:42:51 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 4 February 2009.