



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

SPECfp®_rate2006 = 147

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate_base2006 = 133

CPU2006 license: 001176


Test date: Sep-2009

Test sponsor: Supermicro

Hardware Availability: Jun-2009

Tested by: Supermicro

Software Availability: Apr-2009



Hardware

CPU Name: AMD Opteron 2439 SE
CPU Characteristics:
CPU MHz:
FPU: Integrated
CPU(s) enabled: 12 cores, 2 chips, 6 cores/chip
CPU(s) orderable: 1,2 chips
Primary Cache: 64 KB I + 64 KB D on chip per core
Secondary Cache: 512 KB I+D on chip per core

Software

Operating System: Red Hat Enterprise Linux Server release 5.3, Advanced Platform, Kernel 2.6.18-128.el5
Compiler: PGI Server Complete Version 8.0 x86 Open64 4.2.2 Compiler Suite (from AMD)
Auto Parallel: Yes
File System: ext3
System State: Run level 3 (Full multiuser with network)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

CPU2006 license: 001176

Test date: Sep-2009

Hardware Availability: Jun-2009

Software Availability: Apr-2009

Test sponsor: Supermicro

Tested by: Supermicro

L3 Cache: 6 MB I+D on chip per chip
 Other Cache: None
 Memory: 32 GB (8 x 4 GB, DDR2-800, CL5, Reg, Dual Rank)
 Disk Subsystem: 1 x 320 GB SATA, 7200 RPM
 Other Hardware: None

Other Software: binutils 2.18

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	12	1490	109	<u>1483</u>	110	1480	110	12	1444	113	<u>1446</u>	113	1448	113
416.gamess	12	1112	211	<u>1114</u>	211	1114	211	12	1030	228	1031	228	<u>1030</u>	228
433.milc	12	<u>1351</u>	81.6	1357	81.2	1344	81.9	12	<u>1351</u>	81.6	1357	81.2	1344	81.9
434.zeusmp	12	728	150	746	146	<u>735</u>	149	12	716	153	719	152	<u>718</u>	152
435.gromacs	12	<u>468</u>	183	468	183	467	183	12	385	223	<u>383</u>	223	383	224
436.cactusADM	12	<u>916</u>	157	912	157	924	155	2	118	203	<u>119</u>	201	120	198
437.leslie3d	12	1666	67.7	<u>1655</u>	68.2	1652	68.3	12	1551	72.7	<u>1557</u>	72.5	<u>1555</u>	72.5
444.namd	12	577	167	577	167	<u>577</u>	167	12	525	183	523	184	<u>523</u>	184
447.dealII	12	623	220	625	220	<u>624</u>	220	12	<u>458</u>	300	454	302	<u>463</u>	296
450.soplex	12	1208	82.9	1202	83.2	<u>1203</u>	83.2	12	1097	91.3	1094	91.4	<u>1096</u>	91.3
453.povray	12	298	214	<u>298</u>	214	298	214	12	248	258	249	257	<u>248</u>	257
454.calculix	12	<u>437</u>	227	436	227	437	226	12	388	255	387	256	<u>387</u>	256
459.GemsFDTD	12	1898	67.1	1903	66.9	<u>1903</u>	66.9	12	1859	68.5	<u>1861</u>	68.4	1862	68.4
465.tonto	12	<u>683</u>	173	687	172	677	175	12	564	209	569	207	<u>567</u>	208
470.lbm	12	2586	63.8	2580	63.9	<u>2581</u>	63.9	12	<u>2597</u>	63.5	2581	63.9	<u>2606</u>	63.3
481.wrf	12	1074	125	1075	125	<u>1075</u>	125	12	1037	129	<u>1036</u>	129	1032	130
482.sphinx3	12	1460	160	1447	162	<u>1453</u>	161	12	1312	178	1324	177	<u>1318</u>	177

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
 'numactl' was used to bind copies to the cores.
 See the configuration file for details.

Operating System Notes

'ulimit -s unlimited' was used to set environment stack size
 'ulimit -l 2097152' was used to set environment locked pages in memory limit

Set vm/nr_hugepages=5400 in /etc/sysctl.conf
 mount -t hugetlbfs nodev /mnt/hugepages



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

CPU2006 license: 001176

Test date: Sep-2009

Test sponsor: Supermicro

Hardware Availability: Jun-2009

Tested by: Supermicro

Software Availability: Apr-2009

General Notes

Environment variables set by runspec before the start of the run:

HUGETLB_LIMIT = "450"

LD_LIBRARY_PATH = "/usr/cpu2006/amd0905is-libs/64:/usr/cpu2006/amd0905is-libs/32"

NCPUS = "6"

PGI_HUGE_PAGES = "450"

The x86 Open64 Compiler Suite is only available from (and supported by) AMD at
<http://developer.amd.com/cpu/open64>

System was tested in an open environment.

ATX power supply 865W, PWS-865-PQ was used,
[2 8-pin (+12V), and 24-pin are provided]

Product description can be obtained at:

<http://www.supermicro.com/Aplus/motherboard/Opteron2000/SR56x0/H8DI3+-F.cfm>

Base Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -Mnomain
436.cactusADM: -DSPEC_CPU_LP64 -Mnomain
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -Mnomain
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

CPU2006 license: 001176

Test date: Sep-2009

Test sponsor: Supermicro

Hardware Availability: Jun-2009

Tested by: Supermicro

Software Availability: Apr-2009

Base Portability Flags (Continued)

481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-festsse -Msmartralloc=huge -Mfprelaxed -Mipa=fast -Mipa=inline
-tp shanghai-64 -Bstatic_pgi

C++ benchmarks:

-festsse -Msmartralloc=huge -Mfprelaxed --zc_eh -Mipa=fast
-Mipa=inline -tp shanghai-64 -Bstatic_pgi

Fortran benchmarks:

-festsse -Msmartralloc=huge -Mfprelaxed -Mvect=short -Mipa=fast
-Mipa=inline -tp shanghai-64 -Bstatic_pgi

Benchmarks using both Fortran and C:

-festsse -Msmartralloc=huge -Mfprelaxed -Mipa=fast -Mipa=inline
-tp shanghai-64 -Mvect=short -Bstatic_pgi

Base Other Flags

C benchmarks:

-Mipa=jobs:4

C++ benchmarks:

-Mipa=jobs:4

Fortran benchmarks:

-Mipa=jobs:4

Benchmarks using both Fortran and C:

-Mipa=jobs:4

Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks (except as noted below):

openCC

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

CPU2006 license: 001176

Test date: Sep-2009

Test sponsor: Supermicro

Hardware Availability: Jun-2009

Tested by: Supermicro

Software Availability: Apr-2009

Peak Compiler Invocation (Continued)

444.namd: pgcpp

Fortran benchmarks (except as noted below):

openf95

410.bwaves: pgf95

434.zeusmp: pgf95

437.leslie3d: pgf95

Benchmarks using both Fortran and C (except as noted below):

pgcc pgf95

435.gromacs: opencc openf95

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -Mnomain
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -Mnomain
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -fastsse -Msmartralloc=huge -Mprefetch=t0 -Mloop32
-Mfprelaxed -Mipa=fast -Mipa=inline -tp shanghai-64
-Bstatic_pgi

482.sphinx3: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse
-Mfprelaxed -Msmartralloc -tp shanghai-64 -Bstatic_pgi

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Sep-2009
Hardware Availability: Jun-2009
Software Availability: Apr-2009

Peak Optimization Flags (Continued)

C++ benchmarks:

```
444.namd: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
           -Mipa=inline(pass 2) -fastsse -Munroll=n:4 -Munroll=m:8
           -Msmaralloc=huge -Mnodepchk -Mfprelaxed --zc_eh
           -tp shanghai-64 -Bstatic_pgi

447.dealII: -march=barcelona -Ofast -static -INLINE:aggressive=on
            -LNO:opt=0 -Wf,-fno-exceptions -m32 -OPT:unroll_times_max=8
            -OPT:unroll_size=256 -OPT:unroll_level=2 -HP:bdt=2m:heap=2m
            -GRA:unspill=on -CG:cmp_peep=on -TENV:frame_pointer=off

450.soplex: -march=barcelona -fb_create fbdata(pass 1)
            -fb_opt fbdata(pass 2) -O3 -INLINE:aggressive=on
            -OPT:IEEE_arith=3 -OPT:IEEE_NaN_Inf=off
            -OPT:fold_unsigned_relops=on -OPT:malloc_alg=1
            -CG:load_exe=0 -fno-exceptions -m32 -HP:bdt=2m

453.povray: -march=barcelona -fb_create fbdata(pass 1)
            -fb_opt fbdata(pass 2) -Ofast -INLINE:aggressive=on
            -HP:bdt=2m:heap=2m
```

Fortran benchmarks:

```
410.bwaves: -fastsse -Msmaralloc -Mprefetch=nta -Mfprelaxed
            -Mipa=fast -Mipa=inline -tp shanghai-64 -Bstatic_pgi

416.gamess: -march=barcelona -fb_create fbdata(pass 1)
            -fb_opt fbdata(pass 2) -O2 -OPT:Ofast -OPT:ro=3
            -OPT:unroll_size=256 -HP:bdt=2m:heap=2m

434.zeusmp: -fastsse -Mfprelaxed -Mprefetch=distance:8 -Mprefetch=t0
            -Msmaralloc=huge -Msmaralloc=hugebss -Mipa=fast
            -Mipa=inline -tp shanghai-64 -Bstatic_pgi

437.leslie3d: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)
              -Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse
              -Mvect=fuse -Msmaralloc=huge -Mprefetch=distance:8
              -Mprefetch=t0 -Mfprelaxed -tp shanghai-64 -Bstatic_pgi

459.GemsFDTD: -march=barcelona -Ofast -LNO:fission=2 -LNO:simd=2
               -LNO:prefetch_ahead=1 -CG:load_exe=0 -HP

465.tonto: -march=barcelona -Ofast -OPT:alias=no_f90_pointer_alias
            -LNO:blocking=off -CG:load_exe=1 -IPA:plimit=525 -HP
```

Benchmarks using both Fortran and C:

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

CPU2006 license: 001176

Test date: Sep-2009

Test sponsor: Supermicro

Hardware Availability: Jun-2009

Tested by: Supermicro

Software Availability: Apr-2009

Peak Optimization Flags (Continued)

435.gromacs: -march=barcelona -Ofast -OPT:rsqrt=2 -HP:bdt=2m:heap=2m

436.cactusADM: -fastsse -Mconcur -Msmaralloc=huge -Mfrelaxed -Mipa=fast
-Mipa=inline -tp shanghai-64 -Bstatic_pgi

454.calculix: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2)
-Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse
-Mvect=short -Msmaralloc=huge -Mprefetch=t0 -Mpre
-Mfrelaxed -tp shanghai-64 -Bstatic_pgi

481.wrf: -fastsse -Mvect=noaltcode -Msmaralloc=huge
-Mprefetch=distance:8 -Mfrelaxed -tp shanghai-64
-Bstatic_pgi

Peak Other Flags

C benchmarks:

-Mipa=jobs:4(pass 2)

C++ benchmarks:

444.namd: -Mipa=jobs:4(pass 2)

Fortran benchmarks:

410.bwaves: -Mipa=jobs:4

434.zeusmp: -Mipa=jobs:4

437.leslie3d: -Mipa=jobs:4(pass 2)

Benchmarks using both Fortran and C:

436.cactusADM: -Mipa=jobs:4

454.calculix: -Mipa=jobs:4(pass 2)

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/amd-platform.20090710.html>
http://www.spec.org/cpu2006/flags/pgi80_linux_flags.20090914.html
<http://www.spec.org/cpu2006/flags/x86-open64-4.2.2-flags-revE.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/amd-platform.20090710.xml>
http://www.spec.org/cpu2006/flags/pgi80_linux_flags.20090914.xml
<http://www.spec.org/cpu2006/flags/x86-open64-4.2.2-flags-revE.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro

Motherboard H8DI3+-F, AMD Opteron 2439 SE

SPECfp_rate2006 = 147

SPECfp_rate_base2006 = 133

CPU2006 license: 001176

Test date: Sep-2009

Test sponsor: Supermicro

Hardware Availability: Jun-2009

Tested by: Supermicro

Software Availability: Apr-2009

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Wed Jul 23 02:41:20 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 30 September 2009.