



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp[®]2006 = **68.2**

Compute Blade 520H (Intel Xeon E5-2637)

SPECfp_base2006 = **66.3**

CPU2006 license: 35


Test sponsor: HITACHI

Tested by: HITACHI

Test date: Oct-2012

Hardware Availability: Nov-2012

Software Availability: Feb-2012



Hardware

CPU Name: Intel Xeon E5-2637
 CPU Characteristics: Intel Turbo Boost Technology up to 3.50 GHz
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip, 2 threads/core
 CPU(s) orderable: 1, 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

Software

Operating System: Red Hat Enterprise Linux Server release 6.2, Kernel 2.6.32-220.4.2.el6.x86_64
 Compiler: C/C++: Version 12.1.0.225 of Intel C++ Studio XE for Linux;
 Fortran: Version 12.1.0.225 of Intel Fortran Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4
 System State: Run level 3 (multi-user)

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = **68.2**

Compute Blade 520H (Intel Xeon E5-2637)

SPECfp_base2006 = **66.3**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Oct-2012

Hardware Availability: Nov-2012

Software Availability: Feb-2012

L3 Cache: 5 MB I+D on chip per chip
 Other Cache: None
 Memory: 128 GB (16 x 8 GB 2Rx4 PC3L-12800R-11, ECC)
 Disk Subsystem: 1 x 146 GB SAS, 15000 RPM
 Other Hardware: None

Base Pointers: 64-bit
 Peak Pointers: 32/64-bit
 Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>59.9</u>	<u>227</u>	59.9	227	59.7	228	59.7	228	<u>59.7</u>	<u>228</u>	59.5	228
416.gamess	<u>599</u>	<u>32.7</u>	599	32.7	602	32.5	543	36.1	<u>543</u>	<u>36.0</u>	544	36.0
433.milc	154	59.7	<u>154</u>	<u>59.6</u>	154	59.6	152	60.4	<u>152</u>	<u>60.4</u>	153	60.0
434.zeusmp	99.3	91.7	98.9	92.0	<u>99.1</u>	<u>91.9</u>	99.3	91.7	98.9	92.0	<u>99.1</u>	<u>91.9</u>
435.gromacs	192	37.2	191	37.4	<u>191</u>	<u>37.4</u>	192	37.2	191	37.4	<u>191</u>	<u>37.4</u>
436.cactusADM	66.4	180	66.4	180	<u>66.4</u>	<u>180</u>	66.4	180	66.4	180	<u>66.4</u>	<u>180</u>
437.leslie3d	81.2	116	<u>81.2</u>	<u>116</u>	80.0	117	81.2	116	<u>81.2</u>	<u>116</u>	80.0	117
444.namd	336	23.9	<u>336</u>	<u>23.9</u>	336	23.9	<u>331</u>	<u>24.3</u>	330	24.3	331	24.3
447.dealII	219	52.3	219	52.2	<u>219</u>	<u>52.3</u>	219	52.3	219	52.2	<u>219</u>	<u>52.3</u>
450.soplex	<u>249</u>	<u>33.6</u>	248	33.6	249	33.5	<u>249</u>	<u>33.6</u>	248	33.6	249	33.5
453.povray	<u>120</u>	<u>44.4</u>	120	44.3	120	44.4	102	52.3	<u>101</u>	<u>52.5</u>	101	52.6
454.calculix	205	40.2	206	40.0	<u>206</u>	<u>40.1</u>	<u>195</u>	<u>42.4</u>	194	42.5	195	42.4
459.GemsFDTD	121	87.5	<u>121</u>	<u>87.7</u>	121	87.9	115	92.3	<u>115</u>	<u>92.6</u>	114	92.8
465.tonto	<u>241</u>	<u>40.9</u>	241	40.8	240	41.0	<u>227</u>	<u>43.4</u>	227	43.4	227	43.3
470.lbm	53.2	258	<u>53.2</u>	<u>258</u>	53.4	257	53.2	258	<u>53.2</u>	<u>258</u>	53.4	257
481.wrf	155	72.0	<u>152</u>	<u>73.3</u>	152	73.7	155	72.0	<u>152</u>	<u>73.3</u>	152	73.7
482.sphinx3	339	57.5	<u>336</u>	<u>58.0</u>	331	59.0	339	57.5	<u>336</u>	<u>58.0</u>	331	59.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Sysinfo program /home/cpu2006/config/sysinfo.rev6800
 \$Rev: 6800 \$ \$Date:: 2011-10-11 #\$ 6f2ebdff5032aaa42e583f96b07f99d3
 running on localhost.localdomain Sat Oct 27 02:14:04 2012

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:
<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo
 model name : Intel(R) Xeon(R) CPU E5-2637 0 @ 3.00GHz
 Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 68.2

Compute Blade 520H (Intel Xeon E5-2637)

SPECfp_base2006 = 66.3

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Oct-2012

Hardware Availability: Nov-2012

Software Availability: Feb-2012

Platform Notes (Continued)

```

2 "physical id"s (chips)
8 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
cpu cores : 2
siblings  : 4
physical 0: cores 0 1
physical 1: cores 0 1
cache size : 5120 KB

From /proc/meminfo
MemTotal:      132136072 kB
HugePages_Total: 0
Hugepagesize:  2048 kB

/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.2 (Santiago)

From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.2 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server

uname -a:
Linux localhost.localdomain 2.6.32-220.4.2.el6.x86_64 #1 SMP Mon Feb 6
16:39:28 EST 2012 x86_64 x86_64 x86_64 GNU/Linux

run-level 3 Oct 27 00:39

(End of data from sysinfo program)

```

General Notes

Environment variables set by runspec before the start of the run:

KMP_AFFINITY = "granularity=fine,compact,1,0"

LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64"

OMP_NUM_THREADS = "4"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RHEL5.5

Transparent Huge Pages disabled with:

echo never > /sys/kernel/mm/redhat_transparent_hugepage/enabled

HITACHI BladeSymphony BS520H and HITACHI Compute Blade 520H are electronically equivalent. The results have been measured on a HITACHI BladeSymphony BS520H.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 68.2

Compute Blade 520H (Intel Xeon E5-2637)

SPECfp_base2006 = 66.3

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Oct-2012

Hardware Availability: Nov-2012

Software Availability: Feb-2012

Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
 416.gamess: -DSPEC_CPU_LP64
 433.milc: -DSPEC_CPU_LP64
 434.zeusmp: -DSPEC_CPU_LP64
 435.gromacs: -DSPEC_CPU_LP64 -nofor_main
 436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 437.leslie3d: -DSPEC_CPU_LP64
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 450.soplex: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
 459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
 482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias

C++ benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xAVX -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
-ansi-alias



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 68.2

Compute Blade 520H (Intel Xeon E5-2637)

SPECfp_base2006 = 66.3

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Oct-2012

Hardware Availability: Nov-2012

Software Availability: Feb-2012

Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -static -auto-ilp32
-ansi-alias

470.lbm: basepeak = yes

482.sphinx3: basepeak = yes

C++ benchmarks:

444.namd: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -fno-alias
-auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xAVX -ipo -O3 -no-prec-div -opt-prefetch -parallel
-static

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

HITACHI

SPECfp2006 = 68.2

Compute Blade 520H (Intel Xeon E5-2637)

SPECfp_base2006 = 66.3

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Oct-2012

Hardware Availability: Nov-2012

Software Availability: Feb-2012

Peak Optimization Flags (Continued)

416.gamess: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -unroll2
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xAVX(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2)
-no-prec-div(pass 2) -prof-use(pass 2) -inline-calloc
-opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xAVX -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20120829.html>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic12.1-official-linux64.20120829.xml>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.

Report generated on Thu Jul 24 14:03:29 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 November 2012.

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org/>

Page 6