



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECfp®2006 = **75.2**

Express5800/T110f-E (Intel Xeon E3-1270 v3)

SPECfp\_base2006 = **73.8**

CPU2006 license: 9006


Test date: Oct-2013

Test sponsor: NEC Corporation

Hardware Availability: Oct-2013

Tested by: NEC Corporation

Software Availability: Mar-2013



### Hardware

CPU Name: Intel Xeon E3-1270 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.90 GHz  
 CPU MHz: 3500  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip, 2 threads/core  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
 Kernel 2.6.32-358.el6.x86\_64  
 Compiler: C/C++: Version 13.1.1.163 of Intel C++ Studio XE for Linux;  
 Fortran: Version 13.1.1.163 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

SPECfp2006 = **75.2**

Express5800/T110f-E (Intel Xeon E3-1270 v3)

SPECfp\_base2006 = **73.8**

CPU2006 license: 9006

Test date: Oct-2013

Test sponsor: NEC Corporation

Hardware Availability: Oct-2013

Tested by: NEC Corporation

Software Availability: Mar-2013

L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (2 x 8 GB 2Rx8 PC3L-12800E-11, ECC)  
 Disk Subsystem: 1 x 250 GB SATA, 7200 RPM  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: None

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	118	115	117	116	<b><u>117</u></b>	<b><u>116</u></b>	118	115	117	116	<b><u>117</u></b>	<b><u>116</u></b>
416.gamess	449	43.6	452	43.4	<b><u>451</u></b>	<b><u>43.4</u></b>	408	48.0	408	48.0	<b><u>408</u></b>	<b><u>48.0</u></b>
433.milc	<b><u>106</u></b>	<b><u>86.6</u></b>	106	86.8	106	86.6	105	87.5	105	87.2	<b><u>105</u></b>	<b><u>87.2</u></b>
434.zeusmp	78.0	117	<b><u>77.8</u></b>	<b><u>117</u></b>	77.8	117	78.0	117	<b><u>77.8</u></b>	<b><u>117</u></b>	77.8	117
435.gromacs	152	47.0	152	47.1	<b><u>152</u></b>	<b><u>47.0</u></b>	152	47.0	152	47.1	<b><u>152</u></b>	<b><u>47.0</u></b>
436.cactusADM	46.8	256	<b><u>47.1</u></b>	<b><u>253</u></b>	48.1	248	46.8	256	<b><u>47.1</u></b>	<b><u>253</u></b>	48.1	248
437.leslie3d	114	82.5	<b><u>114</u></b>	<b><u>82.4</u></b>	114	82.4	114	82.5	<b><u>114</u></b>	<b><u>82.4</u></b>	114	82.4
444.namd	<b><u>261</u></b>	<b><u>30.7</u></b>	261	30.7	261	30.7	254	31.5	<b><u>254</u></b>	<b><u>31.5</u></b>	254	31.5
447.dealII	163	70.2	<b><u>163</u></b>	<b><u>70.2</u></b>	163	70.0	163	70.2	<b><u>163</u></b>	<b><u>70.2</u></b>	163	70.0
450.soplex	203	41.1	202	41.3	<b><u>203</u></b>	<b><u>41.1</u></b>	203	41.1	202	41.3	<b><u>203</u></b>	<b><u>41.1</u></b>
453.povray	82.4	64.6	<b><u>81.6</u></b>	<b><u>65.2</u></b>	80.4	66.2	73.1	72.8	73.2	72.7	<b><u>73.1</u></b>	<b><u>72.7</u></b>
454.calculix	161	51.1	161	51.1	<b><u>161</u></b>	<b><u>51.1</u></b>	157	52.6	<b><u>157</u></b>	<b><u>52.5</u></b>	157	52.4
459.GemsFDTD	<b><u>157</u></b>	<b><u>67.7</u></b>	157	67.6	157	67.7	<b><u>157</u></b>	<b><u>67.7</u></b>	157	67.6	157	67.7
465.tonto	197	50.1	<b><u>197</u></b>	<b><u>50.0</u></b>	197	49.9	186	52.9	<b><u>186</u></b>	<b><u>52.8</u></b>	187	52.7
470.lbm	<b><u>97.9</u></b>	<b><u>140</u></b>	97.8	140	98.0	140	<b><u>97.9</u></b>	<b><u>140</u></b>	97.8	140	98.0	140
481.wrf	<b><u>113</u></b>	<b><u>98.5</u></b>	115	97.2	113	98.5	<b><u>113</u></b>	<b><u>98.5</u></b>	115	97.2	113	98.5
482.sphinx3	<b><u>239</u></b>	<b><u>81.5</u></b>	242	80.5	238	81.8	233	83.5	237	82.3	<b><u>236</u></b>	<b><u>82.6</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:  
Energy Performance: Performance

## General Notes

Environment variables set by runspec before the start of the run:  
 LD\_LIBRARY\_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"  
 OMP\_NUM\_THREADS = "4"

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 75.2

Express5800/T110f-E (Intel Xeon E3-1270 v3)

SPECfp\_base2006 = 73.8

CPU2006 license: 9006

Test date: Oct-2013

Test sponsor: NEC Corporation

Hardware Availability: Oct-2013

Tested by: NEC Corporation

Software Availability: Mar-2013

## General Notes (Continued)

Added glibc-static-2.12-1.107.el6.x86\_64.rpm to enable static linking

Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.deallI: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 75.2

Express5800/T110f-E (Intel Xeon E3-1270 v3)

SPECfp\_base2006 = 73.8

CPU2006 license: 9006

Test date: Oct-2013

Test sponsor: NEC Corporation

Hardware Availability: Oct-2013

Tested by: NEC Corporation

Software Availability: Mar-2013

## Base Optimization Flags (Continued)

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -static -opt-prefetch -ansi-alias

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -static  
-auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel

C++ benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 75.2

Express5800/T110f-E (Intel Xeon E3-1270 v3)

SPECfp\_base2006 = 73.8

CPU2006 license: 9006

Test date: Oct-2013

Test sponsor: NEC Corporation

Hardware Availability: Oct-2013

Tested by: NEC Corporation

Software Availability: Mar-2013

## Peak Optimization Flags (Continued)

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4  
-ansi-alias

### Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep- -static

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-inline-calloc -opt-malloc-options=3 -auto -unroll4

### Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic13-official-linux64.20130702.html>

<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120d-RevA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic13-official-linux64.20130702.xml>

<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-R120d-RevA.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

SPECfp2006 = 75.2

Express5800/T110f-E (Intel Xeon E3-1270 v3)

SPECfp\_base2006 = 73.8

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Oct-2013

Hardware Availability: Oct-2013

Software Availability: Mar-2013

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Thu Jul 24 17:36:24 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 19 November 2013.