



# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

CPU2006 license: 001176


Test date: Jun-2014

Test sponsor: Supermicro

Hardware Availability: Dec-2013

Tested by: Supermicro

Software Availability: Sep-2013



Hardware	
CPU Name:	Intel Xeon E5-2660 v2
CPU Characteristics:	Intel Turbo Boost Technology up to 3.00 GHz
CPU MHz:	2200
FPU:	Integrated
CPU(s) enabled:	20 cores, 2 chips, 10 cores/chip, 2 threads/core
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	25 MB I+D on chip per chip
Other Cache:	None
Memory:	128 GB (8 x 16 GB 2Rx4 PC3-14900R-13, ECC)
Disk Subsystem:	1 x 1 TB SATA II, 7200 RPM
Other Hardware:	None

Software	
Operating System:	Red Hat Enterprise Linux Server release 6.4, Kernel 2.6.32-358.el6.x86_64
Compiler:	C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux; Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux
Auto Parallel:	No
File System:	ext4
System State:	Run level 3 (multi-user)
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V10.0



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro**

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

**CPU2006 license:** 001176

**Test date:** Jun-2014

**Test sponsor:** Supermicro

**Hardware Availability:** Dec-2013

**Tested by:** Supermicro

**Software Availability:** Sep-2013

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	40	735	532	739	529	<b>737</b>	<b>530</b>	40	613	637	<b>613</b>	<b>638</b>	611	640
401.bzip2	40	1005	384	<b>1005</b>	<b>384</b>	1010	382	40	988	391	<b>988</b>	<b>391</b>	986	391
403.gcc	40	569	565	568	567	<b>568</b>	<b>567</b>	40	<b>570</b>	<b>565</b>	571	564	570	565
429.mcf	40	342	1070	343	1060	<b>342</b>	<b>1070</b>	40	342	1070	343	1060	<b>342</b>	<b>1070</b>
445.gobmk	40	804	522	<b>804</b>	<b>522</b>	788	532	40	776	541	<b>784</b>	<b>535</b>	788	533
456.hammer	40	387	965	<b>388</b>	<b>963</b>	388	962	40	355	1050	352	1060	<b>354</b>	<b>1050</b>
458.sjeng	40	<b>930</b>	<b>520</b>	932	519	929	521	40	895	541	895	541	<b>895</b>	<b>541</b>
462.libquantum	40	177	4680	<b>177</b>	<b>4680</b>	177	4680	40	177	4680	<b>177</b>	<b>4680</b>	177	4680
464.h264ref	40	997	888	<b>1001</b>	<b>884</b>	1007	879	40	990	894	<b>990</b>	<b>894</b>	987	896
471.omnetpp	40	<b>647</b>	<b>386</b>	647	386	648	386	40	614	407	<b>613</b>	<b>408</b>	613	408
473.astar	40	<b>699</b>	<b>402</b>	700	401	697	403	40	<b>699</b>	<b>402</b>	700	401	697	403
483.xalancbmk	40	<b>360</b>	<b>766</b>	360	768	360	766	40	<b>360</b>	<b>766</b>	360	768	360	766

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Configuration:

Disable C1E Support, DRAM RAPL Mode, Demand Scrub, Double Refresh.

Set Package C-state Limit to C0

Sysinfo program /usr/cpu2006/config/sysinfo.rev6818

\$Rev: 6818 \$ \$Date::: 2012-07-17 #\\$ e86d102572650a6e4d596a3cee98f191

running on 194-195.jnet Thu Jun 5 00:39:55 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2660 v2 @ 2.20GHz

2 "physical id"s (chips)

40 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Jun-2014

**Hardware Availability:** Dec-2013

**Software Availability:** Sep-2013

## Platform Notes (Continued)

```
caution.)  
    cpu cores : 10  
    siblings   : 20  
    physical 0: cores 0 1 2 3 4 8 9 10 11 12  
    physical 1: cores 0 1 2 3 4 8 9 10 11 12  
    cache size : 25600 KB  
  
From /proc/meminfo  
MemTotal:      132121112 kB  
HugePages_Total:        0  
Hugepagesize:     2048 kB  
  
/usr/bin/lsb_release -d  
Red Hat Enterprise Linux Server release 6.4 (Santiago)  
  
From /etc/*release* /etc/*version*  
redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)  
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server  
  
uname -a:  
Linux 194-195.jnet 2.6.32-358.18.1.el6.x86_64 #1 SMP Fri Aug 2 17:04:38 EDT  
2013 x86_64 x86_64 x86_64 GNU/Linux  
  
run-level 3 Jun 5 00:25  
  
SPEC is set to: /usr/cpu2006  
Filesystem      Type  Size  Used Avail Use% Mounted on  
/dev/sda2        ext4   1.3T  428G  833G  34% /  
  
Additional information from dmidecode:  
BIOS American Megatrends Inc. 3.0a 12/06/2013  
Memory:  
 8x 16 GB  
 1x DimmA2_Manufacturer DimmA2_PartNumber  
 1x DimmA3_Manufacturer DimmA3_PartNumber  
 1x DimmB2_Manufacturer DimmB2_PartNumber  
 1x DimmB3_Manufacturer DimmB3_PartNumber  
 1x DimmC2_Manufacturer DimmC2_PartNumber  
 1x DimmC3_Manufacturer DimmC3_PartNumber  
 1x DimmD2_Manufacturer DimmD2_PartNumber  
 1x DimmD3_Manufacturer DimmD3_PartNumber  
 1x DimmE2_Manufacturer DimmE2_PartNumber  
 1x DimmE3_Manufacturer DimmE3_PartNumber  
 1x DimmF2_Manufacturer DimmF2_PartNumber  
 1x DimmF3_Manufacturer DimmF3_PartNumber  
 1x DimmG2_Manufacturer DimmG2_PartNumber  
 1x DimmG3_Manufacturer DimmG3_PartNumber  
 1x DimmH2_Manufacturer DimmH2_PartNumber  
 1x DimmH3_Manufacturer DimmH3_PartNumber  
 8x Hynix Semiconductor HMT42GR7AFR4C-RD 16 GB 1866 MHz 2 rank
```

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

**CPU2006 license:** 001176

**Test date:** Jun-2014

**Test sponsor:** Supermicro

**Hardware Availability:** Dec-2013

**Tested by:** Supermicro

**Software Availability:** Sep-2013

## Platform Notes (Continued)

(End of data from sysinfo program)

Only 8 DIMMs are installed. Please ignore extra info above.

## General Notes

Environment variables set by runspec before the start of the run:

LD\_LIBRARY\_PATH = "/usr/cpu2006/lib32:/usr/cpu2006/lib64:/usr/cpu2006/sh"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB  
memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop\_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

## Base Compiler Invocation

C benchmarks:

icc -m32

C++ benchmarks:

icpc -m32

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LINUX\_IA32

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3

C++ benchmarks:

-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -opt-mem-layout-trans=3  
-Wl,-z,muldefs -L/sh -lsmartheap



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Jun-2014

**Hardware Availability:** Dec-2013

**Software Availability:** Sep-2013

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m32

400.perlbench: icc -m64

401.bzip2: icc -m64

456.hmmer: icc -m64

458.sjeng: icc -m64

C++ benchmarks:

icpc -m32

## Peak Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64

401.bzip2: -DSPEC\_CPU\_LP64

456.hmmer: -DSPEC\_CPU\_LP64

458.sjeng: -DSPEC\_CPU\_LP64

462.libquantum: -DSPEC\_CPU\_LINUX

483.xalancbmk: -DSPEC\_CPU\_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

**CPU2006 license:** 001176

**Test sponsor:** Supermicro

**Tested by:** Supermicro

**Test date:** Jun-2014

**Hardware Availability:** Dec-2013

**Software Availability:** Sep-2013

## Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)  
-ansi-alias -opt-mem-layout-trans=3

456.hummer: -xSSE4.2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll14 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs  
-L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>  
<http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revD.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>  
<http://www.spec.org/cpu2006/flags/Supermicro-Platform-Settings-V1.2-revD.xml>



# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Supermicro**

Supermicro SuperServer 2027R-72RFTP+  
(X9DRW-7TPF+, Intel Xeon E5-2660 v2)

**SPECint\_rate2006 = 733**

**SPECint\_rate\_base2006 = 708**

**CPU2006 license:** 001176

**Test date:** Jun-2014

**Test sponsor:** Supermicro

**Hardware Availability:** Dec-2013

**Tested by:** Supermicro

**Software Availability:** Sep-2013

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Fri Jul 25 00:20:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 23 July 2014.