



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint®2006 = **55.5**

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = **53.0**

CPU2006 license: 9046

Test date: Oct-2014

Test sponsor: Sugon

Hardware Availability: Sep-2014

Tested by: Sugon

Software Availability: Sep-2013



Hardware

CPU Name: Intel Xeon E5-2660 v3
 CPU Characteristics: Intel Turbo Boost Technology up to 3.30 GHz
 CPU MHz: 2600
 FPU: Integrated
 CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core
 CPU(s) orderable: 1,2 chip
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 256 KB I+D on chip per core
 L3 Cache: 25 MB I+D on chip per chip
 Other Cache: None
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)
 Disk Subsystem: 1 x 2.0 TB SATA 7200 RPM
 Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 6.4 (Santiago)
 2.6.32-358.el6.x86_64
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux
 Auto Parallel: Yes
 File System: ext4
 System State: Run level 3 (multi-user)
 Base Pointers: 32/64-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V10.0



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = **55.5**

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = **53.0**

CPU2006 license: 9046
Test sponsor: Sugon
Tested by: Sugon

Test date: Oct-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2013

Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|----------------|------------|-------------|-------------|-------------|------------|-------------|------------|-------------|-------------|-------------|------------|-------------|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 299 | 32.6 | 299 | 32.7 | <u>299</u> | <u>32.6</u> | 253 | 38.5 | <u>254</u> | <u>38.5</u> | 254 | 38.5 |
| 401.bzip2 | <u>464</u> | <u>20.8</u> | 463 | 20.8 | 464 | 20.8 | 460 | 21.0 | <u>460</u> | <u>21.0</u> | 460 | 21.0 |
| 403.gcc | 264 | 30.4 | 264 | 30.5 | <u>264</u> | <u>30.5</u> | <u>261</u> | <u>30.9</u> | 261 | 30.9 | 260 | 31.0 |
| 429.mcf | 164 | 55.6 | <u>165</u> | <u>55.3</u> | 165 | 55.3 | 164 | 55.5 | <u>165</u> | <u>55.4</u> | 165 | 55.3 |
| 445.gobmk | 441 | 23.8 | 441 | 23.8 | <u>441</u> | <u>23.8</u> | 434 | 24.2 | <u>434</u> | <u>24.2</u> | 434 | 24.2 |
| 456.hammer | 161 | 57.8 | <u>162</u> | <u>57.5</u> | 163 | 57.3 | 161 | 57.8 | <u>162</u> | <u>57.5</u> | 163 | 57.3 |
| 458.sjeng | 431 | 28.1 | <u>432</u> | <u>28.0</u> | 432 | 28.0 | 426 | 28.4 | <u>427</u> | <u>28.4</u> | 427 | 28.3 |
| 462.libquantum | 3.85 | 5380 | <u>3.85</u> | <u>5380</u> | 4.05 | 5120 | 3.85 | 5380 | <u>3.85</u> | <u>5380</u> | 4.05 | 5120 |
| 464.h264ref | <u>474</u> | <u>46.7</u> | 473 | 46.8 | 477 | 46.4 | <u>474</u> | <u>46.7</u> | 473 | 46.8 | 477 | 46.4 |
| 471.omnetpp | 215 | 29.1 | <u>217</u> | <u>28.8</u> | 218 | 28.6 | 151 | 41.3 | 156 | 40.1 | <u>155</u> | <u>40.4</u> |
| 473.astar | 252 | 27.8 | <u>252</u> | <u>27.9</u> | 251 | 28.0 | 252 | 27.8 | <u>252</u> | <u>27.9</u> | 251 | 28.0 |
| 483.xalancbmk | 125 | 55.2 | <u>125</u> | <u>55.2</u> | 124 | 55.4 | 125 | 55.2 | <u>125</u> | <u>55.2</u> | 124 | 55.4 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

BIOS Configuration:

Enforce POR set to disabled

DDR Speed set to 2133

Early Snoop set to disabled

COD set to disable

Power Technology set to performance

Sysinfo program /home/cpu2006/config/sysinfo.rev6818

\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191

running on localhost.localdomain Thu Oct 9 09:54:00 2014

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2660 v3 @ 2.60GHz

2 "physical id"s (chips)

40 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

<http://www.spec.org/>

Page 2



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 55.5

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = 53.0

CPU2006 license: 9046
Test sponsor: Sugon
Tested by: Sugon

Test date: Oct-2014
Hardware Availability: Sep-2014
Software Availability: Sep-2013

Platform Notes (Continued)

following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

```
cpu cores : 10
siblings  : 20
physical 0: cores 0 1 2 3 4 8 9 10 11 12
physical 1: cores 0 1 2 3 4 8 9 10 11 12
cache size : 25600 KB
```

```
From /proc/meminfo
MemTotal:      264478588 kB
HugePages_Total:    0
Hugepagesize:    2048 kB
```

```
/usr/bin/lsb_release -d
Red Hat Enterprise Linux Server release 6.4 (Santiago)
```

```
From /etc/*release* /etc/*version*
redhat-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release: Red Hat Enterprise Linux Server release 6.4 (Santiago)
system-release-cpe: cpe:/o:redhat:enterprise_linux:6server:ga:server
```

```
uname -a:
Linux localhost.localdomain 2.6.32-358.el6.x86_64 #1 SMP Tue Jan 29 11:47:41
EST 2013 x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Oct 9 09:21
```

```
SPEC is set to: /home/cpu2006
Filesystem      Type      Size      Used Avail Use% Mounted on
/dev/sda3        ext4      1.8T      411G  1.3T   24% /
```

```
Additional information from dmidecode:
BIOS American Megatrends Inc. 067 08/13/2014
Memory:
16x 16 GB
8x NO DIMM NO DIMM
16x Samsung M393A2G40DB0-CPB 16 GB 2133 MHz 2 rank
```

(End of data from sysinfo program)

General Notes

Environment variables set by runspec before the start of the run:

```
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"
OMP_NUM_THREADS = "20"
```

```
Binaries compiled on a system with 1x Core i7-860 CPU + 8GB
memory using RedHat EL 6.4
Transparent Huge Pages enabled with:
echo always > /sys/kernel/mm/redhat_transparent_hugepage/enabled
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 55.5

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = 53.0

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

General Notes (Continued)

Filesystem page cache cleared with:
echo 1> /proc/sys/vm/drop_caches
runspec command invoked through numactl i.e.:
numactl --interleave=all runspec <etc>

Submitted_by: Tian Yuwan <tianyw@sugon.com>
Submitted: Wed Nov 5 02:52:29 EST 2014
Submission: cpu2006-20141105-32756.sub

Submitted_by: Tian Yuwan <tianyw@sugon.com>
Submitted: Sun Nov 23 21:26:15 EST 2014
Submission: cpu2006-20141105-32756.sub

Submitted_by: Tian Yuwan <tianyw@sugon.com>
Submitted: Wed Nov 26 05:11:52 EST 2014
Submission: cpu2006-20141105-32756.sub

Submitted_by: Tian Yuwan <tianyw@sugon.com>
Submitted: Thu Nov 27 00:57:34 EST 2014
Submission: cpu2006-20141105-32756.sub

Base Compiler Invocation

C benchmarks:
icc -m64

C++ benchmarks:
icpc -m64

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 55.5

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = 53.0

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32
-Wl,-z,muldefs -L/sh -lsmartheap64

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

400.perlbench: icc -m32

445.gobmk: icc -m32

C++ benchmarks (except as noted below):

icpc -m64

471.omnetpp: icpc -m32

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

401.bzip2: -DSPEC_CPU_LP64

403.gcc: -DSPEC_CPU_LP64

429.mcf: -DSPEC_CPU_LP64

456.hmmer: -DSPEC_CPU_LP64

458.sjeng: -DSPEC_CPU_LP64

462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

464.h264ref: -DSPEC_CPU_LP64

473.astar: -DSPEC_CPU_LP64

483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 55.5

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = 53.0

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

Peak Optimization Flags

C benchmarks:

400.perlbench: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-opt-prefetch -ansi-alias

401.bzip2: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div -prof-use(pass 2) -auto-ilp32
-opt-prefetch -ansi-alias

403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc
-opt-malloc-options=3 -auto-ilp32

429.mcf: -xCORE-AVX2 -ipo -O3 -no-prec-div -parallel
-opt-prefetch -auto-p32

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
-ansi-alias

456.hmmer: basepeak = yes

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-unroll4

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-opt-ra-region-strategy=block -ansi-alias
-Wl,-z,muldefs -L/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sugon

SPECint2006 = 55.5

Sugon I620-G20 (Intel Xeon E5-2660 v3)

SPECint_base2006 = 53.0

CPU2006 license: 9046

Test sponsor: Sugon

Tested by: Sugon

Test date: Oct-2014

Hardware Availability: Sep-2014

Software Availability: Sep-2013

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/Sugon-Platform-Settings-V1.2-HSW-revA.20141203.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/Sugon-Platform-Settings-V1.2-HSW-revA.20141203.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Wed Dec 3 10:28:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 December 2014.