



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

SPECfp<sup>®</sup>2006 = **110**

Compute Blade 520H (Intel Xeon E5-2699 v3)

SPECfp\_base2006 = **104**

CPU2006 license: 35


Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jan-2015

Hardware Availability: Sep-2014

Software Availability: Nov-2013



### Hardware

CPU Name: Intel Xeon E5-2699 v3  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.60 GHz  
 CPU MHz: 2300  
 FPU: Integrated  
 CPU(s) enabled: 36 cores, 2 chips, 18 cores/chip, 2 threads/core  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core

Continued on next page

### Software

Operating System: Red Hat Enterprise Linux Server release 6.5 (Santiago)  
 2.6.32-431.el6.x86\_64  
 Compiler: C/C++: Version 14.0.0.080 of Intel C++ Studio XE for Linux;  
 Fortran: Version 14.0.0.080 of Intel Fortran Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

SPECfp2006 = **110**

Compute Blade 520H (Intel Xeon E5-2699 v3)

SPECfp\_base2006 = **104**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jan-2015

Hardware Availability: Sep-2014

Software Availability: Nov-2013

L3 Cache: 45 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2133P-R)  
 Disk Subsystem: 2 x 600 GB SAS, 10000 RPM, RAID1  
 Other Hardware: None

System State: Run level 3 (multi-user)  
 Base Pointers: 64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: none

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	22.8	595	<b><u>23.6</u></b>	<b><u>575</u></b>	24.0	566	22.8	595	<b><u>23.6</u></b>	<b><u>575</u></b>	24.0	566
416.gamess	585	33.5	584	33.5	<b><u>585</u></b>	<b><u>33.5</u></b>	462	42.4	<b><u>461</u></b>	<b><u>42.5</u></b>	461	42.5
433.milc	<b><u>143</u></b>	<b><u>64.1</u></b>	144	63.9	143	64.3	144	63.9	147	62.4	<b><u>144</u></b>	<b><u>63.8</u></b>
434.zeusmp	47.2	193	47.4	192	<b><u>47.2</u></b>	<b><u>193</u></b>	47.2	193	47.4	192	<b><u>47.2</u></b>	<b><u>193</u></b>
435.gromacs	189	37.8	<b><u>189</u></b>	<b><u>37.8</u></b>	191	37.4	189	37.8	<b><u>189</u></b>	<b><u>37.8</u></b>	191	37.4
436.cactusADM	<b><u>14.3</u></b>	<b><u>833</u></b>	14.3	833	14.3	833	<b><u>14.3</u></b>	<b><u>833</u></b>	14.3	833	14.3	833
437.leslie3d	<b><u>26.8</u></b>	<b><u>350</u></b>	26.0	361	27.4	343	<b><u>26.8</u></b>	<b><u>350</u></b>	26.0	361	27.4	343
444.namd	<b><u>285</u></b>	<b><u>28.1</u></b>	285	28.1	286	28.1	<b><u>276</u></b>	<b><u>29.1</u></b>	276	29.1	276	29.1
447.dealII	204	56.1	<b><u>202</u></b>	<b><u>56.6</u></b>	201	56.9	204	56.1	<b><u>202</u></b>	<b><u>56.6</u></b>	201	56.9
450.soplex	<b><u>198</u></b>	<b><u>42.2</u></b>	198	42.1	197	42.3	<b><u>198</u></b>	<b><u>42.2</u></b>	198	42.1	197	42.3
453.povray	<b><u>93.3</u></b>	<b><u>57.0</u></b>	94.4	56.4	93.1	57.1	85.0	62.6	<b><u>85.1</u></b>	<b><u>62.5</u></b>	85.6	62.2
454.calculix	189	43.6	<b><u>190</u></b>	<b><u>43.5</u></b>	190	43.4	<b><u>163</u></b>	<b><u>50.8</u></b>	162	50.8	163	50.5
459.GemsFDTD	48.0	221	<b><u>47.8</u></b>	<b><u>222</u></b>	47.6	223	42.3	251	<b><u>42.3</u></b>	<b><u>251</u></b>	42.5	250
465.tonto	270	36.5	<b><u>271</u></b>	<b><u>36.3</u></b>	272	36.2	<b><u>199</u></b>	<b><u>49.3</u></b>	199	49.4	200	49.2
470.lbm	17.4	789	16.4	837	<b><u>16.4</u></b>	<b><u>837</u></b>	17.4	789	16.4	837	<b><u>16.4</u></b>	<b><u>837</u></b>
481.wrf	110	102	109	103	<b><u>110</u></b>	<b><u>102</u></b>	110	102	109	103	<b><u>110</u></b>	<b><u>102</u></b>
482.sphinx3	<b><u>302</u></b>	<b><u>64.5</u></b>	302	64.4	299	65.2	304	64.1	306	63.6	<b><u>306</u></b>	<b><u>63.6</u></b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS configuration:  
 Patrol Scrub = Disable  
 Per Core P-state = Disable

Sysinfo program /home/speccpu2006/cpu2006/config/sysinfo.rev6818  
 \$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191  
 running on 520Hx36564 Fri Jan 9 03:38:59 2015

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

**SPECfp2006 = 110**

Compute Blade 520H (Intel Xeon E5-2699 v3)

**SPECfp\_base2006 = 104**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jan-2015

Hardware Availability: Sep-2014

Software Availability: Nov-2013

### Platform Notes (Continued)

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

From /proc/cpuinfo

model name : Intel(R) Xeon(R) CPU E5-2699 v3 @ 2.30GHz

2 "physical id"s (chips)

72 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/cpuinfo might not be reliable. Use with caution.)

cpu cores : 18

siblings : 36

physical 0: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27

physical 1: cores 0 1 2 3 4 8 9 10 11 16 17 18 19 20 24 25 26 27

cache size : 46080 KB

From /proc/meminfo

MemTotal: 263985944 kB

HugePages\_Total: 0

Hugepagesize: 2048 kB

/usr/bin/lsb\_release -d

Red Hat Enterprise Linux Server release 6.5 (Santiago)

From /etc/\*release\* /etc/\*version\*

redhat-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)

system-release: Red Hat Enterprise Linux Server release 6.5 (Santiago)

system-release-cpe: cpe:/o:redhat:enterprise\_linux:6server:ga:server

uname -a:

Linux 520Hx36564 2.6.32-431.el6.x86\_64 #1 SMP Sun Nov 10 22:19:54 EST 2013  
x86\_64 x86\_64 x86\_64 GNU/Linux

run-level 3 Jan 8 22:11

SPEC is set to: /home/speccpu2006/cpu2006

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/mapper/vg_520hx36564-lv_home	ext4	485G	5.5G	455G	2%	/home

Additional information from dmidecode:

BIOS HITACHI 08-20 01/06/2015

Memory:

8x NO DIMM Unknown

16x Samsung M393A2G40DB0-CPB 16 GB 2133 MHz 2 rank

(End of data from sysinfo program)

### General Notes

Environment variables set by runspec before the start of the run:

KMP\_AFFINITY = "granularity=fine,compact,1,0"

LD\_LIBRARY\_PATH = "/home/speccpu2006/cpu2006/libs/32:/home/speccpu2006/cpu2006/libs/64:/home/speccpu2006/cpu2006/sh"

Continued on next page

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org/



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

**HITACHI**

**SPECfp2006 = 110**

**Compute Blade 520H (Intel Xeon E5-2699 v3)**

**SPECfp\_base2006 = 104**

**CPU2006 license:** 35

**Test sponsor:** HITACHI

**Tested by:** HITACHI

**Test date:** Jan-2015

**Hardware Availability:** Sep-2014

**Software Availability:** Nov-2013

## General Notes (Continued)

OMP\_NUM\_THREADS = "36"

Binaries compiled on a system with 1x Core i7-860 CPU + 8GB memory using RedHat EL 6.4

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat\_transparent\_hugepage/enabled

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

BladeSymphony BS520H, Hitachi Compute Blade 520H and BladeSymphony BS2500 HC0A1 are electronically equivalent.

The results have been measured on a Hitachi Compute Blade 520H.

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
 416.gamess: -DSPEC\_CPU\_LP64  
 433.milc: -DSPEC\_CPU\_LP64  
 434.zeusmp: -DSPEC\_CPU\_LP64  
 435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
 436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
 437.leslie3d: -DSPEC\_CPU\_LP64  
 444.namd: -DSPEC\_CPU\_LP64  
 447.dealII: -DSPEC\_CPU\_LP64  
 450.soplex: -DSPEC\_CPU\_LP64  
 453.povray: -DSPEC\_CPU\_LP64  
 454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
 459.GemsFDTD: -DSPEC\_CPU\_LP64  
 465.tonto: -DSPEC\_CPU\_LP64  
 470.lbm: -DSPEC\_CPU\_LP64  
 481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
 482.sphinx3: -DSPEC\_CPU\_LP64



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

**SPECfp2006 = 110**

Compute Blade 520H (Intel Xeon E5-2699 v3)

**SPECfp\_base2006 = 104**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jan-2015

Hardware Availability: Sep-2014

Software Availability: Nov-2013

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -ansi-alias

Fortran benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch

Benchmarks using both Fortran and C:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch  
-ansi-alias

## Peak Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

Fortran benchmarks:

ifort -m64

Benchmarks using both Fortran and C:

icc -m64 ifort -m64

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32 -ansi-alias

470.lbm: basepeak = yes

482.sphinx3: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll2 -ansi-alias  
-parallel

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

**SPECfp2006 = 110**

Compute Blade 520H (Intel Xeon E5-2699 v3)

**SPECfp\_base2006 = 104**

CPU2006 license: 35

Test sponsor: HITACHI

Tested by: HITACHI

Test date: Jan-2015

Hardware Availability: Sep-2014

Software Availability: Nov-2013

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-fno-alias -auto-ilp32

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll4  
-ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2) -unroll2  
-inline-level=0 -opt-prefetch -parallel

465.tonto: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-inline-calloc -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

436.cactusADM: basepeak = yes

454.calculix: -xCORE-AVX2 -ipo -O3 -no-prec-div -auto-ilp32 -ansi-alias

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.html>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.20150127.html>



# SPEC CFP2006 Result

Copyright 2006-2015 Standard Performance Evaluation Corporation

## HITACHI

**SPECfp2006 = 110**

Compute Blade 520H (Intel Xeon E5-2699 v3)

**SPECfp\_base2006 = 104**

**CPU2006 license:** 35

**Test sponsor:** HITACHI

**Tested by:** HITACHI

**Test date:** Jan-2015

**Hardware Availability:** Sep-2014

**Software Availability:** Nov-2013

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic14.0-official-linux64-revC.xml>

<http://www.spec.org/cpu2006/flags/PlatformHitachi-V1.2.20150127.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.  
Report generated on Tue Jan 27 13:29:45 2015 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 27 January 2015.