



# SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## NEC Corporation

**SPECint®2006 = 62.7**

Express5800/R110h-1 (Intel Xeon E3-1240L v5)

**SPECint\_base2006 = 60.7**

CPU2006 license: 9006


Test date: Dec-2015

Test sponsor: NEC Corporation

Hardware Availability: Mar-2016

Tested by: NEC Corporation

Software Availability: Nov-2015



### Hardware

CPU Name: Intel Xeon E3-1240L v5  
 CPU Characteristics: Intel Turbo Boost Technology up to 3.20 GHz  
 CPU MHz: 2100  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 1 chip, 4 cores/chip  
 CPU(s) orderable: 1 chip  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 256 KB I+D on chip per core  
 L3 Cache: 8 MB I+D on chip per chip  
 Other Cache: None  
 Memory: 16 GB (2 x 8 GB 2Rx8 PC4-2133P-E)  
 Disk Subsystem: 1 x 500 GB SATA, 7200 RPM  
 Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux Server release 7.2 (Maipo)  
 Kernel 3.10.0-327.el7.x86\_64  
 Compiler: C/C++: Version 16.0.0.101 of Intel C++ Studio XE for Linux  
 Auto Parallel: Yes  
 File System: ext4  
 System State: Run level 3 (multi-user)  
 Base Pointers: 32/64-bit  
 Peak Pointers: 32/64-bit  
 Other Software: Microquill SmartHeap V10.2



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

## NEC Corporation

SPECint2006 = **62.7**

Express5800/R110h-1 (Intel Xeon E3-1240L v5)

SPECint\_base2006 = **60.7**

CPU2006 license: 9006

Test date: Dec-2015

Test sponsor: NEC Corporation

Hardware Availability: Mar-2016

Tested by: NEC Corporation

Software Availability: Nov-2015

## Results Table

| Benchmark      | Base              |                    |                    |                    |                    |                    | Peak               |                    |                    |                    |                   |                    |
|----------------|-------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|-------------------|--------------------|
|                | Seconds           | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds            | Ratio              | Seconds           | Ratio              |
| 400.perlbench  | 237               | 41.2               | 238                | 41.0               | <b><u>238</u></b>  | <b><u>41.0</u></b> | 215                | 45.5               | 216                | 45.2               | <b><u>215</u></b> | <b><u>45.5</u></b> |
| 401.bzip2      | 387               | 24.9               | 386                | 25.0               | <b><u>386</u></b>  | <b><u>25.0</u></b> | <b><u>381</u></b>  | <b><u>25.3</u></b> | 381                | 25.3               | 381               | 25.3               |
| 403.gcc        | <b><u>185</u></b> | <b><u>43.4</u></b> | 185                | 43.4               | 186                | 43.3               | 186                | 43.3               | 185                | 43.4               | <b><u>185</u></b> | <b><u>43.4</u></b> |
| 429.mcf        | 128               | 71.1               | <b><u>127</u></b>  | <b><u>72.1</u></b> | 125                | 72.9               | <b><u>126</u></b>  | <b><u>72.3</u></b> | 126                | 72.1               | 124               | 73.6               |
| 445.gobmk      | 365               | 28.7               | 365                | 28.7               | <b><u>365</u></b>  | <b><u>28.7</u></b> | 365                | 28.7               | 365                | 28.7               | <b><u>365</u></b> | <b><u>28.7</u></b> |
| 456.hammer     | 112               | 83.3               | <b><u>112</u></b>  | <b><u>83.6</u></b> | 112                | 83.6               | 112                | 83.3               | <b><u>112</u></b>  | <b><u>83.6</u></b> | 112               | 83.6               |
| 458.sjeng      | 368               | 32.9               | 368                | 32.8               | <b><u>368</u></b>  | <b><u>32.9</u></b> | <b><u>363</u></b>  | <b><u>33.3</u></b> | 363                | 33.3               | 363               | 33.3               |
| 462.libquantum | 11.0              | 1890               | <b><u>11.0</u></b> | <b><u>1890</u></b> | 11.0               | 1880               | 11.0               | 1890               | <b><u>11.0</u></b> | <b><u>1890</u></b> | 11.0              | 1880               |
| 464.h264ref    | 371               | 59.7               | <b><u>371</u></b>  | <b><u>59.7</u></b> | 369                | 59.9               | 371                | 59.7               | <b><u>371</u></b>  | <b><u>59.7</u></b> | 369               | 59.9               |
| 471.omnetpp    | 192               | 32.5               | <b><u>192</u></b>  | <b><u>32.5</u></b> | 193                | 32.3               | 161                | 38.9               | <b><u>160</u></b>  | <b><u>39.1</u></b> | 157               | 39.7               |
| 473.astar      | 206               | 34.0               | 203                | 34.6               | <b><u>206</u></b>  | <b><u>34.1</u></b> | <b><u>205</u></b>  | <b><u>34.3</u></b> | 207                | 33.9               | 204               | 34.4               |
| 483.xalancbmk  | 86.5              | 79.8               | 85.9               | 80.3               | <b><u>86.5</u></b> | <b><u>79.8</u></b> | <b><u>82.3</u></b> | <b><u>83.8</u></b> | 82.2               | 84.0               | 82.4              | 83.7               |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

The config file option 'submit' was used.

## Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

## Platform Notes

BIOS Settings:  
Power Management Policy: Custom  
Energy Performance: Performance  
Hyper-Threading: Disabled

## General Notes

Environment variables set by runspec before the start of the run:

```
KMP_AFFINITY = "granularity=fine,scatter"
LD_LIBRARY_PATH = "/home/cpu2006/libs/32:/home/cpu2006/libs/64:/home/cpu2006/sh"
OMP_NUM_THREADS = "4"
```

Binaries compiled on a system with 1x Intel Core i5-4670K CPU + 32GB memory using RedHat EL 7.1  
Transparent Huge Pages enabled with:  
echo always > /sys/kernel/mm/transparent\_hugepage/enabled



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

NEC Corporation

SPECint2006 = 62.7

Express5800/R110h-1 (Intel Xeon E3-1240L v5)

SPECint\_base2006 = 60.7

CPU2006 license: 9006

Test date: Dec-2015

Test sponsor: NEC Corporation

Hardware Availability: Mar-2016

Tested by: NEC Corporation

Software Availability: Nov-2015

## Base Compiler Invocation

C benchmarks:

icc -m64

C++ benchmarks:

icpc -m64

## Base Portability Flags

400.perlbench: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX\_X64  
 401.bzip2: -DSPEC\_CPU\_LP64  
 403.gcc: -DSPEC\_CPU\_LP64  
 429.mcf: -DSPEC\_CPU\_LP64  
 445.gobmk: -DSPEC\_CPU\_LP64  
 456.hmmer: -DSPEC\_CPU\_LP64  
 458.sjeng: -DSPEC\_CPU\_LP64  
 462.libquantum: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX  
 464.h264ref: -DSPEC\_CPU\_LP64  
 471.omnetpp: -DSPEC\_CPU\_LP64  
 473.astar: -DSPEC\_CPU\_LP64  
 483.xalancbmk: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_LINUX

## Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32

C++ benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch -auto-p32  
-Wl,-z,muldefs -L/sh -lsmartheap64

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):

icc -m64

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

**NEC Corporation**

**SPECint2006 = 62.7**

**Express5800/R110h-1 (Intel Xeon E3-1240L v5)**

**SPECint\_base2006 = 60.7**

**CPU2006 license:** 9006

**Test date:** Dec-2015

**Test sponsor:** NEC Corporation

**Hardware Availability:** Mar-2016

**Tested by:** NEC Corporation

**Software Availability:** Nov-2015

## Peak Compiler Invocation (Continued)

400.perlbench: `icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin`

C++ benchmarks (except as noted below):

`icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/compiler/lib/ia32_lin`

473.astar: `icpc -m64`

## Peak Portability Flags

400.perlbench: `-D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX_IA32`  
 401.bzip2: `-DSPEC_CPU_LP64`  
 403.gcc: `-DSPEC_CPU_LP64`  
 429.mcf: `-DSPEC_CPU_LP64`  
 445.gobmk: `-DSPEC_CPU_LP64`  
 456.hmmmer: `-DSPEC_CPU_LP64`  
 458.sjeng: `-DSPEC_CPU_LP64`  
 462.libquantum: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX`  
 464.h264ref: `-DSPEC_CPU_LP64`  
 471.omnetpp: `-D_FILE_OFFSET_BITS=64`  
 473.astar: `-DSPEC_CPU_LP64`  
 483.xalanbmk: `-D_FILE_OFFSET_BITS=64 -DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

400.perlbench: `-xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -par-num-threads=1(pass 1) -prof-use(pass 2) -opt-prefetch -ansi-alias`

401.bzip2: `-xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div -par-num-threads=1(pass 1) -prof-use(pass 2) -auto-ilp32 -opt-prefetch -ansi-alias`

403.gcc: `-xCORE-AVX2 -ipo -O3 -no-prec-div -inline-calloc -opt-malloc-options=3 -auto-ilp32`

429.mcf: `-xCORE-AVX2 -ipo -O3 -no-prec-div -parallel -opt-prefetch -auto-p32`

445.gobmk: `basepeak = yes`

456.hmmmer: `basepeak = yes`

Continued on next page



# SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

NEC Corporation

SPECint2006 = 62.7

Express5800/R110h-1 (Intel Xeon E3-1240L v5)

SPECint\_base2006 = 60.7

CPU2006 license: 9006

Test date: Dec-2015

Test sponsor: NEC Corporation

Hardware Availability: Mar-2016

Tested by: NEC Corporation

Software Availability: Nov-2015

## Peak Optimization Flags (Continued)

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2) -unroll4

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen:threadsafe(pass 1)  
-ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2)  
-par-num-threads=1(pass 1) -prof-use(pass 2)  
-opt-ra-region-strategy=block -ansi-alias  
-Wl,-z,muldefs -L/sh -lsmarheap

473.astar: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-auto-p32 -Wl,-z,muldefs -L/sh -lsmarheap64

483.xalancbmk: -xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-ansi-alias -Wl,-z,muldefs -L/sh -lsmarheap

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=\_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>

<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-110h-RevA.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>

<http://www.spec.org/cpu2006/flags/NEC-Platform-Settings-V1.2-110h-RevA.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.2.

Report generated on Tue Feb 9 17:21:19 2016 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 9 February 2016.