



SPEC® CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

ACTION S.A.

ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz)

SPECint_rate2006 = 892

SPECint_rate_base2006 = 850

CPU2006 license: 9008


Test sponsor: ACTION S.A.

Tested by: ACTION S.A.

Test date: Nov-2016

Hardware Availability: Mar-2016

Software Availability: Mar-2016



Hardware

CPU Name: Intel Xeon E5-2640 v4
CPU Characteristics: Intel Turbo Boost Technology up to 3.40 GHz
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 20 cores, 2 chips, 10 cores/chip, 2 threads/core
CPU(s) orderable: 1,2 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 256 KB I+D on chip per core
L3 Cache: 25 MB I+D on chip per chip
Other Cache: None
Memory: 256 GB (16 x 16 GB 2Rx4 PC4-2400T-R, running at 2133 MHz)
Disk Subsystem: 1 x 240 GB SATA II SSD
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux Server release 7.2 (Maipo)
Compiler: 3.10.0-327.18.2.el7.x86_64
C/C++: Version 16.0.3.210 of Intel C++ Studio XE for Linux
Auto Parallel: No
File System: ext4
System State: Run level 3 (multi-user)
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: Microquill SmartHeap V10.0



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

| | | |
|-------------------------------------------------------|--------------------------------|------------|
| ACTION S.A. | SPECint_rate2006 = | 892 |
| ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz) | SPECint_rate_base2006 = | 850 |

CPU2006 license: 9008

Test date: Nov-2016

Test sponsor: ACTION S.A.

Hardware Availability: Mar-2016

Tested by: ACTION S.A.

Software Availability: Mar-2016

Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|----------------|--------|-------------|-------------|------------|-------------|------------|-------------|--------|-------------|-------------|------------|------------|------------|-------------|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 40 | 648 | 603 | 648 | 603 | 647 | 604 | 40 | 514 | 760 | 515 | 759 | 516 | 757 |
| 401.bzip2 | 40 | 949 | 407 | 948 | 407 | 948 | 407 | 40 | 912 | 423 | 910 | 424 | 909 | 425 |
| 403.gcc | 40 | 504 | 639 | 501 | 643 | 503 | 640 | 40 | 500 | 644 | 499 | 645 | 496 | 649 |
| 429.mcf | 40 | 331 | 1100 | 334 | 1090 | 331 | 1100 | 40 | 331 | 1100 | 334 | 1090 | 331 | 1100 |
| 445.gobmk | 40 | 751 | 558 | 751 | 559 | 752 | 558 | 40 | 743 | 564 | 744 | 564 | 745 | 563 |
| 456.hammer | 40 | 298 | 1250 | 296 | 1260 | 298 | 1250 | 40 | 254 | 1470 | 255 | 1460 | 253 | 1470 |
| 458.sjeng | 40 | 841 | 575 | 841 | 576 | 841 | 576 | 40 | 803 | 603 | 800 | 605 | 803 | 603 |
| 462.libquantum | 40 | 97.4 | 8510 | 97.3 | 8520 | 97.4 | 8510 | 40 | 97.4 | 8510 | 97.3 | 8520 | 97.4 | 8510 |
| 464.h264ref | 40 | 854 | 1040 | 850 | 1040 | 848 | 1040 | 40 | 833 | 1060 | 830 | 1070 | 832 | 1060 |
| 471.omnetpp | 40 | 539 | 464 | 542 | 461 | 539 | 464 | 40 | 508 | 492 | 505 | 495 | 501 | 499 |
| 473.astar | 40 | 566 | 496 | 568 | 495 | 568 | 494 | 40 | 566 | 496 | 568 | 495 | 568 | 494 |
| 483.xalancbmk | 40 | 275 | 1000 | 274 | 1010 | 278 | 992 | 40 | 275 | 1000 | 274 | 1010 | 278 | 992 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The numactl mechanism was used to bind copies to processors. The config file option 'submit' was used to generate numactl commands to bind each copy to a specific processor. For details, please see the config file.

Operating System Notes

Stack size set to unlimited using "ulimit -s unlimited"

Platform Notes

Bios Settings:

Intel(R) Hyper-Threading Tech = Enabled
Power & Performance = Performance
Enforce POR = Disabled
Memory Operating Speed Selection = 2133
Set FAN Profile = Performance
Fan PWM Offset = 0

Sysinfo program /cpu2006.1.2/config/sysinfo.rev6818
\$Rev: 6818 \$ \$Date:: 2012-07-17 #\$ e86d102572650a6e4d596a3cee98f191
running on SUT Wed Nov 9 16:33:36 2016

This section contains SUT (System Under Test) info as seen by some common utilities. To remove or add to this section, see:

<http://www.spec.org/cpu2006/Docs/config.html#sysinfo>

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

| | | |
|-------------------------------------------------------|--------------------------------|------------|
| ACTION S.A. | SPECint_rate2006 = | 892 |
| ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz) | SPECint_rate_base2006 = | 850 |
| CPU2006 license: 9008 | Test date: | Nov-2016 |
| Test sponsor: ACTION S.A. | Hardware Availability: | Mar-2016 |
| Tested by: ACTION S.A. | Software Availability: | Mar-2016 |

Platform Notes (Continued)

```
From /proc/cpuinfo
    model name : Intel(R) Xeon(R) CPU E5-2640 v4 @ 2.40GHz
        2 "physical id"s (chips)
        40 "processors"
cores, siblings (Caution: counting these is hw and system dependent. The
following excerpts from /proc/cpuinfo might not be reliable. Use with
caution.)
    cpu cores : 10
    siblings : 20
    physical 0: cores 0 1 2 3 4 8 9 10 11 12
    physical 1: cores 0 1 2 3 4 8 9 10 11 12
    cache size : 25600 KB
```

```
From /proc/meminfo
MemTotal:      263860776 kB
HugePages_Total:       1
Hugepagesize:     2048 kB
```

```
From /etc/*release* /etc/*version*
os-release:
    NAME="Red Hat Enterprise Linux Server"
    VERSION="7.2 (Maipo)"
    ID="rhel"
    ID_LIKE="fedora"
    VERSION_ID="7.2"
    PRETTY_NAME="Red Hat Enterprise Linux"
    ANSI_COLOR="0;31"
    CPE_NAME="cpe:/o:redhat:enterprise_linux:7.2:GA:server"
os-release.rpmsave:
    NAME="Red Hat Enterprise Linux Server"
    VERSION="7.0 (Maipo)"
    ID="rhel"
    ID_LIKE="fedora"
    VERSION_ID="7.0"
    PRETTY_NAME="Red Hat Enterprise Linux"
    ANSI_COLOR="0;31"
    CPE_NAME="cpe:/o:redhat:enterprise_linux:7.0:GA:server"
redhat-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)
system-release: Red Hat Enterprise Linux Server release 7.2 (Maipo)
system-release-cpe: cpe:/o:redhat:enterprise_linux:7.2:ga:server
```

```
uname -a:
Linux SUT 3.10.0-327.18.2.el7.x86_64 #2 SMP Wed Jun 1 17:37:13 CEST 2016
x86_64 x86_64 x86_64 GNU/Linux
```

```
run-level 3 Nov 9 16:32
```

```
SPEC is set to: /cpu2006.1.2
Filesystem      Type  Size  Used Avail Use% Mounted on
/dev/sdal      ext4  212G  118G   84G  59%  /
```

Additional information from dmidecode:
Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

| | | |
|-------------------------------------------------------|--------------------------------|------------|
| ACTION S.A. | SPECint_rate2006 = | 892 |
| ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz) | SPECint_rate_base2006 = | 850 |
| CPU2006 license: 9008 | Test date: | Nov-2016 |
| Test sponsor: ACTION S.A. | Hardware Availability: | Mar-2016 |
| Tested by: ACTION S.A. | Software Availability: | Mar-2016 |

Platform Notes (Continued)

BIOS Intel Corporation SE5C610.86B.01.01.0019.101220160604 10/12/2016

Memory:

16x 16 GB
16x Hynix HMA42GR7AFR4N-UH 16 GB 2134 MHz 2 rank
8x NO DIMM NO DIMM

(End of data from sysinfo program)

dmidecode does not properly detect memory modules
16 modules of 16 GB were used to run the test (256 GB total)

General Notes

Environment variables set by runspec before the start of the run:

LD_LIBRARY_PATH = "/cpu2006.1.2/lib/32:/cpu2006.1.2/lib/64:/cpu2006.1.2/sh"

Transparent Huge Pages enabled with:

echo always > /sys/kernel/mm/redhat_transparent_hugepage/enable

Filesystem page cache cleared with:

echo 1> /proc/sys/vm/drop_caches

runspec command invoked through numactl i.e.:

numactl --interleave=all runspec <etc>

Binaries compiled on a system with 2x Xeon E5-2650 v4 chips + 256 GB memory
using RedHat EL 7.2

Base Compiler Invocation

C benchmarks:

icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/lib/ia32_lin

C++ benchmarks:

icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/lib/ia32_lin

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32

462.libquantum: -DSPEC_CPU_LINUX

483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:

-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch
-opt-mem-layout-trans=3

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

| | | |
|-------------------------------------------------------|--------------------------------|------------|
| ACTION S.A. | SPECint_rate2006 = | 892 |
| ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz) | SPECint_rate_base2006 = | 850 |
| CPU2006 license: 9008 | Test date: | Nov-2016 |
| Test sponsor: ACTION S.A. | Hardware Availability: | Mar-2016 |
| Tested by: ACTION S.A. | Software Availability: | Mar-2016 |

Base Optimization Flags (Continued)

C++ benchmarks:

```
-xCORE-AVX2 -ipo -O3 -no-prec-div -opt-prefetch  
-opt-mem-layout-trans=3 -Wl,-z,muldefs -L/cpu2006.1.2/sh -lsmartheap
```

Base Other Flags

C benchmarks:

```
403.gcc: -Dalloca=_alloca
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/lib/ia32_lin
```

```
400.perlbench: icc -m64
```

```
401.bzip2: icc -m64
```

```
456.hmmmer: icc -m64
```

```
458.sjeng: icc -m64
```

C++ benchmarks:

```
icpc -m32 -L/opt/intel/compilers_and_libraries_2016/linux/lib/ia32_lin
```

Peak Portability Flags

```
400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
```

```
401.bzip2: -DSPEC_CPU_LP64
```

```
456.hmmmer: -DSPEC_CPU_LP64
```

```
458.sjeng: -DSPEC_CPU_LP64
```

```
462.libquantum: -DSPEC_CPU_LINUX
```

```
483.xalancbmk: -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
400.perlbench: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)  
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)  
-auto-ilp32
```

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

| | | |
|-------------------------------------------------------|--------------------------------|------------|
| ACTION S.A. | SPECint_rate2006 = | 892 |
| ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz) | SPECint_rate_base2006 = | 850 |
| CPU2006 license: 9008 | Test date: | Nov-2016 |
| Test sponsor: ACTION S.A. | Hardware Availability: | Mar-2016 |
| Tested by: ACTION S.A. | Software Availability: | Mar-2016 |

Peak Optimization Flags (Continued)

401.bzip2: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -opt-prefetch -auto-ilp32 -ansi-alias

403.gcc: -xCORE-AVX2 -ipo -O3 -no-prec-div

429.mcf: basepeak = yes

445.gobmk: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -prof-use(pass 2)
 -ansi-alias -opt-mem-layout-trans=3

456.hmmr: -xCORE-AVX2 -ipo -O3 -no-prec-div -unroll12 -auto-ilp32

458.sjeng: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -unroll14 -auto-ilp32

462.libquantum: basepeak = yes

464.h264ref: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -unroll12 -ansi-alias

C++ benchmarks:

471.omnetpp: -xCORE-AVX2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
 -O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
 -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
 -L/cpu2006.1.2/sh -lsmartheap

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.html>
<http://www.spec.org/cpu2006/flags/ACTION.SA-Platform-Flags-RevB-aug-2015-For-Intel-Platform.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic16.0-official-linux64.xml>
<http://www.spec.org/cpu2006/flags/ACTION.SA-Platform-Flags-RevB-aug-2015-For-Intel-Platform.xml>



SPEC CINT2006 Result

Copyright 2006-2016 Standard Performance Evaluation Corporation

| | | |
|-------------------------------------------------------|--------------------------------|------------|
| ACTION S.A. | SPECint_rate2006 = | 892 |
| ACTINA SOLAR 220 X6 (Intel Xeon E5-2640 v4, 2.40 GHz) | SPECint_rate_base2006 = | 850 |
| CPU2006 license: 9008 | Test date: | Nov-2016 |
| Test sponsor: ACTION S.A. | Hardware Availability: | Mar-2016 |
| Tested by: ACTION S.A. | Software Availability: | Mar-2016 |

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.2.
Report generated on Tue Nov 29 19:08:30 2016 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 November 2016.