



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2100 8X 350MHz R12k

SPECfp_rate2000 = 22.8
SPECfp_rate_base2000 = 21.3

SPEC license #: 4 Tested by: SGI Test date: Apr-2000 Hardware Avail: Jun-2000 Software Avail: Apr-2000

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	724	20.5	8	625	23.7
171.swim	8	1809	15.9	8	1828	15.7
172.mgrid	8	1234	13.5	8	1135	14.7
173.applu	8	1202	16.2	8	1092	17.8
177.mesa	8	578	22.5	8	552	23.5
178.galgel	8	367	73.4	8	320	84.2
179.art	8	303	79.7	8	307	78.7
183.quake	8	874	13.8	8	859	14.0
187.facerec	8	822	21.5	8	809	21.8
188.amp	8	708	28.8	8	710	28.7
189.lucas	8	1259	14.7	8	1259	14.7
191.fma3d	8	1525	12.8	8	1332	14.6
200.sixtrack	8	659	15.5	8	640	16.0
301.apsi	8	1447	16.7	8	1105	21.8

Hardware

CPU: R12000
CPU MHz: 350
FPU: Integrated
CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
CPU(s) orderable: 2, 4, 6, 8
Parallel: No
Primary Cache: 32KBI + 32KBD on chip
Secondary Cache: 4MB(I+D) off chip
L3 Cache: N/A
Other Cache: N/A
Memory: 2048MB
Disk Subsystem: 1 x 18 GB SCSI, 2 x 18 GB (striped)
Other Hardware: None

Software

Operating System: IRIX 6.5.8f
Compiler: MIPSpro 7.3.1.1m C, C++, Fortran90
SCSL 1.2 Math Library
File System: xfs
System State: Single-user

Notes/Tuning Information

Baseline optimization flags (for C benchmarks):

PASS1 : -Ofast=ip27 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)

PASS2 : -Ofast=ip27 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR_base/\$(EXEBASE)

Baseline optimization flags (for Fortran benchmarks): -Ofast=ip27 -LNO:fusion=2

Portability Flags:

178.galgel: -fixedform

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)

PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)

168.wupwise: -Ofast=ip27 -IPA:space=1000:linear=on:plimit=10000:callee_limit=5000 -INLINE:aggressive=on

. -OPT:Olimit=0 -LNO:fusion=2:prefetch Ahead=5

171.swim: -Ofast=ip27 -LNO:cs2=8m

172.mgrid: -Ofast=ip27 -LNO:cs2=8m:fission=2:ou=2

173.applu: -Ofast=ip27 -LNO:ou_max=5:ou_prod_max=10:prefetch=0:fusion=2

177.mesa: -Ofast=ip27 -OPT:goto=off -LNO:opt=0 (FEEDBACK)

178.galgel: -Ofast=ip27 -LNO:ou_max=7 -lscs (FEEDBACK)

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI 2100 8X 350MHz R12k

SPECfp_rate2000 = 22.8

SPECfp_rate_base2000 = 21.3

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2000 | Hardware Avail: Jun-2000 | Software Avail: Apr-2000

Notes/Tuning Information (Continued)

```
.
  RM_SOURCES = lapak.f90
179.art: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -IPA:min_hot=15 (FEEDBACK)
183.quake: -Ofast=ip27 -LNO:prefetch=0 -TENV:X=4 -CG:ld_latency=7 -IPA:space=500 (FEEDBACK)
187.facerec: -Ofast=ip27 -fb_opt /tmp/SPEC2000/FBDIR_peak/$(EXEBASE) -LNO:fusion=2 (FEEDBACK)
188.ammp: -Ofast=ip27 -OPT:goto=off -IPA:space=500:plimit=900 (FEEDBACK)
189.lucas: -Ofast=ip27 -LNO:fusion=2:blocking=off -CG:ld_latency=4 -IPA:min_hot=8 (FEEDBACK)
191.fma3d: -Ofast=ip27 -bigp_off -LNO:prefetch=0 -OPT:goto=off:unroll_size=160:unroll_times_max=4
  -CG:ld_latency=2 (FEEDBACK)
200.sixtrack:= -Ofast=ip27 -IPA:maxdepth=2 -LNO:prefetch=0 (FEEDBACK)
301.apsi: -Ofast=ip27 -TENV:X=4 -LNO:prefetch=0:blocking=off -IPA:linear=on:use_intrinsic
The following O/S parameters were set:
  setenv PAGESIZE_DATA 4096
  setenv PAGESIZE_TEXT 4096
  setenv PAGESIZE_STACK 4096
  systune -i ; percent_totalmem_4m_pages = 50 ; nlpages_4m = 128
  limit stacksize 500000
The following is done before building each benchmark that requires (FEEDBACK):
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
or
rm -rf /tmp/SPEC2000/FBDIR_base/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_base/$baseexe
```