



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.7 GHz, Pentium 4 processor)

SPECfp2000 = 608

SPECfp_base2000 = 598

SPEC license #: 13 Tested by: Intel Corporation Test date: Apr-2001 Hardware Avail: Apr-2001 Software Avail: Oct-2000

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	186	858	186	858	
171.swim	3100	242	1281	242	1282	
172.mgrid	1800	294	612	272	662	
173.applu	2100	294	714	293	716	
177.mesa	1400	220	635	226	621	
178.galgel	2900	501	579	501	579	
179.art	2600	496	525	482	539	
183.quake	1300	164	791	146	889	
187.facerec	1900	377	504	376	506	
188.ammmp	2200	568	387	564	390	
189.lucas	2000	239	836	239	836	
191.fma3d	2100	444	473	444	473	
200.sixtrack	1100	380	290	375	293	
301.apsi	2600	568	457	568	458	

Hardware

CPU: Pentium 4 processor (1.7 GHz, 400 MHz bus)
 CPU MHz: 1700
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip
 CPU(s) orderable: 1
 Parallel: No
 Primary Cache: 12k micro-ops I + 8KBD
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 256 MB (2 128 MB PC800 RDRAM non-ECC modules)
 Disk Subsystem: IBM DTLA-307030 ATA-100
 Other Hardware: Creative Labs Annihilator 2

Software

Operating System: Windows 2000 (Build 2195) Service Pack 1
 Compiler: Intel C/C++ Compiler 5.0 Build 001120
 Intel Fortran Compiler 5.0 Build 001027
 Microsoft Visual C++ 6.0 (for libraries)
 Other software: Microquill SmartHeap V5.0
 File System: FAT32
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 +FDO
177.mesa: -Qipo -QxW -Oa -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO shlw32M.lib
183.quake: -Qipo -QxW -Qrcd -Oa +FDO shlw32M.lib
187.facerec: -Qipo -QxW -O3 +FDO shlw32M.lib
188.ammmp: -Qipo -Oa -QxW -O3 +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850GB motherboard(1.7 GHz, Pentium 4 processor)

SPECfp2000 = 608

SPECfp_base2000 = 598

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Apr-2001 | Hardware Avail: Apr-2001 | Software Avail: Oct-2000

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO
 301.apsi: -Qipo -QxW -O3 +FDO
 Library ordering for 187.facerec (include SmartHeap correctly with default libs):
 LIBS=libIEPCF90.lib libintrins.lib libF90.lib libqwind.lib libm.lib shlW32M.lib
 LIBC.lib libirc.lib OLDNAMES.lib
 shlW32M.lib is the SmartHeap library V5.0 from Microquill: <http://www.microquill.com>
 Tested systems can be used with Shin-G ATX case, Delta Inc. power supply
 Product description located as of 11/2000:
http://developer.intel.com/design/motherbd/gb/gb_ds.htm
 Motherboard is available through Intel OEM Distribution Channel. See
<http://channel.intel.com/business/ibp/boards/d850gb.htm> for more information
 The system bus runs at 400 MHz