



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 8X 600MHz R14000A

SPECint_rate2000 = 43.3
SPECint_rate_base2000 = 41.9

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	8	437	29.7	8	423	30.7
175.vpr	8	277	46.8	8	260	50.0
176.gcc	8	259	39.4	8	260	39.2
181.mcf	8	340	49.2	8	340	49.2
186.crafty	8	204	45.5	8	209	44.4
197.parser	8	448	37.3	8	426	39.2
252.eon	8	261	46.1	8	239	50.4
253.perlbnk	8	497	33.6	8	496	33.7
254.gap	8	381	26.8	8	372	27.5
255.vortex	8	292	60.4	8	260	67.8
256.bzip2	8	324	42.9	8	307	45.4
300.twolf	8	473	58.9	8	473	58.9

Hardware

CPU: R14000A
 CPU MHz: 600
 FPU: Integrated
 CPU(s) enabled: 8 cores, 8 chips, 1 core/chip
 CPU(s) orderable: 2-32
 Parallel: No
 Primary Cache: 32KBI + 32KBD on chip
 Secondary Cache: 4MB(I+D) off chip
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 8 GB
 Disk Subsystem: 1 x 18 GB FC, 2 x 18 GB FC (striped)
 Other Hardware: None

Software

Operating System: IRIX 6.5.16m
 Compiler: MIPSpro 7.3.1.3m C, C++
 SCSSL 1.4 Math Library
 File System: xfs
 System State: Single-user

Notes/Tuning Information

Baseline optimization flags (C and C++ use same flags):

PASS1 : -Ofast=ip35 -IPA:use_intrinsic -fb_create /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

PASS2 : -Ofast=ip35 -IPA:use_intrinsic -fb_opt /tmp/SPEC2000/FBDIR/base/\$(EXEBASE)

Portability Flags:

176.gcc: -Dalloca=__builtin_alloca -DMIPS -DHOST_WORDS_BIG_ENDIAN

186.crafty: -DSGI

253.perlbnk: -DSPEC_CPU2000_SGI -DI_FCNTL

252.eon: -lm

254.gap: -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO -DSYS_HAS_IOCTL_PROTO
-DSYS_HAS_ANSI -DSYS_HAS_CALLOC_PROTO

300.twolf: -DHAVE_SIGNED_CHAR

Peak optimization flags:

note: all occurrences of (FEEDBACK) below means compiled with a two-step process:

PASS1 = -fb_create /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)

PASS2 = -fb_opt /tmp/SPEC2000/FBDIR_peak/\$(EXEBASE)

164.gzip: -Ofast=ip35 -IPA:space=500:plimit=500 -lmalloc (FEEDBACK)

175.vpr: -Ofast=ip35 -IPA:space=300:plimit=10000:callee_limit=5000:linear=on

. -LNO:prefetch Ahead=2 -INLINE:aggressive=on

. -OPT:Olimit=0:alias=disjoint:alias=restrict -CG:ld_latency=10 -lmalloc (FEEDBACK)

181.mcf: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

SGI
SGI Origin 300 8X 600MHz R14000A

SPECint_rate2000 = 43.3
SPECint_rate_base2000 = 41.9

SPEC license #: 4 | Tested by: SGI | Test date: Apr-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

```

176.gcc: -Ofast=ip35 -CG:ld_latency=4 (FEEDBACK)
186.crafty: -Ofast=ip35 -LNO:prefetch=0 -OPT:goto=off -CG:ld_latency=4 -lmalloc (FEEDBACK)
197.parser: -Ofast=ip35 -IPA:min_hot=14 (FEEDBACK)
252.eon: -Ofast=ip35 -LNO:prefetch=0 -LANG:exceptions=off -CG:ld_latency=4 -lmalloc -lm
      (FEEDBACK)
253.perlbnk: -Ofast=ip35 -IPA:use_intrinsic -Wl,-x (FEEDBACK)
254.gap: -Ofast=ip35 -IPA:use_intrinsic -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4
      -OPT:alias=restrict:alias=disjoint -IPA:min_hot=7 -CG:ld_latency=8 -lmalloc (FEEDBACK)
255.vortex: -Ofast=ip35 -IPA:use_intrinsic
      -OPT:unroll_analysis=off:unroll_size=0:unroll_times_max=4 -LNO:opt=0 -CG:ld_latency=5
      -IPA:min_hot=14 -TENV:X=4 -IPA:space=500:plimit=3600 -OPT:goto=off (FEEDBACK)
256.bzip2: -Ofast=ip35 -IPA:min_hot=5:space=500:plimit=2900 -INLINE:aggressive=on (FEEDBACK)
300.twolf: basepeak=yes

```

The following O/S parameters were set:

```

setenv PAGESIZE_DATA 4096 ; setenv PAGESIZE_TEXT 4096 ; setenv PAGESIZE_STACK 4096
system -i ; percent_totalmem_4m_pages = 40 ; percent_totalmem_1m_pages = 7
system -i ; percent_totalmem_256k_pages = 7 ; percent_totalmem_64k_pages = 7
system -i ; r12k_bdiag = 0x4000000
limit stacksize 500000

```

The following is done before building each benchmark that requires (FEEDBACK):

```
rm -rf /tmp/SPEC2000/FBDIR_peak/$baseexe ; mkdir -p /tmp/SPEC2000/FBDIR_peak/$baseexe
```

Jobs are submitted using dplace. Contents of the placement file submit.pf:

```
memories 1 in topology physical near $NODE
```

```
threads 1
```

```
run thread 0 on memory 0 using cpu $CPU
```

The first disk mentioned in the Disk Subsystem is the system disk. A striped XFS filesystem was created using the rest of the disks and the benchmark was run on this.