



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER850 (810MHz)

SPECfp2000 = 613

SPECfp_base2000 = 458

SPEC license #: 22 Tested by: Fujitsu Limited Test date: Jun-2002 Hardware Avail: Sep-2002 Software Avail: May-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	492	325	272	589
171.swim	3100	677	458	663	467
172.mgrid	1800	505	356	458	393
173.applu	2100	868	242	403	521
177.mesa	1400	468	299	298	470
178.galgel	2900	259	1120	191	1522
179.art	2600	116	2232	73.2	3554
183.earthquake	1300	293	444	155	841
187.facerec	1900	292	652	267	712
188.amp	2200	527	418	391	562
189.lucas	2000	498	402	498	402
191.fma3d	2100	644	326	634	331
200.sixtrack	1100	400	275	291	378
301.apsi	2600	614	424	595	437

Hardware

CPU: SPARC64 GP
CPU MHz: 810
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 4 to 16
Parallel: None
Primary Cache: 128KBI+128KBD on chip
Secondary Cache: 8MB(I+D) off chip, per CPU
L3 Cache: None
Other Cache: None
Memory: 8192MB
Disk Subsystem: 36GB SCSI
Other Hardware: Ethernet

Software

Operating System: Solaris 8 2/02 with patches 108434-07 and 108435-07.
Compiler: Fujitsu Parallelnavi 1.0.2 with patches 911403-01 and 911746-01, Sun ONE Studio 7 with patches 111704-01, 111705-01, 111706-01, 111708-01, 111709-01, 111715-01 and 111716-01, Sun Performance Library 7
File System: ufs
System State: single user

Notes/Tuning Information

```
FDO: (Parallelnavi 1.0.2)
fdo_pre0=rm -rf `pwd`/*.*.d
PASS1=-Kpg PASS2=-Kpu
FDO: (Sun ONE Studio 7)
fdo_pre0=rm -rf `pwd`/../feedback.profile
PASS1=-xprofile=collect:`pwd`/../feedback
PASS2=-xprofile=use:`pwd`/../feedback
Baseline :
(using Fortran compiler of Sun ONE Studio 7)
-fast -xtarget=ultra3 -lprism32 FDO

(using C compiler of Sun ONE Studio 7)
-fast -xipo=2 -xdepend FDO

Peak:
(using Fortran compiler of Parallelnavi 1.0.2)
168.wupwise: -Kfast_GP=2,prefetch=4,nounroll -x dir=`pwd`/../../src
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER850 (810MHz)

SPECfp2000 = 613
SPECfp_base2000 = 458

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Sep-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

-fs -lssl2mtfma FDO ONESTEP=yes

171.swim: -Kfast_GP=2,GREG,preex,ilfunc,prefetch=3,largepage,commonpad=152,prefetch_iteration=3,unroll=2,nogs,frecipro
-O4 -fs

172.mgrid: -Kfast_GP=2,preex,GREG,commonpad=144,unroll=3,largepage,prefetch=3
-O4 -fs

178.galgel: -Kfast_GP=2,GREG,largepage,preex,unroll=3,prefetch_iteration=2,commonpad=24
-O4 -lssl2mtfma -fs FDO

RM_SOURCES=lapak.f90

200.sixtrack: -Kfast_GP=2,GREG,noprefetch,unroll=4,largepage,frecipro -fs

301.apsi: -Kfast_GP=2,GREG,preex,ilfunc,largepage,unroll=2 -O4 -fs

(using FORTRAN77 compiler of Sun ONE Studio 7)

173.applu: -fast -xtarget=ultra3 -Qoption iropt -Adata_access,-Mt7000,-Mm14000,-Mr40000,-Ma400,-whole
-xregs=syst -Qoption iropt -Rscalarrep,-MR -Qoption cg
-Qlp=1-av=192-fa=1 -Qoption f90comp -O3 -stackvar ONESTEP=yes

(using FORTRAN90 compiler of Sun ONE Studio 7)

187.facerec: -fast -xarch=v9 FDO ONESTEP=yes

189.lucas: basepeak=1

191.fma3d: -fast -xarch=v8plusb -xcrossfile -stackvar -xdepend
-xprefetch -Qoption cg -Qlp=1-av=256-t=3-fa=1 FDO ONESTEP=yes

(using C compiler of Sun ONE Studio 7)

177.mesa: -fast -xtarget=ultra2 -xcrossfile -xrestrict -xalias_level=strong
-xregs=syst -Wc,-Qgsched-trace_late=1,-Qgsched-trace_spec_load=1
-xarch=v8plus -W2,-Amemopt -xsafe=mem -dn
FDO ONESTEP=yes

179.art: -fast -xtarget=ultra3 -xipo=2 -xalias_level=strong -xregs=syst -dn
FDO ONESTEP=yes

183.earthquake: -fast -xtarget=ultra3 -xalias_level=std -xdepend
-W2,-whole,-Amemopt:arrayloc,-crit -xprefetch -Wc,-Qms_pipe-pref,-Qlp=1-av=256-t=4-fa=1-fl=1 -lprism32 -lmopt -lm
FDO ONESTEP=yes

188.ammp: -fast -xtarget=ultra3 -xcrossfile -xrestrict
-xalias_level=strong -xdepend -xprefetch
-Wc,-Qiselect-funcalign=64 -lprism32 FDO ONESTEP=yes

Portability:

(for Sun ONE Studio 7)

178.galgel: -e -fixed

(for Parallelnavi 1.0.2)

178.galgel: -Am -Fixed

Note:

System Tunables: (for /etc/system)

consistent_coloring=1, tune_t_fsflushr=86400, autoup=86400,

shmsys:shminfo_shmmax=1477846784, shmsys:shminfo_shmnni=1024, shmsys:shminfo_shmseg=1024,shminfo_shmmin=1

(for /etc/opt/FJSVpnm/lpg.conf)

TSS=512M, SHMSEGSIZE=256M

Shell Environments:

LD_LIBRARY_PATH="/usr/lib:/opt/FD7/SUNWspro/lib/v8plusb:/opt/FD7/SUNWspro/prod/lib/v8plusb:/opt/FSUNf90/lib"

LD_LIBRARY_PATH_64="/usr/lib/64:/opt/FD7/SUNWspro/lib/v9:/opt/FD7/SUNWspro/prod/lib/v9"

PRISM_HEAP=268435456

PRISM_MODE=2

Feedback directed optimization was used for all baseline benchmarks and peak benchmarks except following peak benchmarks: 171.swim, 172.mgrid, 173.applu, 200.sixtrack.

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Fujitsu Siemens Computers
PRIMEPOWER850 (810MHz)

SPECfp2000 =	613
SPECfp_base2000 =	458

SPEC license #: 22 | Tested by: Fujitsu Limited | Test date: Jun-2002 | Hardware Avail: Sep-2002 | Software Avail: May-2002

Notes/Tuning Information (Continued)

System board used with only one CPU present.