



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (1.8 GHz, Pentium 4 processor)

SPECfp2000 = 708

SPECfp_base2000 = 699

SPEC license #: 13 Tested by: Intel Corporation Test date: May-2002 Hardware Avail: May-2002 Software Avail: Apr-2002

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	185	867	184	871	
171.swim	3100	242	1280	239	1297	
172.mgrid	1800	268	672	266	676	
173.applu	2100	277	757	271	776	
177.mesa	1400	207	678	205	682	
178.galgel	2900	293	989	290	999	
179.art	2600	492	528	481	540	
183.quake	1300	151	862	143	909	
187.facerec	1900	237	800	236	803	
188.ammmp	2200	531	414	527	418	
189.lucas	2000	201	996	201	997	
191.fma3d	2100	307	685	306	686	
200.sixtrack	1100	335	329	325	339	
301.apsi	2600	502	518	501	519	

Hardware

CPU: Pentium 4 processor (1.8 GHz, 400 MHz bus)
CPU MHz: 1800
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 256KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC800-40 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional(Build 2600)
Compiler: Intel C++ Compiler 6.0 Build 020321Z
Intel Fortran Compiler 6.0 Build 020321Z
Microsoft Visual C++ 6.0 SP5(for libraries)
File System: FAT32
System State: Default

Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning: -Qipo -QxW -O3 +FDO
Portability:
178.galgel: -FI /F32000000
Peak tuning:
168.wupwise: -Qipo -QxW -O3 +FDO
171.swim: -Qipo -QxW -O3 +FDO
172.mgrid: -Qipo -QaxW -O3 +FDO
173.applu: -Qipo -QxW -O3 -Qscalar_rep- -Qauto +FDO
177.mesa: -Qipo -Oa -QxW -O3 +FDO
178.galgel: -Qipo -QxW -O3 +FDO
179.art: -Qipo -QxW -O3 -Oa +FDO
183.quake: -Qipo -QxW -Oa -Qrcd +FDO
187.facerec: -Qipo -QxW -O3 +FDO
188.ammmp: -Qipo -QxW -O3 -Oa +FDO
189.lucas: -Qipo -QxW -O3 +FDO
191.fma3d: -Qipo -QxW -O3 +FDO
```



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMV2 motherboard (1.8 GHz, Pentium 4 processor)

SPECfp2000 = 708

SPECfp_base2000 = 699

SPEC license #: 13 | Tested by: Intel Corporation | Test date: May-2002 | Hardware Avail: May-2002 | Software Avail: Apr-2002

Notes/Tuning Information (Continued)

200.sixtrack: -Qipo -QxW +FDO

301.apsi: -Qipo -QxW -O3 +FDO

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1 B

Product description located as of 8/2002:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

Motherboard ordering information is available at:

<http://program.intel.com/shared/products/boards/d850emv2/index.htm>

The system bus runs at 400 MHz