





# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Advanced Micro Devices

Asus A7M266-D Motherboard, AMD Athlon (TM) MP 2400+

SPECfp\_rate2000 = 7.61

SPECfp\_rate\_base2000 = 7.01

SPEC license #: 49 | Tested by: AMD Austin, TX | Test date: Nov-2002 | Hardware Avail: Dec-2002 | Software Avail: Feb-2002

## Notes/Tuning Information (Continued)

```
187.facerec: ifl -O3 -QxK -Qipo +FDO
188.ammf:    icl -O3 -QxK -Qwp_ipo -Oa +FDO
189.lucas:   ifl -O3 -QxK -Qwp_ipo +FDO shlw32M.lib
191.fma3d:   ifl -O3 -QxK -Qwp_ipo +FDO
200.sixtrack: ifl -QxK -QaxW -Qwp_ipo -Qprefetch +FDO
301.apsi:    f90 -Optimize:5 -fast
```

Library ordering for 189.lucas (to include SmartHeap correctly with default libs):

```
LIBS=libIEPCF90.lib libintrins.lib libF90.lib
libqwind.lib libm.lib shlw32M.lib LIBC.lib libirc.lib OLDNAMES.lib
```

ONESTEP is used for all base and peak runs

The tested system can be assembled using an ATX case such as the Antec KS-282, a 400W power supply such as the Sparkle FSP400-60GN, and a PCI or AGP video card. The System bus runs at 266MHz