



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.40B GHz, Pentium 4 processor)

SPECint2000 = 1006

SPECint_base2000 = 973

SPEC license #: 13 Tested by: Intel Corporation Test date: Sep-2003 Hardware Avail: Oct-2002 Software Avail: Dec-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	140	1003	139	1006	
175.vpr	1400	230	608	230	608	
176.gcc	1100	96.5	1139	96.4	1141	
181.mcf	1800	227	794	227	793	
186.crafty	1000	110	910	110	910	
197.parser	1800	197	915	197	913	
252.eon	1300	106	1230	93.6	1389	
253.perlbnk	1800	170	1058	152	1184	
254.gap	1100	88.7	1241	88.7	1241	
255.vortex	1900	106	1794	106	1794	
256.bzip2	1500	201	745	194	773	
300.twolf	3000	413	727	361	830	

Hardware

CPU: Intel Pentium 4 Processor (2.40B GHz, 533 MHz bus)
CPU MHz: 2400
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1
Parallel: No
Primary Cache: 12k micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: N/A
Other Cache: N/A
Memory: 256 MB (2 128 MB PC1066-32 RDRAM non-ECC modules)
Disk Subsystem: IBM 120GXP 80 GB IC35L080AVVA07-0 ATA-100
Other Hardware: None

Software

Operating System: Windows XP Professional Service Pack 1a
Compiler: Intel C++ Compiler 8.0
Microsoft Visual Studio .Net 7.0(for libraries)
MicroQuill SmartHeap library V6.0
File System: FAT32
System State: Default

Notes/Tuning Information

```
ONESTEP=yes +FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxN -Qipo -O3 +FDO
Base tuning for C++ programs: -QxN -Qipo -GX -GR
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -QxN -Qipo -Oa -O3 +FDO
175.vpr: -QxN -Qipo -O3 +FDO
176.gcc: -QxN -Qipo -O3 +FDO
181.mcf: -QxN -Qipo -O3 +FDO
186.crafty: -QxN -Qipo -Oa -O3 +FDO
197.parser: -QxN -Qipo -O3 +FDO
252.eon: -QxN -Qipo -O3 +FDO
253.perlbnk: -QxN -Qipo -O3 +FDO shlw32M.lib
254.gap: basepeak=yes
255.vortex: basepeak=yes
256.bzip2: -Qipo -Oa -Qunroll1 +FDO
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Intel Corporation

Intel D850EMVR motherboard (2.40B GHz, Pentium 4 processor)

SPECint2000 = 1006

SPECint_base2000 = 973

SPEC license #: 13 | Tested by: Intel Corporation | Test date: Sep-2003 | Hardware Avail: Oct-2002 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

300.twolf: -QxN -Qipo -O3 +FDO shlw32M.lib

Tested systems can be used with Shin-G ATX case, Delta Inc. power supply PS-300GB-1

Product description located as of 9/2003:

<http://developer.intel.com/design/motherbd/mv2/index.htm>

The system bus runs at 533 MHz

shlw32M.lib is the SmartHeap library V6.0 from <http://www.microquill.com/smartheap/index.html>

An AGP video card is installed