



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3(3.2GHz/1MB L3 cache, Intel Xeon)

SPECint2000 = 1313
SPECint_base2000 = 1239

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Sep-2003 Hardware Avail: Oct-2003 Software Avail: Sep-2003

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	112	1253	112	1252	
175.vpr	1400	162	867	161	870	
176.gcc	1100	69.1	1591	65.1	1690	
181.mcf	1800	241	747	231	779	
186.crafty	1000	81.9	1221	81.9	1221	
197.parser	1800	152	1185	150	1197	
252.eon	1300	92.3	1408	78.8	1649	
253.perlbmk	1800	127	1416	118	1521	
254.gap	1100	67.8	1622	67.7	1625	
255.vortex	1900	99.5	1910	99.4	1912	
256.bzip2	1500	157	956	151	994	
300.twolf	3000	252	1189	185	1621	

Hardware

CPU: Intel Xeon (3.2GHz, 533MHz bus)
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading disabled)
CPU(s) orderable: 1,2
Parallel: No
Primary Cache: 12K micro-ops I + 8KBD on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 1024KB(I+D) on chip
Other Cache: N/A
Memory: 4x512MB PC2100
Disk Subsystem: 2x36.4GB 15K Ultra320 SCSI
Other Hardware:

Software

Operating System: Windows 2000 Server(Build 2195 SP3)
Compiler: Intel C++ Compiler 7.1 Build 20030813Z
Microsoft Visual Studio .NET 7.0.9466 (for libraries)
MicroQuill Smartheap Library 7.0
File System: NTFS
System State: Hyper Threading disabled in BIOS

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -QxW -Qipo -O3 +FDO ONESTEP=yes
Base tuning for C++ programs: -Qipo -GX -GR +FDO ONESTEP=yes
Portability flags:
176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbmk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
164.gzip: -O3 -QxW -Qipo +FDO ONESTEP=yes
175.vpr: -QxW -Qipo -O3 +FDO ONESTEP=yes
176.gcc: -QxW -Qipo -Oi- -O3 +FDO ONESTEP=yes
181.mcf: -Oa -Qipo +FDO shlw32M.lib ONESTEP=yes
186.crafty: -QxW -Qipo -O3 +FDO ONESTEP=yes
197.parser: -QxW -Qipo -Oa -O3 +FDO ONESTEP=yes
252.eon: -QxW -Qipo -O3 +FDO shlw32M.lib ONESTEP=yes
253.perlbmk: -Qipo -Oa -O3 +FDO shlw32M.lib ONESTEP=yes
254.gap: -QxW -Qipo -O3 +FDO ONESTEP=yes
255.vortex: -QxW -Qipo -O3 +FDO ONESTEP=yes
256.bzip2: -Qunroll1 -Oa -Qipo +FDO ONESTEP=yes
```



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL380 G3(3.2GHz/1MB L3 cache, Intel Xeon)

SPECint2000 = 1313
SPECint_base2000 = 1239

SPEC license #: 3 | Tested by: Hewlett-Packard Company | Test date: Sep-2003 | Hardware Avail: Oct-2003 | Software Avail: Sep-2003

Notes/Tuning Information (Continued)

300.twolf: -QxW -Qipo -O3 -Oa +FDO shlw32M.lib ONESTEP=yes