



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**Bull
NovaScale 5160 (1500MHz)**

SPECint_rate2000 = 198
SPECint_rate_base2000 = 196

SPEC license #: 20 | Tested by: Allaoua AIT ELDJOUDI | Test date: Nov-2003 | Hardware Avail: Sep-2003 | Software Avail: Jan-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	16	155	167	16	155	167
175.vpr	16	169	154	16	169	154
176.gcc	16	90.0	227	16	85.9	238
181.mcf	16	233	143	16	229	146
186.crafty	16	83.5	222	16	82.9	224
197.parser	16	218	153	16	217	154
252.eon	16	86.4	279	16	86.4	279
253.perlbnk	16	157	213	16	157	213
254.gap	16	155	132	16	155	132
255.vortex	16	118	300	16	115	306
256.bzip2	16	147	189	16	147	189
300.twolf	16	220	253	16	220	253

Hardware

CPU: Itanium 2 processor 1500 MHz
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
 CPU(s) orderable: 4 to 16
 Parallel: No
 Primary Cache: 16KBI + 16KBD on chip
 Secondary Cache: 256KB(I+D) on chip
 L3 Cache: 6MB (I+D) on chip
 Other Cache: N/A
 Memory: 64 GB (4 * 16 * 1GB DIMMs)
 Disk Subsystem: 1 SJ0812 Disk drawer with 2 15krpm 36GB SCSI disks
 Other Hardware:

Software

Operating System: Bull Advanced Server 3 (linux 64 bits)
 Compiler: Intel(R) C++ Compiler for Linux 8 (Build 20030916)
 MicroQuill SmartHeap Library 7.01 (www.microquill.com)
 File System: ext2
 System State: Multiuser

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -auto_ilp32 +FDO
 C++ programs: -fast -ansi_alias +FDO
 Extra Library: libsmartheap64.a (smh)

Portability Flags:

176.gcc: -DSPEC_CPU2000_LP64 -Dalloca=_builtin_alloca -D_LIBC
 186.crafty: -DLINUX_i386
 252.eon: -DSPEC_CPU2000_LP64 -DHAS_ERRLIST -DFMAX_IS_DOUBLE
 253.perlbnk: -DSPEC_CPU2000_LP64 -DSPEC_CPU2000_NEED_BOOL
 -DSPEC_CPU2000_LINUX_IA64 -DSPEC_CPU2000_GLIBC22
 254.gap: -DSPEC_CPU2000_LP64 -DSYS_HAS_CALLOC_PROTO -DSYS_IS_USG
 -DSYS_HAS_IOCTL_PROTO -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
 255.vortex: -DSPEC_CPU2000_LP64

Peak optimization flags: (default)

C programs: -fast -auto_ilp32 +FDO
 C++ programs: -fast -ansi_alias +FDO
 No Extra Library



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Bull
NovaScale 5160 (1500MHz)

SPECint_rate2000 = 198

SPECint_rate_base2000 = 196

SPEC license #: 20 | Tested by: Allaoua AIT ELDJOUDI | Test date: Nov-2003 | Hardware Avail: Sep-2003 | Software Avail: Jan-2004

Notes/Tuning Information (Continued)

```
164.gzip: basepeak=yes
175.vpr: basepeak=yes
176.gcc: +FDO -ipo -O2 -static -auto_ilp32
186.crafty: +FDO -ipo -O2 -static -auto_ilp32 + smh
197.parser: +FDO -fast -auto_ilp32
252.eon: basepeak=yes
253.perlbnk: basepeak=yes
254.gap: basepeak=yes
255.vortex: +FDO -ipo -O2 -static -auto_ilp32 + smh
256.bzip2: basepeak=yes
300.twolf: basepeak=yes
```