



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V1280 (1200MHz)

SPECfp_rate2000 = 123
SPECfp_rate_base2000 = 99.6

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2004 Hardware Avail: Dec-2003 Software Avail: Dec-2003

2000	1500	1000	500	Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
				168.wupwise	12	231	96.5	12	215	103
				171.swim	12	752	57.4	12	138	314
				172.mgrid	12	446	56.1	12	448	55.9
				173.applu	12	342	85.5	12	251	116
				177.mesa	12	203	96.0	12	193	101
				178.galgel	12	156	259	12	129	313
				179.art	12	28.1	1288	12	25.6	1412
				183.quake	12	158	114	12	156	116
				187.facerec	12	175	151	12	176	150
				188.amp	12	421	72.8	12	388	79.0
				189.lucas	12	685	40.7	12	561	49.6
				191.fma3d	12	596	49.0	12	539	54.2
				200.sixtrack	12	287	53.4	12	251	61.1
				301.apsi	12	439	82.5	12	439	82.4

Hardware

CPU: UltraSPARC III Cu
 CPU MHz: 1200
 FPU: Integrated
 CPU(s) enabled: 12 cores, 12 chips, 1 core/chip
 CPU(s) orderable: 4,8,12
 Parallel: No
 Primary Cache: 32KBI+64KBD on chip
 Secondary Cache: 8MB(I+D) off chip
 L3 Cache: None
 Other Cache: None
 Memory: 24GB 16-way interleaved
 Disk Subsystem: 1 x 36GB FUJITSU MAN3367M SUN36G
 Other Hardware: None

Software

Operating System: Solaris 9 12/03
 Compiler: Sun ONE Studio 8
 Sun Performance Library 8
 File System: ufs with ufs logging
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
 CXX: CC
 F90: f90
 F77: f90

Floating point base flags:

C: -fast -xipo=2 -xalias_level=std with ONESTEP=yes and feedback
 F90: -fast -xipo=2 with ONESTEP=yes and feedback

Floating point peak flags:

ONESTEP=yes and feedback for all benchmarks, unless otherwise noted

168.wupwise: -fast -xipo=2 -Qoption iropt -Ainline:inc=800:cp=1
 171.swim: -fast -xpad=common:3969 -xpagesize=64K -xprefetch=latx:1.6
 -Qoption iropt -Atile:skewp,-Ainline:cs=700
 (no feedback)



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire V1280 (1200MHz)

SPECfp_rate2000 = 123
SPECfp_rate_base2000 = 99.6

SPEC license #: 6 Tested by: Sun Microsystems Test date: Jan-2004 Hardware Avail: Dec-2003 Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```
172.mgrid: -fast -xipo=2
173.applu: -fast -xipo=2
           -Qoption cg -Qlp=1-av=192-fa=1,-Qms_pipe+prefolim=7
           -Qoption iropt -Aujam:inner=g
177.mesa: -fast -xipo=2 -xalias_level=strong -xrestrict
          -Wc,-Qms_pipe+unoovf
178.galgel: -fast -xipo=2 -Qoption iropt -Addint:sf=9 -xlic_lib=sunperf
           RM_SOURCES=lapak.f90
179.art: -fast -xipo=2 -xalias_level=std
         -Wc,-Qms_pipe-prefst,-Qms_pipe+prefolim=11
183.quake: -fast -xipo=2 -xalias_level=strong -xprefetch_level=2
187.facerec: -fast -xipo=2
188.ammp: -fast -xipo=2 -xalias_level=std -xpagesize=512K -lmopt -lm
189.lucas: -fast -xprefetch_level=3 -Qoption iropt -Apf:pdl=1
           -Qoption f90comp -array_pad_rows,1977
191.fma3d: -fast -xipo=2 -stackvar -xprefetch_level=3
           -Qoption iropt -Apf:pdl=1
200.sixtrack: -O -dalign -xchip=ultra3 -xarch=v8plusb -fsimple=2
301.apsi: -fast -xipo=2
```

Feedback is done as follows, unless otherwise noted:

```
fdo_pre0: rm -rf ./feedback.profile ./SunWS_cache
PASS1: -xprofile=collect:./feedback
PASS2: -xprofile=use:./feedback
```

Portability:

```
178.galgel: -e -fixed
```

Shell Environments:

```
Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1
```

Kernel Parameters (/etc/system):

```
autoup=900
tune_t_fsflushr=1
```

Processes were bound to CPUs using submit=pbind