



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 6600 (3.0 GHz Xeon MP)

SPECint_rate2000 = 16.3

SPECint_rate_base2000 = 16.0

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Dec-2003 | Hardware Avail: Jan-2004 | Software Avail: Apr-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	1	120	13.5	1	120	13.5
175.vpr	1	126	12.9	1	126	12.9
176.gcc	1	68.6	18.6	1	68.8	18.5
181.mcf	1	128	16.3	1	130	16.1
186.crafy	1	85.3	13.6	1	85.2	13.6
197.parser	1	142	14.7	1	142	14.7
252.eon	1	98.2	15.4	1	84.7	17.8
253.perlbnk	1	129	16.1	1	127	16.5
254.gap	1	73.0	17.5	1	73.0	17.5
255.vortex	1	91.8	24.0	1	91.8	24.0
256.bzip2	1	117	14.9	1	111	15.6
300.twolf	1	204	17.1	1	193	18.0

Hardware

CPU: Intel Xeon MP (400 MHz system bus)
 CPU MHz: 3000
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology disabled)
 CPU(s) orderable: 1,2,4
 Parallel: No
 Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
 Secondary Cache: 512KB(I+D) on chip
 L3 Cache: 4096KB(I+D) on chip
 Other Cache: N/A
 Memory: 4 x 1024MB DDR200
 Disk Subsystem: 1 x 36GB SEAGATE SCSI
 Other Hardware:

Software

Operating System: Windows 2000 Advanced Server (SP2)
 Compiler: Intel C++ Compiler 7.1 (20030402Z)
 Microsoft Visual Studio .NET (7.0.9466)
 MicroQuill SmartHeap Library 6.01
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
 186.crafy: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

FEEDBACK DIRECTED OPTIMIZATION

FDO: PASS1= -Qprof_gen PASS2=-Qprof_use

BASE TUNING

C: -QxW -Qipo -O3 +FDO
 C++: -QxW -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxW -Qipo -Oa -O3 +FDO
 175.vpr: -QxW -Qipo -O3 +FDO
 176.gcc: -QxW -Qipo -O3 +FDO
 181.mcf: -QxW -Qipo -O3 +FDO shlw32M.lib
 186.crafy: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3
 197.parser: -QxW -Qipo -O3 +FDO
 252.eon: PASS1= -Qprof_gen PASS2= -Qipo -Qprof_use -QxW -O3
 253.perlbnk: -QxW -Qipo -O3 +FDO shlw32M.lib
 254.gap: basepeak=yes



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell
PowerEdge 6600 (3.0 GHz Xeon MP)

SPECint_rate2000 = 16.3

SPECint_rate_base2000 = 16.0

SPEC license #: 55 | Tested by: Dell, Round Rock, TX | Test date: Dec-2003 | Hardware Avail: Jan-2004 | Software Avail: Apr-2003

Notes/Tuning Information (Continued)

```
255.vortex    basepeak=yes
256.bzip2:    -Qipo -Oa -Qunroll1 +FDO
300.twolf:    -Qipo -QxW -O3 -Oa      shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 6.01
              www.microquill.com
ONESTEP=YES is set for all benchmarks
Hyper-Threading Technology disabled in BIOS
```