



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell

Precision Workstation 650 (3.06 GHz Xeon, 1MB L3 Cache)

SPECint_rate2000 = 28.5

SPECint_rate_base2000 = 27.4

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Jan-2004 | Hardware Avail: Feb-2004 | Software Avail: Dec-2003

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.gzip	2	112	29.1	2	112	29.1
175.vpr	2	182	17.9	2	182	17.9
176.gcc	2	74.5	34.3	2	74.5	34.3
181.mcf	2	305	13.7	2	305	13.7
186.crafty	2	83.7	27.7	2	83.2	27.9
197.parser	2	153	27.2	2	153	27.2
252.eon	2	81.3	37.1	2	71.3	42.3
253.perlbnk	2	132	31.7	2	124	33.6
254.gap	2	78.6	32.5	2	78.6	32.5
255.vortex	2	89.0	49.5	2	89.0	49.5
256.bzip2	2	177	19.7	2	172	20.3
300.twolf	2	263	26.5	2	208	33.5

Hardware

CPU: Intel Xeon (533 MHz system bus)
CPU MHz: 3066
FPU: Integrated
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip (Hyper-Threading Technology disabled)
CPU(s) orderable: 2
Parallel: No
Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 1024(I+D) on chip
Other Cache: N/A
Memory: 4 x 512MB ECC CL2-2-2 PC2100 DDR SDRAM
Disk Subsystem: 1 x 18GB U320 SCSI, 10K RPM
Other Hardware:

Software

Operating System: Windows XP Professional SP1
Compiler: Intel C/C++ Compiler 8.0 (20031229Z)
Microsoft Visual Studio .NET (7.0.9466)
File System: NTFS
System State: Default

Notes/Tuning Information

GENERAL

ONESTEP=yes
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

PORTABILITY FLAGS

176.gcc: -Dalloca=_alloca /F10000000
186.crafty: -DNT_i386
253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO

BASE TUNING

C: -QxN -Qipo -O3 +FDO
C++: -QxN -Qipo -GX -GR

PEAK TUNING

164.gzip: -QxN -Qipo -O3 -Oa +FDO
175.vpr: basepeak=yes
176.gcc: basepeak=yes
181.mcf: -QxN -Qipo -O3 +FDO shlw32M.lib
186.crafty: -QxN -Qipo -O3 -Oa +FDO shlw32M.lib
197.parser: basepeak=yes
252.eon: -QxN -Qipo -O3 +FDO
253.perlbnk: -QxN -Qipo -O3 +FDO shlw32M.lib



CINT2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Dell

Precision Workstation 650 (3.06 GHz Xeon, 1MB L3 Cache)

SPECint_rate2000 = 28.5

SPECint_rate_base2000 = 27.4

SPEC license #: 55 | Tested by: Dell Inc., Round Rock, TX | Test date: Jan-2004 | Hardware Avail: Feb-2004 | Software Avail: Dec-2003

Notes/Tuning Information (Continued)

```
254.gap:      basepeak=yes
255.vortex    basepeak=yes
256.bzip2:    -Qipo      -Oa -Qunroll1 +FDO shlw32M.lib
300.twolf:    -QxN -Qipo -O3      +FDO shlw32M.lib
EXTRA LIBRARIES
shlw32M.lib:  MicroQuill SmartHeap Library 7.1
              www.microquill.com
```

NOTES

Hyper-Threading Technology not enabled.