



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**ION Computer Systems**  
SR2300WV2 (3.2GHz Xeon processor w. 1MB L3 cache)

SPECfp\_rate2000 = 17.6  
SPECfp\_rate\_base2000 = 17.5

SPEC license #: 2697 | Tested by: ION | Test date: Feb-2004 | Hardware Avail: Nov-2003 | Software Avail: Jan-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	128	29.0	2	128	29.0
171.swim	2	474	15.2	2	474	15.2
172.mgrid	2	305	13.7	2	300	13.9
173.applu	2	369	13.2	2	369	13.2
177.mesa	2	97.0	33.5	2	97.0	33.5
178.galgel	2	254	26.4	2	241	27.9
179.art	2	608	9.91	2	615	9.81
183.quake	2	173	17.5	2	169	17.9
187.facerec	2	179	24.6	2	179	24.6
188.amp	2	348	14.7	2	348	14.7
189.lucas	2	330	14.0	2	330	14.0
191.fma3d	2	276	17.7	2	276	17.7
200.sixtrack	2	180	14.1	2	180	14.1
301.apsi	2	360	16.8	2	360	16.8

### Hardware

CPU: Intel Xeon processor, 533MHz system bus  
CPU MHz: 3200  
FPU: Integrated  
CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
CPU(s) orderable: 1-2  
Parallel: No  
Primary Cache: 12K(I) micro-ops + 8KB(D) on chip  
Secondary Cache: 512KB(I+D) on chip  
L3 Cache: 1024KB(I+D) on chip  
Other Cache: None  
Memory: 2 GB (2x1GB 2-2-2 DIMMs)  
Disk Subsystem: 1x 80GB IDE  
Other Hardware: None

### Software

Operating System: Red Hat Enterprise Linux ES release 3  
Compiler: Intel(R) Fortran Compiler for Linux 8.0 (Build 20031231Z)  
Intel(R) C++ Compiler for Linux 8.0 (Build 20031231Z)  
File System: ext2  
System State: Multi-user, 2.4.21 smp kernel

## Notes/Tuning Information

HyperThreading disabled in BIOS

Baseline optimization flags:

C programs: PASS1= -xW -prof\_gen PASS2= -xW -ipo -O3 -prof\_use  
Fortran programs: PASS1= -xW -prof\_gen PASS2= -xW -ipo -O3 -prof\_use

FP Peak optimization flags:

168.wupwise: basepeak=yes  
171.swim: basepeak=yes  
172.mgrid: PASS1= -xN -prof\_gen PASS2= -xN -ipo -O3 -prof\_use  
173.applu: basepeak=yes  
177.mesa: basepeak=yes  
178.galgel: PASS1= -xN -prof\_gen PASS2= -xN -ipo -O3 -prof\_use  
179.art: PASS1= -xN -prof\_gen PASS2= -xN -ipo -O3 -prof\_use  
183.quake: PASS1= -xN -prof\_gen PASS2= -xN -ipo -O3 -prof\_use  
187.facerec: basepeak=yes  
188.amp: basepeak=yes



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

**ION Computer Systems**

SR2300WV2 (3.2GHz Xeon processor w. 1MB L3 cache)

SPECfp\_rate2000 = 17.6

SPECfp\_rate\_base2000 = 17.5

SPEC license #: 2697 | Tested by: ION | Test date: Feb-2004 | Hardware Avail: Nov-2003 | Software Avail: Jan-2004

## Notes/Tuning Information (Continued)

```
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes
```

```
FP Portability Flags:
178.galgel: -FI
```