



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems
SR2300WV2 (3.2GHz Xeon processor w. 1MB L3 cache)

SPECfp2000 = **1078**
SPECfp_base2000 = **1107**

SPEC license #: 2697 | Tested by: ION | Test date: Feb-2004 | Hardware Avail: Nov-2003 | Software Avail: Jan-2004

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
168.wupwise	1600	106	1511	106	1511	
171.swim	3100	214	1448	214	1448	
172.mgrid	1800	175	1030	221	813	
173.applu	2100	208	1010	208	1010	
177.mesa	1400	95.1	1472	95.1	1472	
178.galgel	2900	168	1724	170	1710	
179.art	2600	305	853	307	846	
183.quake	1300	105	1244	117	1110	
187.facerec	1900	138	1373	138	1373	
188.amp	2200	307	717	307	717	
189.lucas	2000	164	1217	164	1217	
191.fma3d	2100	208	1011	208	1011	
200.sixtrack	1100	180	612	180	612	
301.apsi	2600	284	914	284	914	

Hardware

CPU: Intel Xeon processor, 533MHz system bus
CPU MHz: 3200
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 1-2
Parallel: No
Primary Cache: 12K(I) micro-ops + 8KB(D) on chip
Secondary Cache: 512KB(I+D) on chip
L3 Cache: 1024KB(I+D) on chip
Other Cache: None
Memory: 2 GB (2x1GB 2-2-2 DIMMs)
Disk Subsystem: 1x 80GB IDE
Other Hardware: None

Software

Operating System: Red Hat Enterprise Linux ES release 3
Compiler: Intel(R) Fortran Compiler for Linux 8.0 (Build 20031231Z)
Intel(R) C++ Compiler for Linux 8.0 (Build 20031231Z)
File System: ext2
System State: Multi-user, 2.4.21 smp kernel

Notes/Tuning Information

Only 1 processor installed
HyperThreading disabled in BIOS

Baseline optimization flags:

C programs: PASS1= -xW -prof_gen PASS2= -xW -ipo -O3 -prof_use
Fortran programs: PASS1= -xW -prof_gen PASS2= -xW -ipo -O3 -prof_use

FP Peak optimization flags:

168.wupwise: basepeak=yes
171.swim: basepeak=yes
172.mgrid: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
173.applu: basepeak=yes
177.mesa: basepeak=yes
178.galgel: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
179.art: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
183.quake: PASS1= -xN -prof_gen PASS2= -xN -ipo -O3 -prof_use
187.facerec: basepeak=yes



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

ION Computer Systems

SR2300WV2 (3.2GHz Xeon processor w. 1MB L3 cache)

SPECfp2000 = 1078

SPECfp_base2000 = 1107

SPEC license #: 2697 | Tested by: ION | Test date: Feb-2004 | Hardware Avail: Nov-2003 | Software Avail: Jan-2004

Notes/Tuning Information (Continued)

188.ammmp: basepeak=yes
189.lucas: basepeak=yes
191.fma3d: basepeak=yes
200.sixtrack: basepeak=yes
301.apsi: basepeak=yes

FP Portability Flags:
178.galgel: -FI