



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V20z

SPECfp\_rate2000 = 19.6

SPECfp\_rate\_base2000 = 18.0

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	1	96.3	19.3	1	76.1	24.4
171.swim	1	154	23.3	1	146	24.6
172.mgrid	1	129	16.1	1	110	18.9
173.applu	1	159	15.3	1	139	17.6
177.mesa	1	76.6	21.2	1	70.7	23.0
178.galgel	1	108	31.0	1	99.0	34.0
179.art	1	166	18.2	1	117	25.8
183.quake	1	96.3	15.7	1	91.0	16.6
187.facerec	1	85.0	25.9	1	85.0	25.9
188.amp	1	160	15.9	1	157	16.2
189.lucas	1	132	17.5	1	132	17.5
191.fma3d	1	141	17.3	1	141	17.3
200.sixtrack	1	148	8.60	1	148	8.60
301.apsi	1	175	17.2	1	173	17.5

### Hardware

CPU: AMD Opteron (TM) 250  
CPU MHz: 2400  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 64KBI + 64KBD on chip  
Secondary Cache: 1024KB (I+D) on chip  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 4x1GB, PC2700 CL2.5 DDR SDRAM ECC Registered  
Disk Subsystem: SCSI, 73GB, 10K RPM  
Other Hardware: None

### Software

Operating System: SuSE Linux 8.0 SLES 64 bit (SP3)  
Compiler: PathScale EKO Compiler Suite, Release 1.1  
SuSE optional gcc 3.3 (from SLES8 SP3)  
PGI Fortran 5.2 (build 5.2-0E)  
AMD Core Math Library (Version 2.0) for AMD64  
File System: Linux/ext3  
System State: Multi-user, Run level 3

## Notes/Tuning Information

A two-pass compilation method is used where indicated:

+PSFDO indicates PathScale feedback

PASS1: -fb\_create fbdata

PASS2: -fb\_opt fbdata

+ACML is the AMD Core Math Library V2.0

Compilers:

C: pathcc (PathScale C) unless otherwise noted

Fortran: pathf90 (PathScale f90) unless otherwise noted

If other compilers are used, they are indicated as:

gcc: Gnu C

pgf90: PGI Fortran

Floating Point base tuning:

Fortran: pgf90 -fastsse -Mipa=fast -Msmart

C: pathcc -Ofast -WOPT:mem\_opnds=on +PSFDO

Standard Performance Evaluation Corporation

info@spec.org

http://www.spec.org



# CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Sun Microsystems  
Sun Fire V20z

SPECfp\_rate2000 = 19.6

SPECfp\_rate\_base2000 = 18.0

SPEC license #: 6 Tested by: Sun Microsystems, Santa Clara Test date: Jul-2004 Hardware Avail: Jul-2004 Software Avail: Jul-2004

## Notes/Tuning Information (Continued)

Floating Point peak tuning:

```

168.wupwise: pgf90 -fastsse -Mipa=fast,inline -Msmart
171.swim: -Ofast -OPT:ro=3 -LNO:fusion=2:prefetch=2
172.mgrid: -O3 -OPT:Ofast
           -LNO:fusion=2:blocking=off:ou_max=5:sclrze=off:prefetch=2
           -OPT:unroll_times=8:unroll_size=256:ro=3
           -CG:gcm=off:cflow=off
173.applu: -O3 -ipa
           -LNO:fusion=2:interchange=OFF:blocking=OFF:ou_prod_max=10
           :ou_max=5:prefetch=2 -OPT:IEEE_arith=1:ro=3:unroll_size=0
           -TENV:X=4 -WOPT:mem_opnds=on:retype_expr=on:val=0 -CG:local_fwd_sched=on
177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on +PSFDO
178.galgel: pgf90 -fastsse -Mipa=fast -mp +ACML
           RM_SOURCES=lapak.f90 ONESTEP
179.art: -O3 -OPT:Ofast -fno-math-errno -m32 +PSFDO
183.earthquake: gcc -DSPEC_CPU2000_LP64 -O3 -funroll-all-loops -ffast-math
           -finline-limit=2000 ONESTEP
187.facerec: basepeak=true
188.ammp: -O3 -OPT:alias=disjoint:unroll_times=8:Ofast:ro=3
           -fno-math-errno -TENV:X=4 +PSFDO
189.lucas: pgf90 -fastsse -Mipa=fast,inline -Msmart
191.fma3d: basepeak=true
200.sixtrack: basepeak=true
301.apsi: -Ofast -TENV:X=4 -LNO:fusion=2:prefetch=0:blocking=off
           -IPA:linear=on:plimit=525

```

Portability:

178.galgel: -Mfixed

Notes:

BIOS build 2.1.0.9E, default setting was used.  
 Second CPU was physically removed from the system.