



CFP2000 Result

Copyright ©1999-2004, Standard Performance Evaluation Corporation

Bull
NovaScale 6320 HPC 16way (1600MHz)

SPECfp_rate2000 = 373
SPECfp_rate_base2000 = 373

SPEC license #: 20 | Tested by: Allaoua Ait Eldjoudi | Test date: Nov-2004 | Hardware Avail: Nov-2004 | Software Avail: Nov-2004

				Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
4000	3000	2000	1000	168.wupwise	16	91.8	324	16	91.8	324
				171.swim	16	147	391	16	147	391
				172.mgrid	16	128	261	16	128	261
				173.applu	16	59.2	658	16	59.2	658
				177.mesa	16	110	237	16	110	237
				178.galgel	16	40.7	1323	16	40.7	1323
				179.art	16	20.8	2325	16	20.8	2325
				183.quake	16	70.6	342	16	70.6	342
				187.facerec	16	103	342	16	103	342
				188.amp	16	172	237	16	172	237
				189.lucas	16	162	229	16	162	229
				191.fma3d	16	176	222	16	176	222
				200.sixtrack	16	80.0	255	16	80.0	255
				301.apsi	16	268	180	16	268	180

Hardware

CPU: Itanium 2 processor 1600 MHz
 CPU MHz: 1600
 FPU: Integrated
 CPU(s) enabled: 16 cores, 16 chips, 1 core/chip
 CPU(s) orderable: 4 to 16
 Parallel: No
 Primary Cache: 16KBI + 16KBD on chip, per core
 Secondary Cache: 256KB(I+D) on chip, per core
 L3 Cache: 9.0MB (I+D) on chip, per core
 Other Cache: N/A
 Memory: 128 GB (8 * 16 * 1GB DIMMs)
 Disk Subsystem: 1 SJ0812 Disk drawer with
 2 15krpm 36GB SCSI disks
 Other Hardware: --

Software

Operating System: Bull Advanced Server 2 V3 (linux kernel 2.6.4, glibc 2.2.4)
 Compiler: Intel(R) Fortran Compiler for Linux 8.1 (Build 20041021)
 Intel(R) C++ Compiler for Linux 8.1 (Build 20041021)
 File System: ext3
 System State: Multi User

Notes/Tuning Information

+FDO: PASS1=-prof_gen PASS2=-prof_use

Baseline optimization flags:

C programs: -fast -ansi_alias -IPF_fp_relaxed +FDO
 Fortran programs: -fast -IPF_fp_relaxed + FDO

Portability Flags:

178.galgel: -FI

Peak optimization flags: basepeak=yes

32 CPU machine with only 16 CPU enabled
 16 CPU disabled by service processor before booting
 Processes were bound to CPUs using pexec