




# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL145 G2 (AMD Opteron (TM) 254)

SPECfp\_rate2000 = 48.2  
SPECfp\_rate\_base2000 = 44.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Sep-2005



### Hardware

CPU: AMD Opteron (TM) 254  
 CPU MHz: 2800  
 FPU: Integrated  
 CPU(s) enabled: 2 cores, 2 chips, 1 core/chip  
 CPU(s) orderable: 1,2  
 Parallel: No  
 Primary Cache: 64KBI + 64KBD on chip  
 Secondary Cache: 1024KB(I+D) on chip  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8x2048MB PC3200 CL3.0  
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI  
 Other Hardware:

### Software

Operating System: SuSE Linux Enterprise Server 9 (x86\_64) SP 2  
 SuSE kernel 2.6.5-7.191-smp  
 Compiler: PathScale EKOPath(TM) Compiler Suite, Release 2.2.1  
 AMD Core Math Library 2.5.1  
 File System: Linux/ext2  
 System State: Multi-user run level 3

## Notes/Tuning Information

```
+FDO: PASS1= -fb_create fbdata PASS2= -fb_opt fbdata
+ACML: Linked with AMD Core Math Library
Base tuning for C programs: -Ofast -WOPT:mem_opnds=on +FDO
Base tuning for FORTRAN programs: -Ofast -LNO:fusion=2 -OPT:fast_complex=on +FDO
Portability flags:
  178.galgel: -fixedform
Peak tuning:
  168.wupwise: -Ofast -LNO:prefetch Ahead=5:prefetch=3
              -OPT:unroll_times_max=8:unroll_size=128:IEEE NaN_Inf=off:ro=3
              -IPA:linear=on:plimit=50000:callee_limit=5000 -INLINE:aggressive=on
  171.swim: -Ofast -CG:local_fwd_sched=on -LNO:fusion=2 -m3dnow
  172.mgrid: -Ofast -CG:gcm=off -OPT:IEEE_a=3:unroll_size=200
              -LNO:fusion=2:fission=1:blocking=off:prefetch Ahead=2 -WOPT:mem_opnds=on:aggstr=0
  173.applu: -Ofast -CG:local_fwd_sched=on -OPT:ro=3 -TENV:X=3
              -LNO:fusion=2:fission=2:full_unroll_size=10000 +FDO
  177.mesa: -O2 -ipa -OPT:Ofast -fno-math-errno -CG:local_fwd_sched=on
              -WOPT:mem_opnds=on +FDO
```



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company  
ProLiant DL145 G2 (AMD Opteron (TM) 254)

SPECfp\_rate2000 = 48.2  
SPECfp\_rate\_base2000 = 44.2

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Sep-2005

## Notes/Tuning Information (Continued)

```

178.galgel: -Ofast -OPT:fast_complex-on RM_SOURCES=lapak.f90 +ACML +FDO
179.art: -O3 -OPT:Ofast -fno-math-errno -mno-sse2 -m32
183.equake: -Ofast -CG:load_exe=2 -WOPT:mem_opnds=on -m32 +FDO
187.facerec: -Ofast -LNO:fusion=2 -OPT:fast_complex=on:IEEE_NaN_Inf=off:unroll_size=0 +FDO
188.ammp: -O3 -OPT:alias=disjoint:unroll_times_max=8:Ofast:ro=3
          -fno-math-errno -TENV:X=4 +FDO
189.lucas: -Ofast -OPT:ro=3:fast_nint=off:unroll_size=256 -WOPT:mem_opnds=on +FDO
191.fma3d: -O2 -ipa -CG:load_exe=1 -OPT:Ofast:IEEE_arith=3:ro=3
          -WOPT:mem_opnds=on:retype_expr=on -IPA:pu_reorder=1 +FDO
200.sixtrack: -O3 -OPT:Ofast:Olimit=6000:early_intrinsics=on -fno-math-errno
          -CG:load_exe=1 +FDO
301.apsi: -Ofast -CG:load_exe=0 -LNO:prefetch=0:simd=2

```

BIOS Configuration Notes  
Node Interleaving is Disabled

Other Configuration Notes  
Taskset utility used to bind process to CPU(s)