



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## Fujitsu Siemens Computers

PRIMERGY RX200 S2, Intel Xeon processor 3.20GHz, 2MB L2

SPECfp\_rate2000 = 20.5

SPECfp\_rate\_base2000 = 20.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	2	135	27.5	2	135	27.5
171.swim	2	252	28.6	2	252	28.6
172.mgrid	2	231	18.0	2	231	18.0
173.applu	2	321	15.2	2	321	15.2
177.mesa	2	195	16.6	2	195	16.6
178.galgel	2	198	34.0	2	198	34.0
179.art	2	163	37.0	2	163	37.0
183.quake	2	87.7	34.4	2	87.7	34.4
187.facerec	2	190	23.2	2	190	23.2
188.amp	2	384	13.3	2	384	13.3
189.lucas	2	232	20.0	2	232	20.0
191.fma3d	2	295	16.5	2	295	16.5
200.sixtrack	2	273	9.35	2	273	9.35
301.apsi	2	372	16.2	2	372	16.2

### Hardware

CPU: Intel Xeon processor 3.20GHz, 2MB L2, 800MHz system bus  
CPU MHz: 3200  
FPU: Integrated  
CPU(s) enabled: 1 core, 1 chip, 1 core/chip (Hyper-Threading Technology enabled)  
CPU(s) orderable: 1,2  
Parallel: No  
Primary Cache: 12k micro-ops I + 16KBD on chip, per core  
Secondary Cache: 2048KB(I+D) on chip, per core  
L3 Cache: N/A  
Other Cache: N/A  
Memory: 8x512 MB DDRII-RAM PC2-3200R  
Disk Subsystem: Seagate ST336753LC(U320 SCSI, 15krpm)  
Other Hardware: none

### Software

Operating System: Windows Server 2003 Enterprise Edition + SP1  
Compiler: Intel C and Fortran Compiler 9.0  
Build 20050722Z (for 32-bit applications),  
Microsoft Visual Studio .Net 2003  
7.1.3088 (for libraries),  
SmartHeap Library Version 7.4  
from <http://www.microquill.com>  
File System: NTFS  
System State: Default

## Notes/Tuning Information

### GENERAL

+FDO: PASS1=-Qprof\_gen PASS2=-Qprof\_use

### Portability flags

178.galgel: -FI /F32000000

### Base tuning flags

for Fortran programs: -fast -Qansi\_alias +FDO shlw32M.lib  
for C programs: -fast +FDO shlw32M.lib

### Peak tuning flags

same as baseline (basepeak=true set globally)

New 32-bit Windows tools used, approved in May-2005

The system bus runs at 800 MHz



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

**Fujitsu Siemens Computers**

PRIMERGY RX200 S2, Intel Xeon processor 3.20GHz, 2MB L2

SPECfp\_rate2000 = 20.5

SPECfp\_rate\_base2000 = 20.5

SPEC license #: 22 | Tested by: Fujitsu Siemens Computers | Test date: Nov-2005 | Hardware Avail: Oct-2005 | Software Avail: Sep-2005

## Notes/Tuning Information (Continued)

This result was measured with 32-bit binaries using the 32-bit version of the operating system.

For information about Fujitsu Siemens Computers in your country please see:  
<http://www.fujitsu-siemens.com/countries>