



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL145 G2 (AMD Opteron (TM) 275)

SPECint2000 = 1561
SPECint_base2000 = 1490

SPEC license #: 3 Tested by: Hewlett-Packard Company Test date: Dec-2005 Hardware Avail: Sep-2005 Software Avail: Nov-2005

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio	
164.gzip	1400	115	1216	115	1216	
175.vpr	1400	114	1228	110	1273	
176.gcc	1100	67.0	1642	66.2	1661	
181.mcf	1800	163	1102	138	1306	
186.crafty	1000	69.5	1439	63.1	1585	
197.parser	1800	128	1403	128	1402	
252.eon	1300	58.9	2206	54.1	2403	
253.perlbnk	1800	120	1498	120	1498	
254.gap	1100	70.0	1572	70.0	1572	
255.vortex	1900	83.0	2289	83.3	2281	
256.bzip2	1500	124	1208	123	1222	
300.twolf	3000	197	1526	169	1773	

Hardware

CPU: AMD Opteron (TM) 275
 CPU MHz: 2200
 FPU: Integrated
 CPU(s) enabled: 1 core, 1 chip, 2 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 64KBI + 64KBD (on chip) per core
 Secondary Cache: 1024KB(I+D) (on chip) per core
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 4x2048MB PC3200 CL3.0
 Disk Subsystem: 1x36.4GB 15K Ultra320 SCSI
 Other Hardware:

Software

Operating System: Windows Server 2003 Enterprise SP1
 Compiler: Intel C++ Compiler 8.0 Build 20040318Z
 Microsoft Visual Studio .NET 7.0.9466 (for libraries)
 MicroQuill Smartheap Library 7.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

```
+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use
Base tuning for C programs: -fast -arch:SSE2 -Oi- +FDO ONESTEP=yes
Base tuning for C++ programs: -fast -GX -GR +FDO ONESTEP=yes
Portability flags:
 176.gcc: -Dalloca=_alloca /F10000000
 186.crafty: -DNT_i386
 253.perlbnk: -DSPEC_CPU2000_NTOS -DPERLDLL /MT
 254.gap: -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_MALLOC_PROTO
Peak tuning:
 164.gzip: basepeak=yes
 175.vpr: -fast -arch:SSE2 -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 176.gcc: -fast -arch:SSE2 -Oi- -Qunroll3 +FDO
 181.mcf: -fast -QaxN +FDO ONESTEP=yes
 186.crafty: -fast -arch:SSE2 +FDO ONESTEP=yes
 197.parser: -arch:SSE2 -Oi- -Qipo +FDO ONESTEP=yes
 252.eon: -fast -arch:SSE2 -Qansi_alias -Qoption,c,-ip_ninl_max_stats=2000
          -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO ONESTEP=yes
 253.perlbnk: basepeak=yes
 254.gap: basepeak=yes
```



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Hewlett-Packard Company
ProLiant DL145 G2 (AMD Opteron (TM) 275)

SPECint2000 =	1561
SPECint_base2000 =	1490

SPEC license #:	3	Tested by:	Hewlett-Packard Company	Test date:	Dec-2005	Hardware Avail:	Sep-2005	Software Avail:	Nov-2005
-----------------	---	------------	-------------------------	------------	----------	-----------------	----------	-----------------	----------

Notes/Tuning Information (Continued)

```
255.vortex: -fast -arch:SSE2 -Oi- -Qoption,c,-ip_ninl_max_stats=2000
            -Qoption,c,-ip_ninl_max_total_stats=4500 +FDO shlw32M.lib ONESTEP=yes
256.bzip2:  -fast -Qunroll2
300.twolf:  -fast -arch:SSE2 -Qansi_alias +FDO shlw32M.lib ONESTEP=yes
BIOS Configuration Notes
Node Interleaving Disabled
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke uniprocessor environment.
```