



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E20K (32 processor)

SPECint_rate2000 = 660
SPECint_rate_base2000 = 554

SPEC license #: 6 Tested by: Sun Microsystems Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
164.zip	64	224	464	64	204	509
175.vpr	64	193	539	64	184	564
176.gcc	64	279	292	128	236	693
181.mcf	64	268	499	64	221	606
186.crafty	64	99.3	748	64	91.1	815
197.parser	64	247	542	64	213	627
252.eon	64	128	754	64	118	815
253.perlbnk	64	199	672	64	191	698
254.gap	64	288	283	192	586	418
255.vortex	64	133	1062	64	127	1110
256.bzip2	64	187	596	64	183	608
300.twolf	64	358	622	64	325	685

Hardware

CPU: UltraSPARC IV+
 CPU MHz: 1500
 FPU: Integrated
 CPU(s) enabled: 64 cores, 32 chips, 2 cores/chip
 CPU(s) orderable: 4-36 (order by number of chips, groups of 4)
 Parallel: No
 Primary Cache: 64KBI+64KBD per core on chip (128KBI+128KBD on chip)
 Secondary Cache: 2MB(I+D) per chip (on chip)
 L3 Cache: 32MB(I+D) per chip (off chip)
 Other Cache: None
 Memory: 256GB 16-way interleaved
 Disk Subsystem: Sun StorEdge D240 Media Tray (2x73GB)
 Sun StorEdge 6120 Array (14x73GB)
 Other Hardware: None

Software

Operating System: Solaris 10
 Compiler: Sun Studio 11
 File System: ufs (default ufs logging on with Solaris 10)
 System State: Multi-User

Notes/Tuning Information

Compiler invocation:

C: cc
CXX: CC

Integer base flags:

-fast -xipo=2 with ONESTEP=yes and feedback

Integer peak flags:

ONESTEP=yes for all benchmarks
Profile feedback used for those marked with +FDO

164.zip: -x04 -xbuiltin=%all -xtarget=native -xalias_level=std
 -xipo=2 -Wc,-Qeps:enabled=1,-Qeps:rp_filtering_margin=30,
 -Qeps:do_spec_load=1 +FDO
 175.vpr: -fast -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1,
 -Qeps:rp_filtering_margin=30 -xipo=2 -xpagesize_stack=8K
 -lmopt -lm +FDO



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E20K (32 processor)

SPECint_rate2000 = 660
SPECint_rate_base2000 = 554

SPEC license #: 6 Tested by: Sun Microsystems Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Notes/Tuning Information (Continued)

```

176.gcc: -fast -xipo=2 -Wc,-Qicache-chbab=1 -Wc,-Qeps:enabled=1
        -Qeps:ws=32 -Wc,-Qdepgraph-early_cross_call=1
        -Wc,-Qms_pipe-pref_prolog -ll2amm +FDO
181.mcf: -fast -xipo=2 -xprefetch_level=2
186.crafty: -fast -xpagesize=8k -xipo=2 -xalias_level=strong
        -W2,-Ashort_ldst -xinline= -xprefetch -xrestrict
        +FDO (-xlinkopt during pass2)
197.parser: -fast -xipo=2 -xalias_level=strong -Wc,Qgsched-T6
        -Wc,-Qipa:valueprediction -Wc,-Qms_pipe-prefstrong=0,
        -Qlp-pt=weak +FDO
252.eon: -fast -xipo=2 -xalias_level=compatible -Qoption cg
        -Qeps:enabled=1 -xvector -Qoption iropt -Abcopy -xunroll=16
        +FDO
253.perlbnk: -fast -xipo -Wc,-Qeps:enabled=1,-Qeps:ws=16 -xalias_level=std
        -xsafe=mem -Wc,-Qiselect-funcalign=128,-Qicache-chbab=1
        -Wc,-Qiselect-sw_pf_tbl_th=40,-Qeps:do_spec_load=1 +FDO
254.gap: -fast -W2,-Abcopy -xvector -xprefetch_level=3 +FDO
255.vortex: -fast -xrestrict -xipo=2 -Wc,-Qeps:enabled=1
        -W2,-Ainline:recursion=1:cs=400:irs=5000
        -Wc,-Qdepgraph-early_cross_call=1 -Wc,-Qiselect-funcalign=64
        -Wc,-Qpeep-Sh0 -W2,-crit -xprefetch=latx:1.7 -fsimple=1
        -Wc,-Qiselect-sw_pf_tbl_th=30 -Wc,-Qicache-chbab=1
        -W2,-Ainline:inc=300 -ll2amm +FDO
256.bzip2: -fast -xipo=2 -xalias_level=strong -xrestrict
        -Wc,-Qeps:enabled=1,-Qeps:do_spec_load=1 +FDO
300.twolf: -fast -xalias_level=strong -xsafe=mem -xipo=2
        -xprefetch=no%auto -Wc,-Qms_pipe+intdivusefp -xinline= +FDO

```

Feedback is done as follows, unless otherwise noted:

```

fdo_pre0:  rm -rf ./feedback.profile ./SunWS_cache
PASS1:    -xprofile=collect:./feedback
PASS2:    -xprofile=use:./feedback

```

Portability:

```

176.gcc:  -Dalloca=__builtin_alloca -DHOST_WORDS_BIG_ENDIAN
186.crafty: -DSUN
252.eon:   -DFMAX_IS_DOUBLE -library=iostream
253.perlbnk: -DSPEC_CPU2000_SOLARIS
254.gap:   -DSYS_IS_USG -DSYS_HAS_TIME_PROTO -DSYS_HAS_SIGNAL_PROTO
        -DSYS_HAS_CALLOC_PROTO -DSYS_HAS_IOCTL_PROTO

```

Shell Environments:

```

Stack size set to unlimited via "ulimit -s unlimited"
MPSSHEAP=4M
MPSSSTACK=4M
LD_PRELOAD=mpss.so.1

```

Kernel Parameters (/etc/system):

```

autoup=900
tune_t_fsflushr=1

```

The system was configured with multiple file systems.

The O/S was installed on one disk of the Sun StorEdge D240 Media Tray (ufs, ufs w/logging). The benchmark was run on the Sun StorEdge 6120 Array, using H/W Raid 5 and ufs with ufs logging file system.



CINT2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire E20K (32 processor)

SPECint_rate2000 = 660

SPECint_rate_base2000 = 554

SPEC license #: 6 Tested by: Sun Microsystems Test date: Nov-2005 Hardware Avail: Oct-2005 Software Avail: Nov-2005

Notes/Tuning Information (Continued)