



# CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

## IBM Corporation

IBM System X 3500 (1.86 GHz Xeon 5120, 4MB L2 Cache)

SPECfp2000 = --

SPECfp\_base2000 = 1837

SPEC license #: 11 | Tested by: IBM Corporation | Test date: Jul-2006 | Hardware Avail: Jul-2006 | Software Avail: Mar-2006

Benchmark	Reference Time	Base Runtime	Base Ratio	Runtime	Ratio
168.wupwise	1600	62.5	2561		
171.swim	3100	141	2201		
172.mgrid	1800	151	1194		
173.applu	2100	151	1386		
177.mesa	1400	78.0	1796		
178.galgel	2900	63.9	4540		
179.art	2600	40.1	6477		
183.earth	1300	57.4	2266		
187.facerec	1900	104	1821		
188.amp	2200	164	1344		
189.lucas	2000	126	1590		
191.fma3d	2100	154	1367		
200.sixtrack	1100	147	747		
301.apsi	2600	232	1122		

### Hardware

CPU: Intel Xeon processor 5120 ( 1.86 GHz, 1066 MHz bus)  
 CPU MHz: 1866  
 FPU: Integrated  
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip  
 CPU(s) orderable: 1, 2  
 Parallel: No  
 Primary Cache: 32KB(I) + 32KB(D) on chip (per core)  
 Secondary Cache: 4096KB(I+D) on chip (per chip)  
 L3 Cache: N/A  
 Other Cache: N/A  
 Memory: 8 x 1024 MB ECC PC2-5300F  
 Disk Subsystem: 80GB SATA 10K RPM  
 Other Hardware:

### Software

Operating System: Windows Server 2003 Enterprise Edition (32-bit)  
 Compiler: Intel C++ and Fortran Compiler 9.1 for 32-bit applications  
 Build 20060323Z  
 Microsoft Visual Studio 2005(for libraries)  
 SmartHeap Library Version 8.0 from <http://www.microquill.com/>  
 File System: NTFS  
 System State: Default

## Notes/Tuning Information

```
+FDO: PASS1= -Qprof_gen PASS2=-Qprof_use
Base tuning for Fortran programs: -fast -Qansi_alias +FDO
Base tuning for C programs: -fast +FDO shlw32M.lib
Portability:
178.galgel: -FI /F32000000
```

This result was measured on an IBM System X 3400. IBM System X 3500 and IBM System X 3400 are electronically equivalent.