



CFP2000 Result

Copyright ©1999-2005, Standard Performance Evaluation Corporation

Itaotec

Servidor Itaotec MX221 (Intel Xeon X5355 processor)

SPECfp_rate2000 = 91.1

SPECfp_rate_base2000 = 91.1

SPEC license #: 9001 | Tested by: Itaotec | Test date: Nov-2006 | Hardware Avail: Jan-2007 | Software Avail: May-2006

Benchmark	Base Copies	Base Runtime	Base Ratio	Copies	Runtime	Ratio
168.wupwise	8	136	109	8	136	109
171.swim	8	620	46.4	8	620	46.4
172.mgrid	8	380	43.9	8	380	43.9
173.applu	8	478	40.8	8	478	40.8
177.mesa	8	59.6	218	8	59.6	218
178.galgel	8	91.2	295	8	91.2	295
179.art	8	100	240	8	100	240
183.equake	8	173	69.8	8	173	69.8
187.facerec	8	164	107	8	164	107
188.amp	8	180	113	8	180	113
189.lucas	8	400	46.4	8	400	46.4
191.fma3d	8	327	59.6	8	327	59.6
200.sixtrack	8	107	95.3	8	107	95.3
301.apsi	8	278	86.9	8	278	86.9

Hardware

CPU: Intel Xeon X5355 processor (2.66 GHz, 2x4MB L2, 1333 MHz system bus)
 CPU MHz: 2660
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2
 Parallel: No
 Primary Cache: 32KB(I) + 32KB(D) on chip, per core
 Secondary Cache: 8MB (I+D) on chip, per chip (4MB shared per 2 cores)
 L3 Cache: N/A
 Other Cache: N/A
 Memory: 16GB (8x2GB DDR2-RAM PC2-5300 FB-DIMM CL5 ECC)
 Disk Subsystem: 1 x 120GB Serial ATA 7200 RPM
 Other Hardware: None

Software

Operating System: Windows Server 2003 Enterprise Edition + SP1 (32-bit)
 Compiler: Intel C++ Compiler 9.1
 Build 20060519Z (for 32-bit applications),
 Intel Fortran Compiler 9.1
 Build 20060323Z (for 32-bit applications),
 Microsoft Visual Studio 2005 (for libraries),
 MicroQuill SmartHeap for SMP Library v.8.0
 File System: NTFS
 System State: Default

Notes/Tuning Information

PORTABILITY FLAGS

178.galgel: -FI /F32000000

GENERAL

+FDO: PASS1=-Qprof_gen PASS2=-Qprof_use

Base tuning flags

for Fortran programs: -fast -Qansi_alias +FDO
for C programs: -fast +FDO shlsmpmt.lib

EXTRA LIBRARIES

MicroQuill SmartHeap for SMP Library v.8.0
<http://www.microquill.com>

BIOS settings: Adjacent Sector Prefetch = disable
The system bus runs at 1333 MHz

This result was measured with 32-bit binaries using the 32-bit version of the operating system.